CONSUMER DATA BOOK 2026



YOKOHAMA

Yokohama Tire Corporation is the North American arm of Yokohama Rubber Co. Ltd., a global manufacturer of premium tires since 1917.

Headquartered in Southern California, we are honored to be ranked among the most elite tire manufacturers in the world, engineering products for passenger cars and commercial trucks. With our plant in Mississippi and production facility in Virginia, we proudly make many of our products right here in the USA.

Yokohama has always been synonymous with advanced tire technology. Our core focus on technological advancements has enabled us to pioneer numerous groundbreaking innovations and industry firsts. We were the first to introduce asymmetric tread design to the United States and the first to engineer products using nanotechnology.

We are continually committed to leveraging our technological strength to improve tire performance, and we are always dedicated to environmental protection.



YOKOHAMA®

CONTENTS

4 **Product Families**
5 **Performance Continuums**
6 **Programs**
7 **Definitions**

REPLACEMENT

ADVAN

8 ADVAN® A055
9 ADVAN A052®
11 ADVAN Neova® AD09
13 ADVAN Sport® V107
15 ADVAN Apex® V601
17 ADVAN Sport ZPS®
18 ADVAN Fleva® V701
19 ADVAN Sport® EV A/S
20 ADVAN Sport® A/S+

AVID

22 AVID ENVigor® ZPS
23 AVID Ascend GT®
25 AVID Ascend LX®
27 AVID Touring-S®

GEOLANDAR

28 GEOLANDAR X-MT®
29 GEOLANDAR M/T® G003
31 GEOLANDAR M/T® G003 SxS
32 GEOLANDAR A/T XD®
33 GEOLANDAR X-AT®
35 GEOLANDAR A/T4®
38 GEOLANDAR® A/T G015
39 GEOLANDAR H/T4™
41 GEOLANDAR® H/T G056
43 GEOLANDAR CV 4S®
45 GEOLANDAR CV® G058
46 GEOLANDAR X-CV®

PARADA

48 PARADA Spec-X®

BLUEARTH

49 BluEarth-Van All Season® RY61
50 BluEarth Winter® V906
51 BluEarth Winter® V906 SUV
52 BluEarth Winter® V905

ICEGUARD

53 iceGUARD® iG53
54 iceGUARD® G075
56 iceGUARD® iG51v

YOKOHAMA®

PRODUCT FAMILIES

From commuting in the family sedan to taking on the trail in your 4x4, there's a Yokohama that's perfect for everyone

ADVAN® FAMILY
Everything we've learned from engineering tires for the racetrack has been rolled into our line of ultra-high performance products.

AVID® FAMILY
Innovation for the everyday. Our line of AVID products offers reliable all-season performance, superior comfort, and most importantly: they're built to last.

GEOLANDAR® FAMILY
Tough, durable and long-lasting, these tires are built for wherever life takes you. On-road or off, there's a GEOLANDAR perfect for your truck, SUV or crossover.

WINTER PRODUCTS
Winter driving can be unpredictable, which is why we've built advanced traction technologies into each of our winter tires.

BLUEARTH® PRODUCTS
BluEarth is an ecologically-friendly series of tires from Yokohama that pursues the highest standards of performance, while striving to protect the global environment

YOKOHAMA TIRE PERFORMANCE CONTINUUMS



PROGRAMS



The 4 Performance Program assists dealers in fulfilling the needs of customers who are looking to purchase ultra-high performance tires. Direct Dealers can place orders for up to four (4) units of the following eligible tires: ADVAN Apex®, ADVAN FLEVA® V701, ADVAN Sport® V105, ADVAN Sport ZPS®, ADVAN Neova® AD08R, ADVAN Sport® A/S+, ADVAN A052®, ADVAN Sport® V107 and ADVAN Neova® AD09. A $15.00 per tire freight charge will be applied at the time the order is placed. Shipments under this program can be delivered to any authorized ship-to location or authorized drop-ship location. Please clarify at the time of order that your tires qualify under the 4 Performance Program.

The O.E. Ship Three Program allows dealers to service Yokohama customers who are trying to match the O.E. tires on their car. Direct Dealers are eligible to receive up to three (3) tires of a designated O.E. part number, freight prepaid within 72 hours. To place an order, Direct Dealers should contact their Yokohama Customer Service Representative and identify the order as an O.E. Ship Three. A fee of $15.00 per eligible tire will be applied and the order will then be shipped and should be received within 72 hours.





Yokohama's Performance Promise guarantees customers will be happy with their new tires. If within 30 days they are not completely satisfied, tires can be returned to the dealership of purchase along with the original sales receipt and Yokohama will refund the full purchase price. Offer applies only to the original purchased set of four (select) Yokohama tires. See Yokohama Warranty Claims Procedure Manual for details.

M+S

This mark is commonly found on “all season” tires. In several formats, the letters “M” and “S” indicate the tire is intended for limited mud and snow service. Other formats include: “MS,” “M/S,” or “M&S.”

This mark is commonly found on dedicated winter/snow tires. Tires that meet the USTMA definition for passenger and light truck tires for use in severe snow conditions are marked on at least one sidewall with the letters “M” and “S” plus a pictograph of a mountain with a snowflake, as shown here.



LEGEND		
Sidewall	BW	Blackwall
	OWL	Outlined White Letters
Load Index	SL	Standard Load
	XL	Extra Load or Reinforced Load
UTQG	Treadwear/Traction/Temperature	

ADVAN A055

SUMMER **Performance Cars | Competition**

Built specifically for on-track racing with competitive performance and fast lap times.



FEATURES AND BENEFITS

MAXIMUM GRIP
Alternating twin grooves maximize the contact patch while an advanced motorsport compound provides outstanding dry grip on track.

ULTIMATE HANDLING
Aggressive motorsport construction provides ultimate handling on the track.

CONSISTENT PERFORMANCE
Profile contour delivers consistent contact with the track surface.

RACE READY
Engineered to dominate in sanctioned racing categories requiring a DOT tire.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/50R15 86W	110115501	SL	40/C/A	17.8	6.5	5.5 - 7.5	8.5	23.1	8	4	10.6	900	1168@51	-	BW
225/45R16 89W	110115502	SL	40/C/A	18.9	7.5	7.5 - 8.5	9	23.9	8.3	4	11.1	869	1279@51	-	BW
245/40R17 91W	110115503	SL	40/C/A	20.5	8.5	8.0 - 9.5	9.9	24.7	9.2	4	11.5	841	1356@51	-	BW
255/40R17 94W	110115504	SL	40/C/A	21.5	9	8.5 - 10.0	10.3	25.2	9.6	4	11.7	826	1477@51	-	BW
275/40R17 98W	110115505	SL	40/C/A	23.2	9.5	9.5 - 11.0	10.9	25.7	10.3	4	11.9	808	1653@51	-	BW
245/40R18 93W	110115506	SL	40/C/A	21.6	8.5	8.0 - 9.5	9.9	25.8	9.2	4	12	807	1433@51	-	BW
275/35R18 95W	110115507	SL	40/C/A	22.4	9.5	9.0 - 11.0	10.9	25.6	10.3	4	11.9	813	1521@51	-	BW

ADVAN A052®

SUMMER **Performance Cars | Competition**

Nothing rewards your passion for extreme grip and high speeds like the race-ready ADVAN A052.



FEATURES AND BENEFITS

ULTIMATE HANDLING
Ultra-high turn up and lower belt angle for ultimate handling on and off the track.

MAXIMUM GRIP
Dedicated motorsports-inspired compound for maximum wet and dry grip on and off the track.

RACE READY
Engineered to dominate in sanctioned competition categories requiring a 200 UTQG tire.

CONSISTENT PERFORMANCE
Tread design delivers consistent contact to the road while minimizing localized heat.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
	110115247			30.4										-	BW
	110115246			30.1										-	BW
185/55R14 80V	110105285	SL	200/A/A	15.2	6	5.0 - 6.5	7.6	22	6.7	7	10.1	945	992@51	-	BW
195/50R15 86V	110105269	XL	200/A/A	17.2	6	5.5 - 7.0	8	22.6	7.2	7	10.5	917	1169@50	-	BW
195/55R15 89V	110105270	XL	200/A/A	18.1	6	5.5 - 7.0	8	23.4	7.2	7	10.7	890	1279@50	-	BW
205/50R15 89V	110105271	XL	200/A/A	18.7	6.5	5.5 - 7.5	8.5	23	7.6	7	10.6	902	1279@50	-	BW
225/50R15 95V	110105272	XL	200/A/A	20.3	7	6.0 - 8.0	9.2	23.9	8.3	7	11	869	1521@50	-	BW
195/45R16 84W	110105273	XL	200/A/A	17	6.5	6.0 - 7.5	7.8	22.8	7	7	10.7	911	1103@50	-	BW
195/50R16 88W	110105274	XL	200/A/A	18.5	6	5.5 - 7.0	7.9	23.6	7.2	7	11	879	1235@50	-	BW
205/50R16 91W	110115220	XL	200/A/A	19.6	6.5	5.5 - 7.5	8.4	24.2	7.6	7	11.2	858	1356@50	-	BW
205/55R16 94W	110115221	XL	200/A/A	20.9	6.5	5.5 - 7.5	8.4	25	7.6	7	11.5	831	1477@50	-	BW
225/45R16 93W	110115223	XL	200/A/A	19.8	7.5	7.0 - 8.5	8.9	24.1	8.3	7	11.1	863	1433@50	-	BW
225/50R16 96W	110115222	XL	200/A/A	21.6	7	6.0 - 8.0	9.1	25	8.3	7	11.5	831	1566@50	-	BW
245/45R16 94W	110105275	SL	200/A/A	21.4	8	7.5 - 9.0	9.8	24.6	8.9	7	11.3	845	1477@51	-	BW
205/40R17 84W	110105276	XL	200/A/A	18.5	7.5	7.0 - 8.0	8.5	23.4	7.6	7	11	888	1103@50	-	BW
205/45R17 88W	110115224	XL	200/A/A	19.4	7	6.5 - 7.5	8.2	24.3	7.6	7	11.4	854	1235@50	-	BW
215/40R17 87W	110105277	XL	200/A/A	19.6	7.5	7.0 - 8.5	8.8	23.7	8	7	11.1	878	1202@50	-	BW
215/45R17 91W	110115206	XL	200/A/A	20.3	7	7.0 - 8.0	8.4	24.7	7.8	7	11.5	840	1356@50	-	BW
225/45R17 94W	110115207	XL	200/A/A	20.9	7.5	7.0 - 8.5	8.9	25.1	8.3	7	11.7	828	1477@50	-	BW
235/45R17 97W	110115208	XL	200/A/A	22.3	8	7.5 - 9.0	9.3	25.5	8.7	7	11.8	815	1610@50	-	BW
245/40R17 95W	110105278	XL	200/A/A	22.1	8.5	8.0 - 9.5	9.9	24.7	9.2	7	11.5	840	1521@50	-	BW
255/40R17 98W	110115209	XL	200/A/A	19.4	9	8.5 - 10.0	10.3	25.2	9.6	7	11.7	826	1654@50	-	BW
225/35R18 87Y	110105279	XL	200/A/A	20.7	8	7.5 - 9.0	9.1	24.2	8.4	7	11.4	859	1202@50	-	BW
225/40R18 92Y	110115210	XL	200/A/A	21.6	8	8.5 - 10.0	9.1	25.1	8.4	7	11.8	827	1389@50	-	BW
235/40R18 95Y	110115211	XL	200/A/A	22.7	8.5	8.0 - 9.5	9.5	25.5	8.8	7	11.9	815	1521@50	-	BW
235/45R18 98Y	110105280	XL	200/A/A	24	8	7.5 - 9.0	9.5	26.3	8.7	7	12.2	789	1654@50	-	BW
245/40R18 97Y	110115212	XL	200/A/A	24	8.5	8.0 - 9.5	9.8	25.8	9.2	7	12	805	1610@50	-	BW
255/35R18 94Y	110115213	XL	200/A/A	23.6	9	8.5 - 10.0	10.2	25.1	9.6	7	11.8	828	1477@50	-	BW
255/40R18 99Y	110115214	XL	200/A/A	24.9	9	8.5 - 10.0	10.3	26.1	9.6	7	12.2	795	1709@50	-	BW
265/35R18 97Y	110115215	XL	200/A/A	24.5	9.5	9.0 - 10.5	10.6	25.4	10	7	11.9	818	1610@50	-	BW
265/40R18 101Y	110115216	XL	200/A/A	25.6	9.5	9.0 - 10.5	10.7	26.5	10	7	12.3	785	1819@50	-	BW
265/45R18 104Y	110105281	XL	200/A/A	26.7	9	8.5 - 10.0	10.6	27.4	9.7	7	12.7	757	1985@50	-	BW
275/40R18 103Y	110105282	XL	200/A/A	26.2	9.5	9.0 - 11.0	11	26.7	10.3	7	12.4	778	1929@50	-	BW
295/30R18 98Y	110115217	XL	200/A/A	26.2	10.5	10.0 - 11.0	11.8	25.1	11.2	7	11.8	828	1654@50	-	BW
295/35R18 103Y	110115218	XL	200/A/A	27.6	10.5	10.0 - 11.5	11.8	26.2	11.2	7	12.2	792	1929@50	-	BW
315/30R18 98Y	110115219	SL	200/A/A	28	11	10.5 - 11.5	12.6	25.6	12	7	11.9	813	1654@51	-	BW
235/40ZR19 (96Y)	110115229	XL	200/A/A	24	8.5	8.0 - 9.5	9.5	26.4	8.8	7	12.4	786	1565@50	-	BW
245/35ZR19 93Y	110115225	XL	200/A/A	23.4	8.5	8.0 - 9.5	9.7	25.7	9.1	7	12.1	807	1433@50	-	BW

ADVAN A052®

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
255/35ZR19 (96Y)	110115227	XL	200/A/A	24.8	9	8.5 - 10.0	10.2	26	9.6	7	12.2	799	1565@50	-	BW
265/40ZR19 (102Y)	110115228	XL	200/A/A	26.8	9.5	9.0 - 10.5	10.6	27.4	10	7	12.8	757	1874@50	-	BW
275/35ZR19 (100Y)	110115226	XL	200/A/A	25.9	9.5	9.0 - 11.0	10.8	26.6	10.3	7	12.5	781	1764@50	-	BW
295/35R19 104Y	110115233	XL	200/A/A	29.6	10.5	10.0 - 11.5	11.8	27.2	11.2	7	12.7	765	1984@50	-	BW
245/30ZR20 (90Y)	110115231	XL	200/A/A	23	8.5	8.0 - 9.0	9.6	25.8	9.1	7	12.3	804	1323@50	-	BW
245/35ZR20 (95Y)	110115232	XL	200/A/A	24.7	8.5	8.0 - 9.5	9.6	26.8	9.1	7	12.6	776	1521@50	-	BW
255/40ZR20 101Y	110105283	XL	200/A/A	26.7	9	8.5 - 10.0	10.4	27.9	9.6	7	13.1	745	1819@50	-	BW
285/35ZR20 104Y	110105284	XL	200/A/A	29.1	10	9.5 - 11.0	11.6	28	10.9	7	13.1	743	1985@50	-	BW
295/30R20 101Y	110115230	XL	200/A/A	28.5	10.5	10.0 - 11.0	11.7	27	11.2	7	12.7	768	1819@50	-	BW

ADVAN NEOVA® AD09

SATISFACTION 4 PERFORMANCE PROGRAM 30 DAY TRIAL GUARANTEED

SUMMER **Performance Cars**

Our newest street legal sports tire delivers ultra-high performance on the street and at the track.



FEATURES AND BENEFITS

OUTSTANDING DRY GRIP
Maximized road contact for faster lap times.

PRECISION HANDLING
Fast and responsive handling for street or track.

CONSISTENT PERFORMANCE
Lap times stay fast throughout the life of the tire.

IMPROVED WET GRIP
High silica compound for powerful grip in wet conditions.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/50R15 86V	110111905	SL	200/AA/A	19	6.5	5.5 - 7.5	8.4	23	7.7	8	10.6	904	1168@51	-	BW
205/45R16 87W	110111908	XL	200/AA/A	19.4	7	6.5 - 7.5	8.1	23.1	7.5	8	10.8	899	1201@50	-	BW
205/50R16 87V	110111909	SL	200/AA/A	18.8	6.5	5.5 - 7.5	8.5	24.1	7.7	8	11.2	862	1201@51	-	BW
205/55R16 91V	110111910	SL	200/AA/A	19.1	6.5	5.5 - 7.5	8.5	24.8	7.7	8	11.4	836	1356@51	-	BW
225/50R16 92V	110111913	SL	200/AA/A	23.7	7	6.0 - 8.0	9.1	24.8	8.4	8	11.4	838	1389@51	-	BW
205/45R17 88W	110111916	XL	200/AA/A	21.4	7	6.5 - 7.5	8.1	24.2	7.5	8	11.3	858	1235@50	-	BW
205/50R17 89W	110111917	SL	200/AA/A	23.2	6.5	5.5 - 7.5	8.4	25.1	7.7	8	11.7	828	1279@51	-	BW
215/40R17 87W	110111918	XL	200/AA/A	21.5	7.5	7.0 - 8.5	8.6	23.8	8	8	11.1	874	1201@50	-	BW
215/45R17 91W	110111919	XL	200/AA/A	22	7	7.0 - 8.0	8.3	24.6	7.7	8	11.5	843	1356@50	-	BW
225/45R17 94W	110111920	XL	200/AA/A	23.6	7.5	7.0 - 8.5	8.7	25	8.1	8	11.6	832	1477@50	-	BW
225/50R17 98W	110111921	XL	200/AA/A	25.6	7	6.0 - 8.0	9.1	25.9	8.4	8	12	802	1653@50	-	BW
235/45R17 94W	110111923	SL	200/AA/A	24.7	8	7.5 - 9.0	9.3	25.3	8.5	8	11.7	822	1477@51	-	BW
245/40R17 91W	110111924	SL	200/AA/A	25.6	8.5	8.0 - 9.5	9.7	24.7	9	8	11.5	840	1356@51	-	BW
245/45R17 95W	110111925	SL	200/AA/A	26.3	8	7.5 - 9.0	9.5	25.7	8.7	8	11.9	809	1521@51	-	BW
255/40R17 98W	110111914	XL	200/AA/A	25.5	9	8.5 - 10.0	10.1	25	9.4	8	11.6	830	1653@50	-	BW
225/40R18 92W	110111930	XL	200/AA/A	23.4	8	7.5 - 9.0	9	25.1	8.3	8	11.8	828	1389@50	-	BW
225/45R18 95W	110111931	XL	200/AA/A	24.6	7.5	7.0 - 8.5	8.8	25.9	8.1	8	12.1	802	1521@50	-	BW
235/40R18 95W	110111932	XL	200/AA/A	24.5	8.5	8.0 - 9.5	9.4	25.4	8.7	8	11.9	819	1521@50	-	BW
245/35R18 92W	110111933	XL	200/AA/A	24.5	8.5	8.0 - 9.5	9.6	24.8	9	8	11.6	839	1389@50	-	BW
245/40R18 97W	110111934	XL	200/AA/A	26.1	8.5	8.0 - 9.5	9.6	25.8	9	8	12.1	804	1609@50	-	BW
245/45R18 100W	110111935	XL	200/AA/A	26.3	8	7.5 - 9.0	9.5	26.7	8.7	8	12.4	779	1764@50	-	BW
255/35R18 94W	110111937	XL	200/AA/A	25.4	9	8.5 - 10.0	10.1	25	9.4	8	11.7	832	1477@50	-	BW
255/40R18 99W	110111927	XL	200/AA/A	27.2	9	8.5 - 10.0	10.3	26	9.3	8	12.1	798	1709@50	-	BW
265/35R18 97W	110111938	XL	200/AA/A	27.1	9.5	9.0 - 10.5	10.6	25.3	9.8	8	11.9	821	1609@50	-	BW
265/40R18 101W	110111939	XL	200/AA/A	27.7	9.5	9.0 - 10.5	10.7	26.3	9.8	8	12.2	790	1819@50	-	BW
275/40R18 103W	110111940	XL	200/AA/A	29.8	9.5	9.0 - 11.0	10.9	26.6	10	8	12.3	782	1929@50	-	BW
285/30R18 97W	110111941	XL	200/AA/A	27	10	9.5 - 10.5	11.1	24.8	10.5	8	11.6	839	1609@50	-	BW
295/30R18 98W	110111942	XL	200/AA/A	28.9	10.5	10.0 - 11.0	11.6	25	10.8	8	11.7	830	1653@50	-	BW
295/35R18 103W	110111943	XL	200/AA/A	30	10.5	10.0 - 11.5	11.7	26.1	10.8	8	12.2	795	1929@50	-	BW
225/35R19 88W	110111945	XL	200/AA/A	25.3	8	7.5 - 9.0	9	25.3	8.3	8	12	821	1235@50	-	BW
225/40R19 93W	110111946	XL	200/AA/A	24.1	8	7.5 - 9.0	8.9	26.1	8.3	8	12.3	797	1433@50	-	BW
235/35R19 91W	110111947	XL	200/AA/A	24.1	8.5	8.0 - 9.5	9.4	25.5	8.7	8	12	816	1356@50	-	BW
235/40R19 96W	110111948	XL	200/AA/A	25.6	8.5	8.0 - 9.5	9.4	26.5	8.7	8	12.4	785	1565@50	-	BW
245/35R19 93W	110111949	XL	200/AA/A	26	8.5	8.0 - 9.5	9.6	25.9	9	8	12.2	803	1433@50	-	BW
245/40R19 98W	110111950	XL	200/AA/A	26.9	8.5	8.0 - 9.5	9.7	26.7	9	8	12.5	777	1653@50	-	BW
255/30R19 91W	110111951	XL	200/AA/A	24.2	9	8.5 - 9.5	10.1	25.1	9.4	8	11.9	828	1356@50	-	BW
255/35R19 96W	110111952	XL	200/AA/A	27.8	9	8.5 - 10.0	10	26.1	9.3	8	12.3	797	1565@50	-	BW
255/40R19 100W	110111953	XL	200/AA/A	27.8	9	8.5 - 10.0	10.1	27	9.4	8	12.6	768	1764@50	-	BW

ADVAN NEOVA®

AD09

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
265/35R19 98W	110111955	XL	200/AA/A	26.4	9.5	9.0 - 10.5	10.6	26.4	9.8	8	12.4	788	1653@50	-	BW
275/35R19 100W	110111958	XL	200/AA/A	29.7	9.5	9.0 - 11.0	10.7	26.6	10	8	12.5	781	1764@50	-	BW
275/40R19 105W	110111959	XL	200/AA/A	31.2	9.5	9.0 - 11.0	10.9	27.6	10	8	12.9	753	2039@50	-	BW
285/35R19 103W	110111960	XL	200/AA/A	29.7	10	9.5 - 11.0	11.3	26.8	10.5	8	12.5	775	1929@50	-	BW
295/30R19 100W	110111944	XL	200/AA/A	29.7	10.5	10.0 - 11.0	11.6	26.1	10.8	8	12.3	797	1764@50	-	BW
305/30R19 102W	110111961	XL	200/AA/A	30.7	11	10.5 - 11.5	12.2	26.3	11.3	8	12.3	791	1874@50	-	BW
325/30R19 105W	110111962	XL	200/AA/A	32.8	11.5	11.0 - 12.0	12.8	26.8	11.9	8	12.5	776	2039@50	-	BW
235/35R20 92W	110111963	XL	200/AA/A	25.3	8.5	8.0 - 9.5	9.4	26.5	8.7	8	12.5	784	1389@50	-	BW
245/30R20 90W	110111964	XL	200/AA/A	25.4	8.5	8.0 - 9.0	9.6	25.8	9	8	12.3	804	1323@50	-	BW
245/35R20 95W	110111965	XL	200/AA/A	26.9	8.5	8.0 - 9.5	9.6	26.8	9	8	12.7	775	1521@50	-	BW
245/40R20 99W	110111966	XL	200/AA/A	28	8.5	8.0 - 9.5	9.6	27.8	9	8	13	748	1709@50	-	BW
255/35R20 97W	110111967	XL	200/AA/A	28	9	8.5 - 10.0	10.1	27	9.4	8	12.7	768	1609@50	-	BW
255/40R20 101W	110111968	XL	200/AA/A	29.5	9	8.5 - 10.0	10	28.1	9.4	8	13.2	738	1819@50	-	BW
265/30R20 94W	110111969	XL	200/AA/A	27.3	9.5	9.0 - 10.0	10.6	26.3	9.8	8	12.5	790	1477@50	-	BW
265/35R20 99W	110111970	XL	200/AA/A	29.4	9.5	9.0 - 10.5	10.5	27.3	9.8	8	12.9	760	1709@50	-	BW
275/30R20 97W	110111971	XL	200/AA/A	27.8	9.5	9.0 - 10.0	10.7	26.6	10	8	12.6	782	1609@50	-	BW
275/35R20 102W	110111972	XL	200/AA/A	30.9	9.5	9.0 - 11.0	10.7	27.7	10	8	13	750	1874@50	-	BW
285/30R20 99W	110111973	XL	200/AA/A	29.6	10	9.5 - 10.5	11.2	26.9	10.5	8	12.7	774	1709@50	-	BW
285/35R20 104W	110111974	XL	200/AA/A	31.2	10	9.5 - 11.0	11.3	27.9	10.5	8	13.1	744	1984@50	-	BW
295/30R20 101W	110111975	XL	200/AA/A	30.3	10.5	10.0 - 11.0	11.7	27	10.8	8	12.7	769	1819@50	-	BW
295/35R20 105W	110111976	XL	200/AA/A	32.4	10.5	10.0 - 11.5	11.8	28.1	10.8	8	13.2	739	2039@50	-	BW
305/30R20 103W	110111977	XL	200/AA/A	31.9	11	10.5 - 11.5	12.1	27.2	11.3	8	12.8	763	1929@50	-	BW
335/30R20 108W	110111978	XL	200/AA/A	31.9	12	11.5 - 12.5	13.4	27.8	12.4	8	13.1	746	2205@50	-	BW
295/25R21 96W	110111983	XL	200/AA/A	28.9	10.5	10.0 - 11.0	11.5	26.8	10.8	8	12.8	776	1565@50	-	BW
305/30R21 104W	110111979	XL	200/AA/A	33.2	11	10.5 - 11.5	12	28.3	11.3	8	13.3	735	1984@50	-	BW
325/30R21 108W	110111980	XL	200/AA/A	35.6	11.5	11.0 - 12.0	12.7	28.7	11.9	8	13.5	723	2205@50	-	BW

ADVAN Sport® V107

SATISFACTION 30 DAY TRIAL GUARANTEED

SUMMER **Performance Cars | Crossovers/SUVs**

With a new compound and construction, the ADVAN Sport® V107 is built to provide drivers of high-performance sedans, CUVs and SUVs with confident performance and handling.



FEATURES AND BENEFITS

OUTSTANDING GRIP
Ultra-microsilica compound and asymmetrical tread provide excellent grip in dry and wet.

RESPONSIVE HANDLING
Rayon matrix body ply and solid center ribs provide precise steering and cornering.

HIGH SPEED STABILITY
Improved contour profile creates an expanded contact patchfor enhanced stability at high speeds.

QUIET RIDE
Specially designed sipes provide a quiet ride.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/40ZR18 92Y	110110710	XL	240/AA/A	21.4	8	7.5 - 9.0	9	25.1	8.2	9	11.8	827	1389@50	-	BW
225/45ZR18 95Y	110110711	XL	240/AA/A	23.1	7.5	7.0 - 8.5	8.8	26	7.9	8	12.1	798	1521@50	-	BW
235/40ZR18 (95Y)	110110712	XL	240/AA/A	23.4	8.5	8.0 - 9.5	9.4	25.5	8.6	9	11.9	816	1521@50	-	BW
235/45ZR18 (98Y)	110110770	XL	240/AA/A	24.5	8	7.5 - 9.0	9.2	26.3	8.3	9	12.2	791	1653@50	-	BW
245/35ZR18 (92Y)	110110771	XL	240/AA/A	22.3	8.5	8.0 - 9.5	9.7	24.7	8.7	9	11.6	842	1389@50	-	BW
245/40ZR18 (97Y)	110110713	XL	240/AA/A	23.6	8.5	8.0 - 9.5	9.6	25.7	8.7	9	12	808	1609@50	-	BW
245/45ZR18 100Y	110110714	XL	240/AA/A	25.1	8	7.5 - 9.0	9.4	26.6	8.6	9	12.4	781	1764@50	-	BW
255/35ZR18 94Y	110110715	XL	240/AA/A	23.8	9	8.5 - 10.0	10.1	25	9.2	9	11.7	831	1477@50	-	BW
255/40ZR18 (99Y)	110110716	XL	240/AA/A	25.8	9	8.5 - 10.0	10.1	26	9.2	9	12.1	799	1709@50	-	BW
255/45ZR18 (103Y)	110110772	XL	240/AA/A	26.5	8.5	8.0 - 9.5	10	27	9	9	12.5	770	1929@50	-	BW
265/35ZR18 (97Y)	110110773	XL	240/AA/A	24.9	9.5	9.0 - 10.5	10.5	25.3	9.7	9	11.8	822	1609@50	-	BW
275/40ZR18 (103Y)	110110717	XL	240/AA/A	27.3	9.5	9.0 - 11.0	10.8	26.5	9.8	9	12.3	783	1929@50	-	BW
225/35ZR19 (88Y)	110110718	XL	240/AA/A	21.4	8	7.5 - 9.0	9.1	25.2	8.2	8	11.9	824	1235@50	-	BW
225/40ZR19 (93Y)	110110719	XL	240/AA/A	22.7	8	7.5 - 9.0	9	26.2	8.2	8	12.3	793	1433@50	-	BW
235/35ZR19 (91Y)	110110720	XL	240/AA/A	22.3	8.5	8.0 - 9.5	9.3	25.5	8.6	9	12	816	1356@50	-	BW
235/40ZR19 (96Y)	110110774	XL	240/AA/A	24	8.5	8.0 - 9.5	9.4	26.4	8.6	9	12.4	786	1565@50	-	BW
235/40ZR19 (92Y)	110110721	SL	240/AA/A	23.8	8.5	8.0 - 9.5	9.6	26.4	8	10	12.4	786	1389@51	-	BW
235/55R19 105Y	110110722	XL	240/AA/A	30	7.5	6.5 - 8.5	9.5	29.3	7.8	9	13.5	709	2039@50	-	BW
245/35ZR19 (93Y)	110110723	XL	240/AA/A	23.6	8.5	8.0 - 9.5	9.6	25.8	8.7	9	12.1	806	1433@50	-	BW
245/40ZR19 (98Y)	110110724	XL	240/AA/A	25.4	8.5	8.0 - 9.5	9.5	26.7	8.7	9	12.5	779	1653@50	-	BW
245/45ZR19 (102Y)	110110725	XL	240/AA/A	26.2	8	7.5 - 9.0	9.4	27.7	8.6	9	12.9	750	1874@50	-	BW
255/30ZR19 (91Y)	110110775	XL	240/AA/A	24.3	9	8.5 - 9.5	10	25	9.2	9	11.8	831	1356@50	-	BW
255/35ZR19 (96Y)	110110726	XL	240/AA/A	25.4	9	8.5 - 10.0	10	26.1	9.2	9	12.3	797	1565@50	-	BW
255/40ZR19 (100Y)	110110727	XL	240/AA/A	26.5	9	8.5 - 10.0	10	27	9.2	9	12.6	768	1764@50	-	BW
255/45ZR19 (104Y)	110110776	XL	240/AA/A	27.6	8.5	8.0 - 9.5	9.9	28	9	9	13	741	1984@50	-	BW
255/50R19 107Y	110110728	XL	240/AA/A	32.6	8	7.0 - 9.0	10.3	29	8.8	9	13.4	716	2149@50	-	BW
255/55R19 111Y	110110729	XL	240/AA/A	34.8	8	7.0 - 9.0	10.5	29.9	8.7	9	13.8	694	2403@50	-	BW
265/35ZR19 (98Y)	110110730	XL	240/AA/A	26.2	9.5	9.0 - 10.5	10.5	26.2	9.7	9	12.3	792	1653@50	-	BW
265/40ZR19 (102Y)	110110731	XL	240/AA/A	27.8	9.5	9.0 - 10.5	10.6	27.3	9.6	9	12.7	760	1874@50	-	BW
275/35ZR19 (100Y)	110110732	XL	240/AA/A	27.1	9.5	9.0 - 11.0	10.8	26.5	9.8	9	12.4	783	1764@50	-	BW
275/40ZR19 (105Y)	110110733	XL	240/AA/A	29.1	9.5	9.0 - 11.0	10.8	27.6	9.8	9	12.8	754	2039@50	-	BW
285/30ZR19 (98Y)	110110734	XL	240/AA/A	27.3	10	9.5 - 10.5	11.3	25.8	10.5	8	12.1	806	1653@50	-	BW
285/40ZR19 (107Y)	110110777	XL	240/AA/A	30.2	10	9.5 - 11.0	11.4	27.8	10.4	9	12.9	746	2149@50	-	BW
225/35ZR20 (90Y)	110110735	XL	240/AA/A	22.5	8	7.5 - 9.0	8.9	26.2	8.2	8	12.4	793	1323@50	-	BW
235/35ZR20 (92Y)	110110736	XL	240/AA/A	23.8	8.5	8.0 - 9.5	9.4	26.4	8.6	9	12.5	786	1389@50	-	BW
235/55R20 105V	110110778	XL	240/AA/A	30.4	7.5	6.5 - 8.5	9.5	30.4	7.8	9	14	684	2039@50	-	BW
245/30ZR20 (90Y)	110110779	XL	240/AA/A	22.7	8.5	8.0 - 9.0	9.6	25.8	8.7	8	12.3	804	1323@50	-	BW
245/35ZR20 (91Y)	110110737	SL	240/AA/A	24.3	8.5	8.0 - 9.5	9.8	26.7	8.2	10	12.6	777	1356@51	-	BW

ADVAN Sport® V107

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
245/35ZR20 (95Y)	110110780	XL	240/AA/A	24.5	8.5	8.0 - 9.5	9.6	26.7	8.7	9	12.6	777	1521@50	-	BW
245/40ZR20 (99Y)	110110738	XL	240/AA/A	26.5	8.5	8.0 - 9.5	9.6	27.8	8.6	9	13	748	1709@50	-	BW
245/45R20 103Y	110110766	XL	240/AA/A	27.1	8	7.5 - 9.0	9.8	28.5	8.2	9	13.3	728	1929@50	-	BW
255/30ZR20 (92Y)	110110739	XL	240/AA/A	25.8	9	8.5 - 9.5	10.1	26.1	9.2	9	12.4	796	1389@50	-	BW
255/35ZR20 (97Y)	110110740	XL	240/AA/A	26.2	9	8.5 - 10.0	10	27	9.2	9	12.7	768	1609@50	-	BW
255/40ZR20 101Y	110110768	XL	240/AA/A	28.2	9	8.5 - 10.0	10.4	28.2	9.1	9	13.2	737	1819@50	-	BW
255/45ZR20 (105Y)	110110781	XL	240/AA/A	28.7	8.5	8.0 - 9.5	10	29.1	9	9	13.5	714	2039@50	-	BW
255/50R20 109Y	110110741	XL	240/AA/A	33.3	8	7.0 - 9.0	10.4	30	8.7	9	13.9	692	2271@50	-	BW
255/55R20 110Y	110110742	XL	240/AA/A	35.3	8	7.0 - 9.0	10.4	30.9	8.7	9	14.3	672	2337@50	-	BW
265/30ZR20 (94Y)	110110743	XL	240/AA/A	25.8	9.5	9.0 - 10.0	10.6	26.3	9.7	9	12.5	790	1477@50	-	BW
265/35ZR20 (99Y)	110110744	XL	240/AA/A	27.8	9.5	9.0 - 10.5	10.5	27.3	9.6	9	12.8	761	1709@50	-	BW
265/45ZR20 108Y	110110782	XL	240/AA/A	32.4	9	8.5 - 10.0	10.5	29.4	9.3	9	13.7	705	2205@50	-	BW
265/50R20 111W	110110783	XL	240/AA/A	35.5	8.5	7.5 - 9.5	10.8	30.6	9.1	9	14.1	679	2403@50	-	BW
275/30ZR20 (97Y)	110110745	XL	240/AA/A	27.1	9.5	9.0 - 10.0	10.7	26.5	9.8	9	12.5	783	1609@50	-	BW
275/35ZR20 (102Y)	110110746	XL	240/AA/A	28.2	9.5	9.0 - 11.0	10.7	27.6	9.8	9	13	753	1874@50	-	BW
275/40ZR20 (106Y)	110110762	XL	240/AA/A	29.8	9.5	9.0 - 11.0	11.1	28.7	9.3	9	13.4	723	2094@50	-	BW
275/45R20 110Y	110110747	XL	240/AA/A	35.1	9	8.5 - 10.5	10.8	29.8	9.8	9	13.8	697	2337@50	-	BW
285/30ZR20 (99Y)	110110784	XL	240/AA/A	28.2	10	9.5 - 10.5	11.1	26.8	10.5	9	12.6	776	1709@50	-	BW
285/35ZR20 (104Y)	110110748	XL	240/AA/A	29.8	10	9.5 - 11.0	11.3	27.9	10.4	9	13.1	745	1984@50	-	BW
285/40R20 108Y	110110767	XL	240/AA/A	31.5	10	9.5 - 11.0	11.7	28.9	9.9	9	13.5	718	2205@50	-	BW
285/45R20 112Y	110110785	XL	240/AA/A	34.2	9.5	9.0 - 10.5	11.2	30	9.9	9	13.9	692	2469@50	-	BW
295/30ZR20 (101Y)	110110749	XL	240/AA/A	29.1	10.5	10.0 - 11.0	11.7	27	10.9	9	12.7	769	1819@50	-	BW
295/35ZR20 (101Y)	110110750	SL	240/AA/A	31.7	10.5	10.0 - 11.5	11.7	28	11	9	13.1	742	1819@51	-	BW
295/35ZR20 105Y	110110769	XL	240/AA/A	31.3	10.5	10.0 - 11.5	12.1	28.1	10.5	9	13.1	740	2039@50	-	BW
295/40ZR20 (110Y)	110110786	XL	240/AA/A	34.6	10.5	10.0 - 11.5	11.8	29.4	10.7	9	13.7	706	2337@50	-	BW
305/30ZR20 (103Y)	110110751	XL	240/AA/A	30.4	11	10.5 - 11.5	12.1	27.2	11.3	9	12.8	764	1929@50	-	BW
305/40ZR20 (112Y)	110110787	XL	240/AA/A	35.5	11	10.0 - 12.0	12.2	29.7	11	9	13.8	700	2469@50	-	BW
315/35ZR20 (110Y)	110110763	XL	240/AA/A	33.1	11	10.5 - 12.5	12.6	28.5	11.2	9	13.3	728	2337@50	-	BW
245/35ZR21 (96Y)	110110788	XL	240/AA/A	25.4	8.5	8.0 - 9.5	9.7	27.7	8.7	9	13.1	750	1565@50	-	BW
245/40R21 100Y	110110789	XL	240/AA/A	28.7	8.5	8.0 - 9.5	9.6	28.7	8.7	9	13.5	723	1764@50	-	BW
255/40ZR21 (102Y)	110110752	XL	240/AA/A	27.3	9	8.5 - 10.0	10	29	8.8	9	13.6	717	1874@50	-	BW
265/35ZR21 (101Y)	110110853	XL	240/AA/A	28.9	9.5	9.0 - 10.5	10.6	28.3	9.6	9	13.3	734	1819@50	-	BW
265/40ZR21 (105Y)	110110753	XL	240/AA/A	31.1	9.5	9.0 - 10.5	10.6	29.2	9.6	9	13.7	712	2039@50	-	BW
275/30ZR21 (98Y)	110110790	XL	240/AA/A	27.8	9.5	9.0 - 10.0	10.6	27.6	9.8	9	13.1	753	1653@50	-	BW
275/35ZR21 (103Y)	110110764	XL	240/AA/A	28.9	9.5	9.0 - 11.0	11	28.7	9.5	9	13.5	725	1929@50	-	BW
275/45R21 110Y	110110791	XL	240/AA/A	35.1	9	8.5 - 10.5	10.8	30.7	9.8	9	14.3	676	2337@50	-	BW
285/30ZR21 (100Y)	110110857	XL	240/AA/A	29.3	10	9.5 - 10.5	11.1	27.8	10.5	9	13.2	747	1764@50	-	BW
285/35ZR21 (105Y)	110110754	XL	240/AA/A	31.7	10	9.5 - 11.0	11.1	28.9	10.4	9	13.6	720	2039@50	-	BW
285/40R21 109Y	110110792	XL	240/AA/A	34.6	10	9.5 - 11.0	11.3	30	10.4	9	14	692	2271@50	-	BW
285/45R21 113Y	110110793	XL	240/AA/A	35.7	9.5	9.0 - 10.5	11.1	31.1	9.9	9	14.4	668	2535@50	-	BW
HL295/30ZR21 105Y	110110863	XL	240/AA/A	32.2	10.5	10.0 - 11.0	11.6	28	10.9	9	13.2	743	2039@50	-	BW
295/35ZR21 (107Y)	110110755	XL	240/AA/A	32.6	10.5	10.0 - 11.5	11.8	29.1	10.8	9	13.7	713	2149@50	-	BW
HL295/35ZR21 (110Y)	110110864	XL	240/AA/A	32.8	10.5	10.0 - 11.5	11.6	29.1	10.7	9	13.7	713	2337@50	-	BW
305/30ZR21 (104Y)	110110756	XL	240/AA/A	32.6	11	10.5 - 11.5	12.4	28.2	11.3	9	13.3	736	1984@50	-	BW
315/30ZR21 (105Y)	110110765	XL	240/AA/A	33.1	11	10.5 - 11.5	12.5	28.4	11.5	9	13.4	732	2039@50	-	BW
315/35R21 111Y	110110860	XL	240/AA/A	35.9	11	10.5 - 12.5	12.4	29.6	11.5	9	13.9	701	2403@50	-	BW
315/40ZR21 (115Y)	110110794	XL	240/AA/A	37.5	11	10.5 - 12.5	12.4	31.1	11.3	9	14.4	668	2679@50	-	BW
325/30ZR21 (108Y)	110110862	XL	240/AA/A	31.3	11.5	11.0 - 12.0	12.9	28.7	11.9	9	13.5	725	2205@50	-	BW
265/35ZR22 (102Y)	110110795	XL	240/AA/A	30.6	9.5	9.0 - 10.5	10.4	29.4	9.6	9	13.9	707	1874@50	-	BW
265/40R22 106Y	110110757	XL	240/AA/A	31.1	9.5	9.0 - 10.5	10.7	30.3	9.6	9	14.2	685	2094@50	-	BW
275/35ZR22 (104Y)	110110758	XL	240/AA/A	31.3	9.5	9.0 - 11.0	10.7	29.6	9.8	9	14	702	1984@50	-	BW
295/25ZR22 (97Y)	110110890	XL	240/AA/A	28.7	10.5	10.0 - 11.0	11.5	27.8	10.5	9	13.3	747	1609@50	-	BW
295/35R22 108Y	110110759	XL	240/AA/A	34	10.5	10.0 - 11.5	11.9	30	10.8	9	14.1	692	2205@50	-	BW
295/40R22 112Y	110110797	XL	240/AA/A	38.1	10.5	10.0 - 11.5	11.7	31.4	10.7	9	14.7	662	2469@50	-	BW
315/30ZR22 (107Y)	110110760	XL	240/AA/A	36.2	11	10.5 - 11.5	12.3	29.6	11.7	9	14	702	2149@50	-	BW
305/35R23 111Y	110110761	XL	240/AA/A	38.8	11	10.0 - 12.0	12.1	31.5	11.2	8	14.8	659	2403@50	-	BW

ADVAN APEX V601

SUMMER **Performance Cars**

An ultra-high performance street tire with big grip for today's popular bigger sizes.



FEATURES AND BENEFITS

PRECISE HANDLING
A strong sidewall and tread deliver precise and immediate cornering response.

MAXIMUM GRIP
A competition-inspired tread design and advanced compound provide confident wet and dry grip.

QUIET RIDE
Rigid construction and optimized groove angles minimize road noise.

LONG TREAD LIFE
Advanced micro-silica compound with rounded rib design extends tread life.

25,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

12,500-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/45R17 94Y	110160101	XL	280/AA/A	22.4	7.5	7.0 - 8.5	8.8	24.9	7.6	9	11.6	833	1477@50	-	BW
245/40R17 95Y	110160102	XL	280/AA/A	23.3	8.5	8.0 - 9.5	9.6	24.6	8.3	9	11.5	843	1521@50	-	BW
245/45R17 99Y	110160103	XL	280/AA/A	24.1	8	7.5 - 9.0	9.6	25.6	8.1	9	11.9	810	1709@50	-	BW
225/40R18 92Y	110160104	XL	280/AA/A	22.1	8	7.5 - 9.0	9	25.1	7.9	9	11.8	827	1389@50	-	BW
225/45R18 95Y	110160105	XL	280/AA/A	23.4	7.5	7.0 - 8.5	8.8	25.9	7.6	9	12.1	802	1521@50	-	BW
235/40R18 95Y	110160106	XL	280/AA/A	23.8	8.5	8.0 - 9.5	9.4	25.4	8.2	9	11.9	818	1521@50	-	BW
235/45R18 98Y	110160107	XL	280/AA/A	24.2	8	7.5 - 9.0	9.3	26.4	7.9	9	12.3	788	1653@50	-	BW
235/50R18 101Y	110160108	XL	280/AA/A	27.2	7.5	6.5 - 8.5	9.5	27.2	8	9	12.6	762	1819@50	-	BW
245/35R18 92Y	110160148	XL	280/AA/A	22.8	8.5	8.0 - 9.5	9.6	24.7	8.5	9	11.6	840	1389@50	-	BW
245/40R18 97Y	110160109	XL	280/AA/A	25	8.5	8.0 - 9.5	9.6	25.8	8.3	9	12	805	1609@50	-	BW
245/45R18 100Y	110160110	XL	280/AA/A	25.6	8	7.5 - 9.0	9.4	26.7	8.1	9	12.4	779	1764@50	-	BW
255/35R18 94Y	110160111	XL	280/AA/A	24.2	9	8.5 - 10.0	10.1	25.1	8.9	9	11.8	828	1477@50	-	BW
255/40R18 99Y	110160112	XL	280/AA/A	26.9	9	8.5 - 10.0	10.1	26.1	8.9	9	12.1	797	1709@50	-	BW
255/45R18 103Y	110160113	XL	280/AA/A	28	8.5	8.0 - 9.5	9.9	27	8.6	9	12.5	768	1929@50	-	BW
265/35R18 97Y	110160114	XL	280/AA/A	25.4	9.5	9.0 - 10.5	10.5	25.3	9.3	9	11.9	821	1609@50	-	BW
275/35R18 99Y	110160147	XL	280/AA/A	26.3	9.5	9.0 - 11.0	10.8	25.4	9.4	9	11.9	817	1709@50	-	BW
275/40R18 103Y	110160115	XL	280/AA/A	29.3	9.5	9.0 - 11.0	10.8	26.7	9.4	9	12.4	778	1929@50	-	BW
225/35R19 88Y	110160116	XL	280/AA/A	22.9	8	7.5 - 9.0	8.8	25.2	7.9	9	11.9	823	1235@50	-	BW
225/40R19 93Y	110160117	XL	280/AA/A	23.1	8	7.5 - 9.0	9	26.1	7.9	9	12.3	795	1433@50	-	BW
225/45R19 96Y	110160118	XL	280/AA/A	24.5	7.5	7.0 - 8.5	8.7	27	7.6	9	12.6	769	1565@50	-	BW
235/35R19 91Y	110160119	XL	280/AA/A	24.3	8.5	8.0 - 9.5	9.4	25.5	8.3	9	12	816	1356@50	-	BW
235/40R19 96Y	110160120	XL	280/AA/A	24.7	8.5	8.0 - 9.5	9.4	26.5	8.3	9	12.4	784	1565@50	-	BW
245/35R19 93Y	110160121	XL	280/AA/A	24	8.5	8.0 - 9.5	9.6	25.8	8.5	9	12.2	804	1433@50	-	BW
245/40R19 98Y	110160122	XL	280/AA/A	26.2	8.5	8.0 - 9.5	9.6	26.8	8.5	9	12.6	775	1653@50	-	BW
245/45R19 102Y	110160123	XL	280/AA/A	26.9	8	7.5 - 9.0	9.4	27.7	8.1	9	12.9	750	1874@50	-	BW
255/30R19 91Y	110160124	XL	280/AA/A	25	9	8.5 - 9.5	10.1	25.1	8.9	9	11.9	828	1356@50	-	BW
255/35R19 96Y	110160125	XL	280/AA/A	25.6	9	8.5 - 10.0	10.1	26.1	8.9	9	12.2	797	1565@50	-	BW
255/40R19 100Y	110160126	XL	280/AA/A	28	9	8.5 - 10.0	10	27.1	8.8	9	12.7	766	1764@50	-	BW
265/35R19 98Y	110160127	XL	280/AA/A	27.1	9.5	9.0 - 10.5	10.6	26.4	9.3	9	12.4	787	1653@50	-	BW
275/35R19 100Y	110160128	XL	280/AA/A	28.3	9.5	9.0 - 11.0	10.7	26.6	9.4	9	12.4	782	1764@50	-	BW
275/40R19 105Y	110160151	XL	280/AA/A	31	9.5	9.0 - 11.0	10.6	27.8	9.4	9	12.9	748	2039@50	-	BW
285/30R19 98Y	110160129	XL	280/AA/A	27.3	10	9.5 - 10.5	11.3	25.8	9.9	9	12.2	804	1653@50	-	BW
285/35R19 103Y	110160130	XL	280/AA/A	29.8	10	9.5 - 11.0	11.3	26.9	9.9	9	12.6	771	1929@50	-	BW
295/30R19 100Y	110160152	XL	280/AA/A	28.5	10.5	10.0 - 11.0	11.7	26	10.3	9	12.2	799	1764@50	-	BW
305/30R19 102Y	110160150	XL	280/AA/A	30.9	11	10.5 - 11.5	12.2	26.2	10.8	9	12.3	792	1874@50	-	BW
325/30R19 105Y	110160153	XL	280/AA/A	33.2	11.5	11.0 - 12.0	12.8	26.7	11.3	9	12.5	779	2039@50	-	BW
235/35R20 92Y	110160131	XL	280/AA/A	26.5	8.5	8.0 - 9.5	9.3	26.5	8.3	9	12.5	784	1389@50	-	BW
245/30R20 90Y	110160145	XL	280/AA/A	24.8	8.5	8.0 - 9.0	9.6	25.8	8.5	9	12.3	804	1323@50	-	BW

ADVAN APEX V601

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
245/35R20 95Y	110160132	XL	280/AA/A	24.9	8.5	8.0 - 9.5	9.6	26.8	8.5	9	12.6	775	1521@50	-	BW
245/40R20 99Y	110160133	XL	280/AA/A	27.6	8.5	8.0 - 9.5	9.4	27.8	8.3	9	13	748	1709@50	-	BW
245/45R20 103Y	110160134	XL	280/AA/A	28.5	8	7.5 - 9.0	9.4	28.7	8.1	9	13.4	724	1929@50	-	BW
255/35R20 97Y	110160135	XL	280/AA/A	28.1	9	8.5 - 10.0	10	27	8.9	9	12.7	769	1609@50	-	BW
265/30R20 94Y	110160154	XL	280/AA/A	28	9.5	9.0 - 10.0	10.4	26.4	9.3	9	12.5	788	1477@50	-	BW
265/35R20 99Y	110160136	XL	280/AA/A	29.3	9.5	9.0 - 10.5	10.5	27.4	9.3	9	12.9	759	1709@50	-	BW
275/30R20 97Y	110160137	XL	280/AA/A	28.4	9.5	9.0 - 10.0	10.6	26.6	9.4	9	12.6	782	1609@50	-	BW
275/35R20 102Y	110160138	XL	280/AA/A	28.9	9.5	9.0 - 11.0	10.7	27.6	9.4	9	12.9	754	1874@50	-	BW
275/40R20 106Y	110160139	XL	280/AA/A	32.1	9.5	9.0 - 11.0	10.7	28.7	9.4	9	13.4	725	2094@50	-	BW
285/30R20 99Y	110160140	XL	280/AA/A	30.7	10	9.5 - 10.5	11.2	26.8	9.9	9	12.6	775	1709@50	-	BW
285/35R20 104Y	110160141	XL	280/AA/A	31.2	10	9.5 - 11.0	11.2	27.9	9.9	9	13.1	745	1984@50	-	BW
295/30R20 101Y	110160142	XL	280/AA/A	30.6	10.5	10.0 - 11.0	11.6	27	10.3	9	12.8	768	1819@50	-	BW
305/30R20 103Y	110160143	XL	280/AA/A	32.5	11	10.5 - 11.5	12.1	27.2	10.8	9	12.8	762	1929@50	-	BW
305/35R20 107Y	110160144	XL	280/AA/A	35.5	11	10.0 - 12.0	12.2	28.4	10.8	9	13.3	732	2149@50	-	BW
245/35R21 96Y	110160146	XL	280/AA/A	26.8	8.5	8.0 - 9.5	9.6	27.8	8.3	9	13.2	746	1565@50	-	BW
265/35R21 101Y	110160149	XL	280/AA/A	29.7	9.5	9.0 - 10.5	10.6	28.4	9.3	9	13.4	731	1819@50	-	BW

ADVAN Sport Z·P·S®

Zero Pressure System

4 PERFORMANCE PROGRAM SATISFACTION 30 DAY TRIAL GUARANTEED

SUMMER **Performance Cars | Passenger Cars**

Legendary ADVAN performance, engineered with Zero Pressure System run-flat capabilities.



FEATURES AND BENEFITS

COMPETITIVE GRIP
Advanced tread compound delivers excellent wet and dry traction.

EXCELLENT WET TRACTION
Asymmetric tread design quickly and efficiently evacuates water.

LONG TREAD LIFE
Advanced construction and groove design controls stress to promote even wear.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/50RF16 92W	110111303	SL	180/AA/A	27.3	7	6.0 - 8.0	9.1	24.9	7.8	10	11.5	835	1389@51	-	BW
225/45RF17 91Y	110111305	SL	180/AA/A	27.1	7.5	7.0 - 8.5	8.9	25	7.8	10	11.6	832	1356@51	-	BW
225/40RF18 88Y	110111307	SL	180/AA/A	27.7	8	7.5 - 9.0	9.2	25	7.8	10	11.7	831	1235@51	-	BW

ADVAN FLEVA V701

SUMMER **Performance Cars | Passenger Cars**

A high-performance summer tire that delivers efficient wet and dry handling.



FEATURES AND BENEFITS

COMPETITIVE HANDLING
Solid ribs increase block stiffness for high-speed stability and superior handling.

EFFICIENT GRIP
Excellent hydroplaning resistance and shorter stops on wet roads.

QUIET RIDE
An offset tread pattern increases stability and reduces pattern noise.

FUEL EFFICIENT
Nano-blend compound with micro silica reduces rolling resistance.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
185/55R15 82V	110170173	SL	300/AA/A	16.9	6	5.0 - 6.5	7.7	23	6.3	9	10.6	905	1047@51	-	BW
195/50R15 82V	110170130	SL	300/AA/A	17	6	5.5 - 7.0	7.9	22.7	6.6	9	10.5	916	1047@51	-	BW
195/55R15 85V	110170131	SL	300/AA/A	17.6	6	5.5 - 7.0	7.9	23.4	6.5	9	10.8	888	1136@51	-	BW
205/50R15 86V	110170174	SL	300/AA/A	18.7	6.5	5.5 - 7.5	8.3	23	6.9	9	10.6	905	1169@51	-	BW
205/55R15 88V	110170132	SL	300/AA/A	18.6	6.5	5.5 - 7.5	8.3	23.8	6.9	9	10.9	872	1235@51	-	BW
195/45R16 84W	110170133	XL	300/AA/A	17.1	6.5	6.0 - 7.5	7.6	22.9	6.5	9	10.7	906	1103@50	-	BW
195/50R16 84V	110170134	SL	300/AA/A	18.4	6	5.5 - 7.0	7.9	23.6	6.6	9	11	879	1103@51	-	BW
195/55R16 87V	110170135	SL	300/AA/A	19.5	6	5.5 - 7.0	7.9	24.3	6.5	9	11.3	854	1202@51	-	BW
205/45R16 87W	110170136	XL	300/AA/A	17.3	7	6.5 - 7.5	8.1	23.2	6.9	9	10.8	896	1202@50	-	BW
205/50R16 87V	110170137	SL	300/AA/A	19.1	6.5	5.5 - 7.5	8.3	24	6.9	9	11.1	865	1202@51	-	BW
205/55R16 91W	110170138	SL	300/AA/A	19.9	6.5	5.5 - 7.5	8.3	24.8	6.9	9	11.5	836	1356@51	-	BW
215/55R16 93W	110170176	SL	300/AA/A	20.6	7	6.0 - 7.5	8.8	25.2	7.2	10	11.6	826	1433@51	-	BW
225/50R16 92W	110170139	SL	300/AA/A	21.6	7	6.0 - 8.0	9.1	24.8	7.6	10	11.4	839	1389@51	-	BW
225/55R16 95W	110170177	SL	300/AA/A	23.5	7	6.0 - 8.0	9.1	25.6	7.4	10	11.7	812	1521@51	-	BW
195/40R17 81W	110170178	XL	300/AA/A	19	7	6.5 - 7.5	7.8	23.2	6.7	9	10.9	896	1019@50	-	BW
195/45R17 85W	110170179	XL	300/AA/A	18.4	6.5	6.0 - 7.5	7.7	23.9	6.5	9	11.2	868	1136@50	-	BW
205/40R17 84W	110170180	XL	300/AA/A	19.5	7.5	7.0 - 8.0	8.4	23.4	7.2	9	11	887	1103@50	-	BW
205/45R17 88W	110170140	XL	300/AA/A	20.3	7	6.5 - 7.5	8	24.2	6.9	9	11.3	858	1235@50	-	BW
205/50R17 93W	110170141	XL	300/AA/A	20.7	6.5	5.5 - 7.5	8.3	25.1	6.9	9	11.7	827	1433@50	-	BW
215/40R17 87W	110170143	XL	300/AA/A	20.7	7.5	7.0 - 8.5	8.5	23.7	7.5	10	11.1	876	1202@50	-	BW
215/45R17 91W	110170144	XL	300/AA/A	21.7	7	7.0 - 8.0	8.4	24.7	7.3	10	11.5	843	1356@50	-	BW
215/50R17 95W	110170145	XL	300/AA/A	23.4	7	6.0 - 7.5	7.3	25.5	7.3	10	11.8	815	1521@50	-	BW
215/55R17 94W	110170146	SL	300/AA/A	23.7	7	6.0 - 7.5	8.8	26.3	7.2	10	12.1	791	1477@51	-	BW
225/50R17 98W	110170148	XL	300/AA/A	24.3	7	6.0 - 8.0	9.1	25.9	7.6	10	12	803	1654@50	-	BW
235/40R17 90W	110170181	SL	300/AA/A	23.5	8.5	8.0 - 9.5	9.5	24.4	8.2	10	11.4	852	1323@51	-	BW
235/45R17 97W	110170150	XL	300/AA/A	23.5	8	7.5 - 9.0	9.3	25.3	8	10	11.7	820	1610@50	-	BW
255/40R17 94W	110170151	SL	300/AA/A	25.6	9	8.5 - 10.0	10.3	25	8.8	10	11.6	831	1477@51	-	BW
205/40R18 86W	110170152	XL	300/AA/A	19.2	7.5	7.0 - 8.0	8.3	24.5	7.2	9	11.5	848	1169@50	-	BW
215/35R18 84W	110170153	XL	300/AA/A	18.7	7.5	7.0 - 8.5	8.5	23.9	7.5	9	11.3	871	1103@50	-	BW
215/40R18 89W	110170154	XL	300/AA/A	20.7	7.5	7.0 - 8.5	8.5	24.8	7.5	10	11.7	837	1279@50	-	BW
215/45R18 93W	110170183	XL	300/AA/A	21.3	7	7.0 - 8.0	8.4	25.7	7.3	10	12	809	1433@50	-	BW
225/35R18 87W	110170155	XL	300/AA/A	20.7	8	7.5 - 9.0	8.9	24.2	7.9	10	11.4	859	1202@50	-	BW
225/50R18 99W	110170184	XL	300/AA/A	24.9	7	6.0 - 8.0	9	26.9	7.6	10	12.4	774	1709@50	-	BW
235/55R18 100V	110170160	SL	300/AA/A	27.7	7.5	6.5 - 8.5	9.5	28.1	7.6	10	12.9	740	1764@51	-	BW
235/45R19 95W	110170167	SL	300/AA/A	24	8	7.5 - 9.0	9.2	27.4	8	10	12.8	759	1521@51	-	BW
265/30R19 93W	110170170	XL	300/AA/A	25.1	9.5	9.0 - 10.0	10.5	25.3	9.3	10	11.9	822	1433@50	-	BW
225/35R20 90W	110170171	XL	300/AA/A	23	8	7.5 - 9.0	9	26.2	7.9	10	12.4	793	1323@50	-	BW
255/30R20 92W	110170172	XL	300/AA/A	25.6	9	8.5 - 9.5	10	26.1	8.9	10	12.4	797	1389@50	-	BW

ADVAN Sport® EV A/S

ALL-SEASON **Performance Cars | Passenger Cars | Electric Vehicles (EVs)**

All-season performance and long, reliable treadwear for electric vehicles.



FEATURES AND BENEFITS

LONG, RELIABLE TREAD LIFE
New compound and optimized contact patch for traction and durability.

OPTIMIZED RIDE QUALITY
Optimized sidewall construction and four-pitch pattern noise give a smooth and quiet ride.

OUTSTANDING ALL-SEASON GRIP
All-Season compound, z grooves and wavy sipes deliver dependable, all-season grip.

SUPERIOR HANDLING
Engineered for enhanced cornering and crisp, responsive handling.

55,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

27,500-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
235/45R18 98W	110140560	XL	580/A/A	25.7	8	7.5 - 9.0	9.3	26.4	7.7	11	12.3	788	1653@50	-	BW
235/40R19 96Y	110140561	XL	580/A/A	25.7	8.5	8.0 - 9.5	9.5	26.4	7.7	11	12.4	788	1565@50	-	BW
245/45R19 102Y	110140562	XL	580/A/A	29.6	8	7.5 - 9.0	9.6	27.6	8	11	12.9	752	1874@50	-	BW
255/45R19 104W	110140563	XL	580/A/A	30.3	8.5	8.0 - 9.5	10	28.1	8.3	11	13.1	738	1984@50	-	BW
285/40R19 107Y	110140564	XL	580/A/A	33.3	10	9.5 - 11.0	11.5	28.1	9.3	12	13.1	739	2149@50	-	BW
235/35R20 92Y	110140565	XL	580/A/A	26.1	8.5	8.0 - 9.5	9.6	26.5	7.9	11	12.5	783	1389@50	-	BW
255/40R20 101W	110140566	XL	580/A/A	29.7	9	8.5 - 10.0	10.1	28.1	8.3	11	13.2	738	1819@50	-	BW
255/45R20 105Y	110140567	XL	580/A/A	32.3	8.5	8.0 - 9.5	10.1	29	8.3	11	13.5	716	2039@50	-	BW
265/45R20 108V	110140568	XL	580/A/A	33	9	8.5 - 10.0	10.4	29.5	8.7	11	13.7	704	2205@50	-	BW
275/45R20 110V	110140569	XL	580/A/A	34.4	9	8.5 - 10.5	10.9	29.8	9	11	13.8	696	2337@50	-	BW

ADVAN Sport® A/S+

ALL-SEASON **Performance Cars | Passenger Cars**

Finish first with a tire that delivers a performance trifecta: high mileage, comfort and handling.

FEATURES AND BENEFITS

SUPERIOR HANDLING
Engineered for enhanced cornering and crisp, responsive handling.

ALL-SEASON GRIP
HS-2 compound, z grooves and wavy sipes deliver dependable, all-season grip.

QUIET RIDE
Four-pitch tread variation keeps things quiet and comfortable.

LONG TREAD LIFE
HS-2 compound and optimized contact patch for traction and durability.

55,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

27,500-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/55R16 91W	110140610	SL	440/AA/A	21.8	6.5	5.5 - 7.5	8.5	24.9	6.9	11	11.5	835	1356@51	-	BW
225/50R16 92W	110140611	SL	440/AA/A	23	7	6.0 - 8.0	9.3	24.8	7.6	11	11.4	836	1389@51	-	BW
225/55R16 95W	110140612	SL	440/AA/A	25.2	7	6.0 - 8.0	9.3	25.7	7.4	11	11.8	807	1521@51	-	BW
205/50R17 93W	110140613	XL	440/AA/A	23.1	6.5	5.5 - 7.5	8.3	25.2	7	11	11.7	824	1433@50	-	BW
215/45R17 87W	110140614	SL	440/AA/A	23.4	7	7.0 - 8.0	8.5	24.6	7	11	11.5	843	1201@51	-	BW
215/50R17 95W	110140615	XL	440/AA/A	23.3	7	6.0 - 7.5	8.7	25.6	7.2	11	11.9	812	1521@50	-	BW
215/55R17 94W	110140616	SL	440/AA/A	24.9	7	6.0 - 7.5	9	26.3	7.2	11	12.1	790	1477@51	-	BW
225/45R17 94W	110140617	XL	440/AA/A	22.9	7.5	7.0 - 8.5	8.8	25	7.4	11	11.6	831	1477@50	-	BW
225/50R17 98W	110140618	XL	440/AA/A	25	7	6.0 - 8.0	9.1	26	7.5	11	12	799	1653@50	-	BW
225/55R17 97W	110140619	SL	440/AA/A	26.9	7	6.0 - 8.0	9.3	26.9	7.5	11	12.3	774	1609@51	-	BW
235/45R17 97W	110140620	XL	440/AA/A	24.2	8	7.5 - 9.0	9.3	25.3	7.7	11	11.7	820	1609@50	-	BW
235/50R17 96W	110140621	SL	440/AA/A	24.9	7.5	6.5 - 8.5	9.6	26.3	7.9	11	12.1	790	1565@51	-	BW
235/55R17 99W	110140622	SL	440/AA/A	27.8	7.5	6.5 - 8.5	9.7	27.2	7.9	11	12.5	765	1709@51	-	BW
245/40R17 95W	110140623	XL	440/AA/A	24.3	8.5	8.0 - 9.5	9.8	24.8	8	11	11.5	837	1521@50	-	BW
245/45R17 99W	110140624	XL	440/AA/A	24.9	8	7.5 - 9.0	9.5	25.7	8	11	11.9	807	1709@50	-	BW
255/40R17 94W	110140625	SL	440/AA/A	26.2	9	8.5 - 10.0	10.2	25	8.3	11	11.6	831	1477@51	-	BW
255/45R17 98W	110140626	SL	440/AA/A	26.9	8.5	8.0 - 9.5	10	26	8.3	11	12	798	1653@51	-	BW
215/40R18 89W	110140627	XL	440/AA/A	20.7	7.5	7.0 - 8.5	8.5	24.9	7	11	11.7	834	1279@50	-	BW
215/45R18 93W	110140628	XL	440/AA/A	23.8	7	7.0 - 8.0	8.3	25.7	7	11	12	807	1433@50	-	BW
225/40R18 92Y	110140629	XL	440/AA/A	23.4	8	7.5 - 9.0	9	25.1	7.4	11	11.8	828	1389@50	-	BW
225/45R18 95W	110140630	XL	440/AA/A	24	7.5	7.0 - 8.5	8.8	26	7.4	11	12.1	799	1521@50	-	BW
225/50R18 95W	110140631	SL	440/AA/A	26.9	7	6.0 - 8.0	9.1	26.9	7.5	11	12.5	773	1521@51	-	BW
235/40R18 95Y	110140632	XL	440/AA/A	25.2	8.5	8.0 - 9.5	9.6	25.4	7.7	11	11.9	818	1521@50	-	BW
235/45R18 98W	110140633	XL	440/AA/A	26.4	8	7.5 - 9.0	9.2	26.4	7.7	11	12.3	788	1653@50	-	BW
235/50R18 97W	110140634	SL	440/AA/A	28.1	7.5	6.5 - 8.5	9.6	27.3	7.9	11	12.6	761	1609@51	-	BW
245/35R18 92Y	110140635	XL	440/AA/A	24.7	8.5	8.0 - 9.5	9.6	24.8	8	11	11.6	839	1389@50	-	BW
245/40R18 97Y	110140636	XL	440/AA/A	25.6	8.5	8.0 - 9.5	9.6	25.7	8	11	12	808	1609@50	-	BW
245/45R18 100W	110140637	XL	440/AA/A	26	8	7.5 - 9.0	9.7	26.7	8	11	12.4	779	1764@50	-	BW
245/50R18 100W	110140638	SL	440/AA/A	29.3	7.5	7.0 - 8.5	9.9	27.6	8.2	11	12.8	752	1764@51	-	BW
255/35R18 94Y	110140639	XL	440/AA/A	25.4	9	8.5 - 10.0	10.1	25	8.3	11	11.7	831	1477@50	-	BW
255/40R18 99Y	110140640	XL	440/AA/A	27.8	9	8.5 - 10.0	10.3	26	8.3	11	12.1	799	1709@50	-	BW
255/45R18 99Y	110140641	SL	440/AA/A	28.9	8.5	8.0 - 9.5	10.2	27	8.3	11	12.5	769	1709@51	-	BW
265/35R18 97Y	110140642	XL	440/AA/A	27.6	9.5	9.0 - 10.5	10.6	25.3	8.7	11	11.9	821	1609@50	-	BW
265/40R18 101Y	110140643	XL	440/AA/A	28.2	9.5	9.0 - 10.5	10.6	26.4	8.7	11	12.3	788	1819@50	-	BW
275/35R18 95Y	110140644	SL	440/AA/A	26.6	9.5	9.0 - 11.0	10.8	25.6	9	11	11.9	813	1521@51	-	BW
275/40R18 99Y	110140645	SL	440/AA/A	29.7	9.5	9.0 - 11.0	10.9	26.6	9	11	12.4	781	1709@51	-	BW
285/35R18 101Y	110140646	XL	440/AA/A	28.5	10	9.5 - 11.0	11.1	25.9	9.3	11	12.1	803	1819@50	-	BW
225/40R19 93Y	110140647	XL	440/AA/A	24.5	8	7.5 - 9.0	9	26.1	7.4	11	12.3	796	1433@50	-	BW

ADVAN Sport® A/S+

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/45R19 96Y	110140648	XL	440/AA/A	26	7.5	7.0 - 8.5	8.8	27	7.4	11	12.6	769	1565@50	-	BW
235/35R19 91Y	110140649	XL	440/AA/A	25.8	8.5	8.0 - 9.5	9.5	25.5	7.9	11	12	814	1356@50	-	BW
235/40R19 96Y	110140650	XL	440/AA/A	25.6	8.5	8.0 - 9.5	9.4	26.4	7.7	11	12.4	786	1565@50	-	BW
245/35R19 93Y	110140651	XL	440/AA/A	25.8	8.5	8.0 - 9.5	9.7	25.7	8.1	11	12.1	807	1433@50	-	BW
245/40R19 98Y	110140652	XL	440/AA/A	26.5	8.5	8.0 - 9.5	9.7	26.7	8	11	12.5	777	1653@50	-	BW
245/45R19 102Y	110140653	XL	440/AA/A	28.3	8	7.5 - 9.0	9.6	27.8	8	11	12.9	748	1874@50	-	BW
255/35R19 96Y	110140654	XL	440/AA/A	27.3	9	8.5 - 10.0	10.1	26	8.3	11	12.2	798	1565@50	-	BW
255/40R19 100Y	110140655	XL	440/AA/A	28.9	9	8.5 - 10.0	10.1	27.1	8.3	11	12.7	767	1764@50	-	BW
255/45R19 104W	110140656	XL	440/AA/A	30.2	8.5	8.0 - 9.5	10	28.2	8.3	11	13.1	737	1984@50	-	BW
265/35R19 98Y	110140657	XL	440/AA/A	28	9.5	9.0 - 10.5	10.5	26.3	8.7	11	12.4	789	1653@50	-	BW
275/35R19 100Y	110140658	XL	440/AA/A	28	9.5	9.0 - 11.0	10.7	26.6	9	11	12.5	781	1764@50	-	BW
275/40R19 101Y	110140659	SL	440/AA/A	30.4	9.5	9.0 - 11.0	10.7	27.8	9	11	12.9	748	1819@51	-	BW
285/30R19 98Y	110140660	XL	440/AA/A	29.4	10	9.5 - 10.5	11.3	25.7	9.3	11	12.1	807	1653@50	-	BW
285/35R19 99Y	110140661	SL	440/AA/A	31.5	10	9.5 - 11.0	11.2	26.9	9.3	11	12.6	774	1709@51	-	BW
245/35R20 95Y	110140662	XL	440/AA/A	26	8.5	8.0 - 9.5	9.6	26.8	8.1	11	12.6	776	1521@50	-	BW
245/40R20 99Y	110140663	XL	440/AA/A	28.3	8.5	8.0 - 9.5	9.7	27.7	8	11	13	749	1709@50	-	BW
245/45R20 103Y	110140664	XL	440/AA/A	29.5	8	7.5 - 9.0	9.6	28.7	8	11	13.4	724	1929@50	-	BW
255/35R20 97Y	110140665	XL	440/AA/A	28.4	9	8.5 - 10.0	10	27.1	8.3	11	12.8	767	1609@50	-	BW
255/45R20 105Y	110140666	XL	440/AA/A	30.9	8.5	9.0 - 10.5	10	29.1	8.3	11	13.6	713	2039@50	-	BW
265/35R20 99Y	110140667	XL	440/AA/A	29.6	9.5	9.0 - 10.5	10.6	27.3	8.7	11	12.9	760	1709@50	-	BW
275/30R20 97Y	110140668	XL	440/AA/A	29.1	9.5	9.0 - 10.0	10.8	26.6	9.1	11	12.6	782	1609@50	-	BW
275/35R20 102Y	110140669	XL	440/AA/A	29.1	9.5	9.0 - 11.0	10.9	27.7	9	11	13	750	1874@50	-	BW
275/40R20 106Y	110140670	XL	440/AA/A	33.3	9.5	9.0 - 11.0	10.7	28.7	9	11	13.4	723	2094@50	-	BW
285/30R20 99W	110140671	XL	440/AA/A	30.7	10	9.5 - 10.5	11.1	26.9	9.3	11	12.7	773	1709@50	-	BW
245/35R21 96Y	110140672	XL	440/AA/A	26.2	8.5	8.0 - 9.5	9.6	27.8	8.1	11	13.2	746	1565@50	-	BW
265/35R21 101Y	110140673	XL	440/AA/A	30.1	9.5	9.0 - 10.5	10.6	28.4	8.9	11	13.4	731	1819@50	-	BW
275/35R21 103Y	110140674	XL	440/AA/A	31.3	9.5	9.0 - 11.0	10.8	28.7	9.2	11	13.5	725	1929@50	-	BW

AVID ENVigor Z·P·S®

Zero Pressure System

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON **Performance Cars | Passenger Cars**

All-weather performance with the added confidence of a Zero Pressure System runflat capability.



FEATURES AND BENEFITS

WET TRACTION
Directional tread design and adaptive sipes channel water away for excellent wet grip.

RUNFLAT
Advanced runflat technology provides added durability in run flat mode.

HANDLING
Aggressive directional design and construction provide crisp and responsive handling.

QUIET RIDE
Multi-pitch design reduces unwanted resonance for a quieter ride.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
195/55R16 87V	110132194	SL	560/A/A	24.9	6	5.5 - 7.0	7.8	24.4	6.5	10	11.3	850	1201@51	-	BW
205/45RF17 84V	110132191	SL	560/A/A	25.4	7	6.5 - 7.5	8.2	24.3	6.9	11	11.3	856	1102@51	-	BW
225/45RF17 91V	110132192	SL	560/A/A	28	7.5	7.0 - 8.5	8.9	25	8	11	11.6	832	1356@51	-	BW
225/50RF17 94V	110132193	SL	560/A/A	31.2	7	6.0 - 8.0	9.2	25.8	7.5	11	11.9	805	1477@51	-	BW
225/55RF17 97V	110132197	SL	560/A/A	30.1	7	6.0 - 8.0	9	26.6	7.2	11	12.2	780	1609@51	-	BW
255/40RF17 94V	110132195	SL	560/A/A	29.6	9	8.5 - 10.0	10.3	25.1	8.4	11	11.7	828	1477@51	-	BW
245/40RF18 93V	110132190	SL	560/A/A	32.2	8.5	8.0 - 9.5	9.9	25.6	8.7	11	12	812	1433@51	-	BW
245/45RF18 96W	110132196	SL	560/A/A	31.5	8	7.5 - 9.0	9.6	26.6	8.3	11	12.4	780	1565@51	-	BW

AVID Ascend GT®

ALL-SEASON **Performance Cars | Passenger Cars | Crossovers/SUVs | Minivans**

A next-generation touring tire that delivers all-weather performance all year long.



FEATURES AND BENEFITS

ALL-SEASON GRIP
Triblend compound provides confident traction in snow and wintry weather.

SHORTER WET/SNOW BRAKING
Triblend Compound and asymmetric groove arrangement deliver ultimate grip on wet and snowy roads.

QUIET RIDE
Multi-pitch tread design and adaptive shoulder reduce noise when new and protect against noise after worn.

LONG TREAD LIFE
Triple 3D sipes and an ultra-square contact patch provide long-lasting, all-season traction.

65,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

32,500-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
175/65R15 84H	110132701	SL	740/A/A	17.6	5	5.0 - 6.0	6.9	24.1	5.4	12	11	864	1102@51	-	BW
185/55R15 82V	110132702	SL	740/A/A	18.1	6	5.0 - 6.5	7.6	23	6.1	12	10.6	902	1047@51	-	BW
185/65R15 88H	110132703	SL	740/A/A	19.4	5.5	5.0 - 6.5	7.5	24.5	5.7	12	11.2	847	1235@51	-	BW
195/60R15 88H	110132704	SL	740/A/A	20.3	6	5.5 - 7.0	8	24.3	6.4	12	11.1	854	1235@51	-	BW
195/65R15 91H	110132705	SL	740/A/A	20.5	6	5.5 - 7.0	7.9	25	6.1	12	11.4	830	1356@51	-	BW
205/60R15 91H	110132706	SL	740/A/A	20.5	6	5.5 - 7.5	8.3	24.8	6.5	12	11.3	839	1356@51	-	BW
P205/65R15 92H	110132707	SL	740/A/A	22.3	6	5.5 - 7.5	8.3	25.6	6.5	12	11.6	813	1400@51	-	BW
185/55R16 83H	110132708	SL	740/A/A	18.7	6	5.0 - 6.5	7.7	24	6.1	12	11.1	865	1074@51	-	BW
195/50R16 84V	110132709	SL	740/A/A	19.2	6	5.5 - 7.0	7.8	23.9	6.4	12	11.1	869	1102@51	-	BW
195/55R16 87V	110132710	SL	740/A/A	19.4	6	5.5 - 7.0	7.8	24.4	6.4	12	11.3	852	1201@51	-	BW
205/50R16 87V	110132752	SL	740/A/A	20.9	6.5	5.5 - 7.5	8.4	24.1	6.7	12	11.1	864	1201@51	-	BW
205/55R16 91H	110132711	SL	740/A/A	21.8	6.5	5.5 - 7.5	8.3	25	6.7	12	11.5	830	1356@51	-	BW
205/60R16 92H	110132712	SL	740/A/A	22.3	6	5.5 - 7.5	8.2	25.7	6.5	12	11.8	808	1389@51	-	BW
205/60R16 92V	110132713	SL	740/A/A	22.3	6	5.5 - 7.5	8.2	25.6	6.5	12	11.7	812	1389@51	-	BW
205/65R16 95H	110132714	SL	740/A/A	23.6	6	5.5 - 7.5	8.2	26.5	6.4	12	12.1	785	1521@51	-	BW
215/55R16 97H	110132715	XL	740/A/A	23.1	7	6.0 - 7.5	8.9	25.4	7	12	11.7	818	1609@50	-	BW
215/60R16 95H	110132717	SL	740/A/A	23.8	6.5	6.0 - 7.5	8.7	26.2	6.9	12	12	792	1521@51	-	BW
215/60R16 95V	110132716	SL	740/A/A	23.8	6.5	6.0 - 7.5	8.7	26.2	6.9	12	12	792	1521@51	-	BW
225/55R16 99V	110132753	XL	740/A/A	25.1	7	6.0 - 8.0	9.1	25.9	7.4	12	11.8	803	1709@50	-	BW
P185/60R16 86H	110132751	SL	740/A/A	19.6	6	5.0 - 6.5	7.6	24.8	5.9	12	11.4	839	1168@51	-	BW
205/50R17 93V	110132718	XL	740/A/A	22.7	6.5	5.5 - 7.5	8.3	25.1	6.7	12	11.7	828	1433@50	-	BW
215/45R17 91V	110132719	XL	740/A/A	22.7	7	7.0 - 8.0	8.4	24.6	7	12	11.5	843	1356@50	-	BW
215/50R17 95V	110132720	XL	740/A/A	23.4	7	6.0 - 7.5	8.7	25.5	7	12	11.8	814	1521@50	-	BW
215/55R17 94V	110132721	SL	740/A/A	24.7	7	6.0 - 7.5	8.8	26.4	7	12	12.2	788	1477@51	-	BW
225/45R17 91V	110132722	SL	740/A/A	23.8	7.5	7.0 - 8.5	8.9	25	7.4	12	11.6	832	1356@51	-	BW
225/50R17 94V	110132723	SL	740/A/A	24.9	7	6.0 - 8.0	9.2	25.9	7.4	12	12	802	1477@51	-	BW
225/55R17 97V	110132724	SL	740/A/A	26.7	7	6.0 - 8.0	9.1	26.9	7.4	12	12.4	771	1609@51	-	BW
225/60R17 99V	110132725	SL	740/A/A	26.9	6.5	6.0 - 8.0	9.1	27.8	7.4	12	12.7	748	1709@51	-	BW
225/65R17 102H	110132755	SL	740/A/A	28.1	6.5	6.0 - 8.0	9	28.6	7	12	13	726	1874@51	-	BW
235/45R17 97V	110132726	XL	740/A/A	24.3	8	7.5 - 9.0	9.4	25.4	7.8	12	11.8	819	1609@50	-	BW
235/50R17 96V	110132727	SL	740/A/A	26	7.5	6.5 - 8.5	9.6	26.3	7.7	12	12.1	790	1565@51	-	BW
235/55R17 99H	110132728	SL	740/A/A	27.1	7.5	6.5 - 8.5	9.7	27.2	7.7	12	12.5	765	1709@51	-	BW
235/60R17 102H	110132729	SL	740/A/A	28.9	7	6.5 - 8.5	9.6	28.2	7.7	12	12.9	737	1874@51	-	BW
245/45R17 99V	110132730	XL	740/A/A	24.9	8	7.5 - 9.0	9.6	25.6	8.1	12	11.9	811	1709@50	-	BW
245/50R17 99V	110132731	SL	740/A/A	27.8	7.5	7.0 - 8.5	9.8	26.8	8	12	12.3	776	1709@51	-	BW
225/40R18 92V	110132754	XL	740/A/A	24	8	7.5 - 9.0	9.2	25.1	7.5	12	11.8	828	1389@50	-	BW
225/45R18 95V	110132733	XL	740/A/A	24.7	7.5	7.0 - 8.5	8.9	25.9	7.4	12	12.1	802	1521@50	-	BW
225/50R18 95V	110132734	SL	740/A/A	26.9	7	6.0 - 8.0	9.1	26.9	7.4	12	12.5	774	1521@51	-	BW

AVID Ascend GT®

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/60R18 100H	110132736	SL	740/A/A	29.8	6.5	6.0 - 8.0	9.1	28.8	7.4	12	13.2	722	1764@51	-	BW
235/45R18 94V	110132737	SL	740/A/A	26.5	8	7.5 - 9.0	9.4	26.3	7.8	12	12.3	789	1477@51	-	BW
235/50R18 101V	110132738	XL	740/A/A	28.4	7.5	6.5 - 8.5	9.5	27.2	7.7	12	12.6	763	1819@50	-	BW
235/55R18 100V	110132739	SL	740/A/A	29.5	7.5	6.5 - 8.5	9.6	28.3	7.7	12	13	734	1764@51	-	BW
235/60R18 107V	110132756	XL	740/A/A	31.8	7	6.5 - 8.5	9.5	29.1	7.7	12	13.3	714	2149@50	-	BW
245/40R18 97V	110132740	XL	740/A/A	26.7	8.5	8.0 - 9.5	9.7	25.7	8.1	12	12	807	1609@50	-	BW
245/45R18 96V	110132741	SL	740/A/A	27.6	8	7.5 - 9.0	9.7	26.7	8	12	12.4	779	1565@51	-	BW
245/50R18 100V	110132742	SL	740/A/A	30.4	7.5	7.0 - 8.5	9.8	27.8	8	12	12.8	747	1764@51	-	BW
255/45R18 99V	110132743	SL	740/A/A	28.4	8.5	8.0 - 9.5	10	27	8.4	12	12.5	768	1709@51	-	BW
P215/55R18 94H	110132732	SL	740/A/A	26.7	7	6.0 - 7.5	8.8	27.3	7	12	12.6	761	1477@51	-	BW
P225/55R18 97H	110132735	SL	740/A/A	27.8	7	6.0 - 8.0	9.2	27.8	7.4	12	12.8	748	1609@51	-	BW
235/40R19 96V	110132744	XL	740/A/A	26.2	8.5	8.0 - 9.5	9.4	26.4	7.8	12	12.4	786	1565@50	-	BW
235/45R19 99V	110132745	XL	740/A/A	27.8	8	7.5 - 9.0	9.3	27.4	7.8	12	12.8	758	1709@50	-	BW
235/50R19 103V	110132757	XL	740/A/A	28.6	7.5	6.5 - 8.5	9.4	28.3	7.7	12	13.1	733	1929@50	-	BW
235/55R19 105V	110132758	XL	740/A/A	30.9	7.5	6.5 - 8.5	9.6	29.1	7.7	12	13.4	714	2039@50	-	BW
245/40R19 94V	110132746	SL	740/A/A	28	8.5	8.0 - 9.5	9.8	26.8	8.2	12	12.5	776	1477@51	-	BW
245/45R19 98V	110132747	SL	740/A/A	28.7	8	7.5 - 9.0	9.8	27.7	8	12	12.9	750	1653@51	-	BW
255/40R19 100V	110132748	XL	740/A/A	27.8	9	8.5 - 10.0	10	27	8.4	12	12.6	768	1764@50	-	BW
255/45R19 100V	110132749	SL	740/A/A	29.8	8.5	8.0 - 9.5	10	28	8.3	12	13	741	1764@51	-	BW
245/45R20 99V	110132750	SL	740/A/A	30	8	7.5 - 9.0	9.5	28.7	8	12	13.4	723	1709@51	-	BW
245/50R20 105V	110132759	XL	740/A/A	31.7	7.5	7.0 - 8.5	9.7	29.9	8	12	13.9	695	2039@50	-	BW
255/50R20 109V	110132760	XL	740/A/A	35.3	8	7.0 - 9.0	10.2	30.2	8.3	12	14	689	2271@50	-	BW

AVID Ascend LX®

ALL-SEASON **Passenger Cars | Crossovers/SUVs | Minivans**

A premium, high-mileage, all-season touring tire that goes the distance.



FEATURES AND BENEFITS

DEPENDABLE WINTER TRACTION
Exceptional strong grip for worry-free winter driving.

SUPERIOR WET TRACTION
Designed for reliable wet braking and resistance to hydroplaning.

QUIET RIDE
Designed for reduced pattern and road noise for a comfortable, smooth ride.

LONG TREAD LIFE
Uniform tread compound and shape deliver a longer tread life.

85,000-Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
185/60R15 84H	110132801	SL	800/A/A	18.1	5.5	5.0 - 6.5	7.4	23.8	5.9	11	10.9	873	1102@51	-	BW
185/65R15 88H	110132802	SL	800/A/A	18.6	5.5	5.0 - 6.5	7.5	24.5	5.7	11	11.2	848	1235@51	-	BW
195/60R15 88H	110132803	SL	800/A/A	19.5	6	5.5 - 7.0	8	24.3	6.4	11	11.1	856	1235@51	-	BW
195/65R15 91H	110132804	SL	800/A/A	20.2	6	5.5 - 7.0	7.9	25	6.1	11	11.4	831	1356@51	-	BW
205/65R15 94H	110132805	SL	800/A/A	21.1	6	5.5 - 7.0	8.4	25.6	6.5	11	11.6	813	1477@51	-	BW
205/70R15 96T	110132806	SL	800/A/B	21.6	6	5.0 - 7.0	8.2	26.4	6.4	11	11.9	787	1565@51	-	BW
215/70R15 98T	110132807	SL	800/A/B	23.4	6.5	5.5 - 7.0	8.8	26.9	6.7	11	12.1	772	1653@51	-	BW
205/55R16 91H	110132809	SL	800/A/A	20.8	6.5	5.5 - 7.5	8.4	25	6.7	11	11.5	832	1356@51	-	BW
205/60R16 92H	110132810	SL	800/A/A	21.1	6	5.5 - 7.5	8.2	25.6	6.5	11	11.7	813	1389@51	-	BW
205/65R16 95H	110132811	SL	800/A/A	22	6	5.5 - 7.5	8.4	26.4	6.5	11	12.1	786	1521@51	-	BW
205/70R16 97T	110132812	SL	800/A/B	22.6	6	5.0 - 7.0	8.3	27.3	6.4	11	12.4	761	1609@51	-	BW
215/55R16 97H	110132813	XL	800/A/A	22.2	7	6.0 - 7.5	8.7	25.4	7	11	11.7	817	1609@50	-	BW
215/60R16 95H	110132814	SL	800/A/A	22.2	6.5	6.0 - 7.5	8.7	26.1	6.9	11	12	794	1521@51	-	BW
215/65R16 98H	110132815	SL	800/A/A	23	6.5	6.0 - 7.5	8.7	27	6.7	11	12.3	768	1653@51	-	BW
225/60R16 98H	110132816	SL	800/A/A	25.2	6.5	6.0 - 8.0	9.1	26.7	7.4	11	12.2	779	1653@51	-	BW
225/65R16 100H	110132817	SL	800/A/A	26.1	6.5	6.0 - 8.0	8.9	27.6	7	11	12.5	754	1764@51	-	BW
235/60R16 100H	110132818	SL	800/A/A	26.3	7	6.5 - 8.5	9.6	27.2	7.7	11	12.4	765	1764@51	-	BW
235/65R16 103T	110132819	SL	800/A/B	28.4	7	6.5 - 8.5	9.5	28	7.5	11	12.7	742	1929@51	-	BW
P195/60R16 89H	110132808	SL	800/A/A	20.2	6	5.5 - 7.0	8	25.2	6.4	11	11.6	823	1279@51	-	BW
205/50R17 93V	110132820	XL	800/A/A	21.8	6.5	5.5 - 7.5	8.2	25.1	6.7	11	11.7	828	1433@50	-	BW
215/45R17 87V	110132821	SL	800/A/A	21.7	7	7.0 - 8.0	8.4	24.6	7	11	11.5	843	1201@51	-	BW
215/50R17 95H	110132822	XL	800/A/A	24	7	6.0 - 7.5	8.7	25.5	7	11	11.9	816	1521@50	-	BW
215/55R17 94V	110132823	SL	800/A/A	24.6	7	6.0 - 7.5	8.8	26.3	7	11	12.1	789	1477@51	-	BW
215/60R17 96H	110132824	SL	800/A/A	24.7	6.5	6.0 - 7.5	8.6	27.2	6.9	11	12.5	763	1565@51	-	BW
215/65R17 99H	110132825	SL	800/A/A	26	6.5	6.0 - 7.5	8.5	28	6.7	11	12.8	741	1709@51	-	BW
225/50R17 94V	110132826	SL	800/A/A	24.4	7	6.0 - 8.0	9.1	25.9	7.4	11	12	801	1477@51	-	BW
225/55R17 97H	110132827	SL	800/A/A	26	6.5	6.0 - 8.0	9.1	26.9	7.4	11	12.4	772	1609@51	-	BW
225/60R17 99H	110132828	SL	800/A/A	27	6.5	6.0 - 8.0	9.1	27.7	7.4	11	12.7	749	1709@51	-	BW
225/65R17 102H	110132829	SL	800/A/A	27.7	6.5	6.0 - 8.0	9.1	28.6	7	11	13	727	1874@51	-	BW
235/50R17 96H	110132830	SL	800/A/A	26.1	7.5	6.5 - 8.5	9.5	26.3	7.7	11	12.1	789	1565@51	-	BW
235/60R17 102T	110132831	SL	800/A/B	27.6	7	6.5 - 8.5	9.5	28.1	7.7	11	12.8	739	1874@51	-	BW
235/65R17 104H	110132832	SL	800/A/A	29.8	7	6.5 - 8.5	9.6	29.1	7.5	11	13.2	715	1984@51	-	BW
225/45R18 95V	110132833	XL	800/A/A	25.2	7.5	7.0 - 8.5	8.8	26	7.4	11	12.1	799	1521@50	-	BW
225/55R18 98H	110132834	SL	800/A/A	28.8	7	6.0 - 8.0	9.1	27.7	7.4	11	12.8	749	1653@51	-	BW
225/60R18 100H	110132835	SL	800/A/A	29.4	6.5	6.0 - 8.0	9.1	28.8	7.4	11	13.2	722	1764@51	-	BW
235/45R18 94V	110132836	SL	800/A/A	26.2	8	7.5 - 9.0	9.2	26.4	7.8	11	12.3	786	1477@51	-	BW
235/55R18 100V	110132837	SL	800/A/A	30	7.5	6.5 - 8.5	9.6	28.1	7.7	11	12.9	739	1764@51	-	BW
235/60R18 103H	110132838	SL	800/A/A	30.2	7	6.5 - 8.5	9.6	29.1	7.7	12	13.3	714	1929@51	-	BW

AVID Ascend LX®

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
P215/50R18 92V	110132839	SL	800/A/A	25.8	7	6.0 - 7.5	8.7	26.5	7	11	12.3	783	1389@51	-	BW

AVID TOURING-S®

ALL-SEASON **Passenger Cars | Crossovers/SUVs | Minivans**

A tire you can trust to deliver competitive comfort, stability and traction in all conditions.



FEATURES AND BENEFITS

LONG TREAD LIFE
Innovative compound provides long wear and confident traction.

QUIET RIDE
Packed with features that combine to deliver a quiet and comfortable ride.

COMPETITIVE WET TRACTION
Symmetric tread design with multiple grooves and sipes for wet and winter weather confidence.

COMPETITIVE HANDLING
A still sidewall and tread block are built strong for sure-footed handling.

65,000-Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/70R15 98S	110131813	SL	620/A/B	24.5	6.5	5.5 - 7.0	8.9	26.9	6.9	10	12.1	774	1653@51	-	BW
P185/60R15 84T	110131805	SL	620/A/B	18	5.5	5.0 - 6.5	7.4	23.7	5.9	10	10.9	875	1102@51	-	BW
P185/65R15 86S	110131806	SL	620/A/B	18.4	5.5	5.0 - 6.5	7.4	24.4	5.6	10	11.2	850	1168@51	-	BW
P195/60R15 87T	110131807	SL	620/A/B	19	6	5.5 - 7.0	7.8	24.3	6.2	10	11.1	856	1190@51	-	BW
P195/65R15 89S	110131808	SL	620/A/B	19.4	6	5.5 - 7.0	8	25	5.9	10	11.4	831	1279@51	-	BW
P205/65R15 92S	110131809	SL	620/A/B	21.2	6	5.5 - 7.5	8.3	25.4	6.2	10	11.6	818	1400@51	-	BW
P215/60R15 93T	110131811	SL	620/A/B	21.4	6.5	6.0 - 7.5	8.7	25.1	6.9	10	11.4	827	1411@51	-	BW
215/65R16 98T	110131817	SL	620/A/B	24.3	6.5	6.0 - 7.5	8.7	27	6.9	10	12.3	770	1653@51	-	BW
235/65R16 103T	110131824	SL	620/A/B	27.6	7	6.5 - 8.2	9.4	27.9	6.9	10	12.6	744	1929@51	-	BW
P205/55R16 89T	110131814	SL	620/A/B	21.1	6.5	5.5 - 7.5	8.5	24.9	7	10	11.5	835	1279@51	-	BW
P205/60R16 91T	110131815	SL	620/A/B	21.3	6	5.5 - 7.5	8.2	25.6	6.5	10	11.8	810	1356@51	-	BW
P215/60R16 94T	110131816	SL	620/A/B	22.4	6.5	6.0 - 7.5	8.8	26.1	6.9	10	12	794	1477@51	-	BW
P215/70R16 99T	110131822	SL	620/A/B	26.3	6.5	5.5 - 7.0	8.7	27.8	6.1	10	12.6	746	1709@51	-	BW
P225/60R16 97S	110131818	SL	620/A/B	24.5	6.5	6.0 - 8.0	9	26.6	7.2	10	12.1	780	1609@51	-	BW
P235/70R16 104T	110131823	SL	620/A/B	29.6	7	6.0 - 8.0	9.3	28.9	6.7	11	13	719	1984@51	-	BW
215/55R17 94H	110131830	SL	620/A/A	25.8	7	6.0 - 7.5	8.8	26.4	7.4	11	12.2	787	1477@51	-	BW
215/60R17 96T	110131825	SL	620/A/B	26	6.5	6.0 - 7.5	8.6	27.2	6.5	10	12.5	765	1565@51	-	BW
215/65R17 99T	110131826	SL	620/A/B	25.8	6.5	6.0 - 7.5	8.6	28.1	6.3	10	12.8	740	1709@51	-	BW
225/50R17 94H	110131831	SL	620/A/A	26	7	6.0 - 8.0	9.1	25.9	7.8	11	10.1	801	1477@51	-	BW
225/55R17 97T	110131827	SL	620/A/B	26.2	7	6.0 - 8.0	9.1	26.8	7.2	10	12.3	776	1609@51	-	BW
225/65R17 102T	110131828	SL	620/A/B	27.2	6.5	6.0 - 8.0	8.9	28.5	6.5	10	13	729	1874@51	-	BW
235/60R17 102T	110131832	SL	620/A/B	27.8	7	6.5 - 8.5	9.4	28.2	7.4	11	11	737	1874@51	-	BW
235/65R17 104T	110131829	SL	620/A/B	29	7	6.5 - 8.5	9.4	29	6.9	10	13.2	716	1984@51	-	BW
P225/60R17 98T	110131819	SL	620/A/B	27.6	6.5	6.0 - 8.0	8.9	27.7	7.2	10	12.7	749	1653@51	-	BW

GEOLANDAR X-MT

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON | OFF-ROAD **Crossovers/SUVs | Trucks**

The hardest of hard-core off-road tires in the GEOLANDAR family takes you to the top without looking back.



FEATURES AND BENEFITS

EXTREME OFF-ROAD TRACTION
High void-to-lug ratio and deep side blocks provide game-changing traction on even the steepest climbs.

OFF-ROAD DURABILITY
With GEO-SHIELD® construction wrapped in a high-density compound, hazardous terrain will never look the same.

LONG TREAD LIFE
High-density, triple-polymer tread compound produces slow, even wear.

QUIET RIDE
Optimized tread pattern reduces pattern noise for a quieter, more comfortable on-road ride.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
35X12.50R17 121Q	110155501	E	NA	75	10	8.5 - 11.0	13	34.8	10.2	21	15.4	598	3195@65	-	BW
37X12.50R17 121Q	110155504	D	NA	80.2	10	8.5 - 11.0	13	36.8	10.2	21	16.2	565	3525@50	-	BW
37X13.50R17 121Q	110155505	E	NA	84	11	8.5 - 11.0	13.9	36.7	11.1	21	16.2	566	3195@65	-	BW
40X13.50R17 121Q	110155509	D	NA	93.5	11	8.5 - 11.0	14.2	39.7	11.1	21	17.3	523	3195@50	-	BW
35X12.50R18 123Q	110155502	E	NA	75.4	10	8.5 - 11.0	13.1	34.8	10.2	21	15.5	598	3415@65	-	BW
37X13.50R18 124Q	110155506	D	NA	84	11	8.5 - 11.0	14	36.7	11.1	21	16.3	566	3525@50	-	BW
38X13.50R18 126Q	110155516	D		85.3	11	9.0 - 11.5	13.7	37.6	11.1	21	16.7	552	3750@50	-	BW
38X15.50R18 128Q	110155517	D	NA	90.6	12.5	11.0 - 14.0	15.7	37.7	12.2	21	16.7	551	3970@50	-	BW
35X12.50R20 121Q	110155503	E	NA	74.5	10	8.5 - 11.0	12.7	34.8	10.2	21	15.8	597	3195@65	-	BW
38X13.50R20 128Q	110155507	E	NA	86.9	11	9.5 - 12.0	13.8	37.7	11.1	21	16.9	551	3970@65	-	BW
38X15.50R20 125Q	110155508	D	NA	91	12	11.0 - 14.0	15.2	37.7	12.2	21	16.9	551	3640@50	-	BW
40X15.50R20 128Q	110155510	D	NA	97.2	12	11.0 - 14.0	15.2	39.8	12.2	21	17.7	522	3970@50	-	BW
38X13.50R22 126Q	110155514	E	NA	86	11	9.5 - 12.0	13.9	37.7	11.1	21	17.1	551	3750@65	-	BW
38X15.50R22 128Q	110155515	E	NA	92.8	12.5	11.0 - 14.0	15.4	37.7	12.2	21	17.1	551	3970@65	-	BW
40X15.50R22 128Q	110155511	E	NA	98.5	12.5	11.0 - 14.0	15.7	39.8	12.2	21	17.9	522	3970@65	-	BW
38X13.50R24 123Q	110155512	E	NA	86.6	11	8.5 - 11.0	13.7	37.8	11.1	21	17.4	550	3415@65	-	BW
40X15.50R24 128Q	110155513	E	NA	98.1	12.5	11.0 - 14.0	15.4	39.9	12.2	21	18.2	521	3970@65	-	BW

GEOLANDAR M/T G003

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON | OFF-ROAD **Crossovers/SUVs | Trucks**

Rock-solid engineering results in a tire capable of conquering just about anything that dares stand in its way.



FEATURES AND BENEFITS

OFF-ROAD TRACTION
An innovative tread pattern and triple-polymer compound provide outstanding grip wherever you venture.

OFF-ROAD DURABILITY
Rock-solid GEO-SHIELD® construction is engineered to withstand punishment from even the most brutal trail.

QUIET RIDE
Advanced pitch variation contributes to a quieter, comfortable highway ride.

LONG TREAD LIFE
High-density triple-polymer compound and wide, flat profile combine for exceptional wear performance.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
30X9.50R15 104Q	110133305	C	NA	40.8	7.5	6.5 - 8.5	9.6	29.8	7.7	19	13.3	698	1985@50	-	BW
31X10.50R15 109Q	110133301	C	NA	47.6	8.5	7.0 - 9.0	10.9	30.7	8.6	19	13.6	676	2270@50	-	BW
32X11.50R15 113Q	110133303	C	NA	55.1	9	8.0 - 10.0	11.8	31.7	9.3	20	14	655	2535@50	-	BW
33X12.50R15 108Q	110133304	C	NA	57.1	10	8.0 - 10.5	12.9	32.6	10.2	21	14.4	636	2205@35	-	BW
35X12.50R15 113Q	110133302	C	NA	67.2	10	8.5 - 11.0	13.1	34.6	10.2	21	15.2	600	2535@35	-	BW
LT215/75R15 100/97Q	110133306	C	NA	32.4	6	5.5 - 7.0	8.2	28	6.8	17	12.6	743	1765@50	1610@50	BW
LT235/75R15 104/101Q	110133307	C	NA	37	6.5	6.0 - 7.0	9.1	29.2	7.4	17	13	712	1985@50	1820@50	BW
LT225/75R16 115/112Q	110133313	E	NA	43.9	6	6.0 - 7.5	8.7	29.5	7	17	13.3	704	2680@80	2470@80	BW
LT235/85R16 120/116Q	110133311	E	NA	50.5	6.5	6.0 - 7.5	9.4	32.1	7.4	17	14.3	647	3042@80	2778@80	BW
LT245/75R16 120/116Q	110133312	E	NA	48.3	7	6.5 - 8.0	9.8	30.5	7.8	17	13.6	682	3042@80	2778@80	BW
LT255/85R16 123/120Q	110133349	E	NA	54.9	7	6.5 - 8.0	10	33.2	7.8	18	14.7	626	3415@80	3085@80	BW
LT265/75R16 123/120Q	110133310	E	NA	54.9	7.5	7.0 - 8.0	10.7	31.9	8.4	18	14.2	651	3415@80	3085@80	BW
LT285/75R16 126/123Q	110133309	E	NA	60.2	8	7.5 - 9.0	11.4	33.2	9	19	14.7	626	3750@80	3415@80	BW
LT305/70R16 124/121Q	110133314	E	NA	64.2	9	8.0 - 10.0	12.4	33.1	10	20	14.7	628	3525@65	3195@65	BW
LT315/75R16 127/124 Q	110133308	E	NA	68.8	8.5	8.0 - 11.0	12.5	34.8	10	20	15.3	598	3860@65	3525@65	BW
265/70R17 116T	110133381	XL	500/B/B	41.7	8	7.0 - 9.0	10.7	31.7	8.6	14	14.2	656	2756@50	-	BW
33X12.50R17 120Q	110133323	E	NA	64.8	10	8.5 - 11.0	12.8	32.6	10.2	21	14.6	636	3085@65	-	BW
35X12.50R17 121Q	110133316	E	NA	70.8	10	8.5 - 11.0	13.2	34.7	10.2	21	15.4	598	3195@65	-	BW
37X12.50R17 124Q	110133317	D	NA	76.1	10	8.5 - 11.0	13.1	36.8	10.2	21	16.2	565	3525@50	-	BW
40X13.50R17 121Q	110133353	D	NA	86.9	11	8.5 - 11.0	14.2	39.7	10.9	21	17.3	523	3195@50	-	BW
LT225/65R17 107/103Q	110133339	D	NA	39.2	6.5	6.0 - 8.0	8.6	28.7	7.2	17	13.1	723	2150@65	1930@65	BW
LT235/80R17 120/117 Q	110133321	E	NA	49.4	6.5	6.0 - 7.5	9.2	32.1	7.4	17	14.4	647	3085@80	2835@80	BW
LT245/70R17 119/116Q	110133373	E	NA	49.8	7	6.5 - 8.0	9.7	30.8	7.8	17	13.9	674	3000@80	2755@80	BW
LT245/75R17 121/118 Q	110133322	E	NA	51.6	7	6.5 - 7.5	9.9	31.7	7.8	17	14.2	655	3195@80	2910@80	BW
LT255/75R17 111/108 Q	110133319	C	NA	48.7	7	6.5 - 8.5	10	32.3	8	18	14.5	643	2405@50	2205@50	BW
LT255/80R17 121/118Q	110133367	E	NA	53.4	7	6.5 - 8.5	9.8	33.3	7.8	18	14.8	624	3195@80	2910@80	BW
LT265/65R17 120/117Q	110133366	E	NA	53.2	8	8.0 - 9.5	10.7	30.7	8.7	18	13.8	677	3085@80	2835@80	BW
LT265/70R17 121/118 Q	110133315	E	NA	56.4	8	7.0 - 8.5	10.9	31.9	8.7	18	14.3	651	3195@80	2910@80	BW
LT275/70R17 121/118Q	110133368	E	NA	58.2	8	7.0 - 9.0	11	32.4	8.9	19	14.5	640	3195@80	2910@80	BW
LT285/70R17 121/118 Q	110133320	E	NA	58.2	8.5	7.5 - 9.0	11.6	32.9	9.4	19	14.7	632	3195@80	2910@80	BW
LT285/75R17 121/118Q	110133342	E	NA	63.3	8	7.5 - 9.5	11.1	34.1	9	19	15.2	610	3195@80	2910@80	BW
LT295/70R17 121/118 Q	110133318	E	NA	65.5	8.5	7.5 - 10.0	12	33.5	9.6	20	15	619	3195@80	2910@80	BW
33X12.50R18 122Q	110133360	F	NA	64.9	10	8.5 - 11.0	12.7	32.7	10.2	21	14.7	635	3305@80	-	BW
33X12.50R18 118Q	110133327	E	NA	65	10	8.5 - 11.0	12.8	32.6	10.2	21	14.7	637	2910@65	-	BW
35X12.50R18 128Q	110133361	F	NA	71.5	10	8.5 - 11.0	13.1	34.8	10.2	21	15.5	598	3970@80	-	BW
35X12.50R18 123Q	110133326	E	NA	71.6	10	8.5 - 11.0	12.9	34.7	10.2	21	15.5	598	3415@65	-	BW
37X12.50R18 128Q	110133374	E	NA	74.3	10	8.0 - 10.5	13	36.7	10.2	21	16.3	566	3970@65	-	BW
LT275/65R18 123/120Q	110133330	E	NA	58.2	8	7.5 - 9.0	10.9	32.4	9	19	14.6	642	3415@80	3085@80	BW

GEOLANDAR M/T G003

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
LT275/70R18 125/122 Q	110133329	E	NA	61.9	8	7.0 - 8.5	11.2	33.1	9	19	14.9	627	3640@80	3305@80	BW
LT285/65R18 125/122 Q	110133328	E	NA	60.4	8.5	8.0 - 10.0	11.6	32.8	9.4	19	14.8	633	3640@80	3305@80	BW
LT285/70R18 127/124Q	110133346	E	NA	64.2	8.5	7.5 - 9.5	11.4	33.9	9.2	19	15.2	612	3860@80	3525@80	BW
LT285/75R18 129/126Q	110133343	E	NA	65.7	8	7.5 - 9.5	11.2	35	9	19	15.6	594	4080@80	3750@80	BW
LT295/70R18 129/126Q	110133325	E	NA	65.9	8.5	7.5 - 10.0	12	34.6	9.6	20	15.5	600	4080@80	3750@80	BW
LT305/70R18 126/123 Q	110133324	E	NA	69.9	9	8.5 - 10.0	12.4	34.8	10	20	15.5	598	3750@65	3415@65	BW
LT315/70R18 127/124Q	110133365	E	NA	71.6	9.5	8.0 - 10.5	12.4	35.6	10.1	20	15.9	584	3860@65	3525@65	BW
275/65R20 116H	110133382	XL	500/B/B	47.8	8	7.5 - 9.5	11	34.1	8.8	15	15.5	609	2756@50	-	BW
33X12.50R20 114Q	110133332	E	NA	64.8	10	8.5 - 11.0	12.7	32.7	10.2	21	14.9	636	2600@65	-	BW
33X12.50R20 119Q	110133362	F	NA	66.1	10	8.5 - 11.0	12.6	32.7	10.2	21	15	635	3000@80	-	BW
35X12.50R20 121Q	110133331	E	NA	71.2	10	8.5 - 11.0	12.6	34.7	10.2	21	15.7	598	3195@65	-	BW
35X11.50R20 124Q	110133357	E	NA	67.7	9	8.0 - 10.5	11.3	34.8	9.3	21	15.8	597	3525@80	-	BW
35X12.50R20 125Q	110133359	F	NA	71.3	10	8.5 - 11.0	12.6	34.8	10.2	21	15.8	597	3640@80	-	BW
35X13.50R20 126Q	110133370	F	NA	76.3	11	9.5 - 12.0	13.7	34.7	11.1	21	15.7	599	3750@80	-	BW
37X12.50R20 126Q	110133337	E	NA	76.7	10	8.5 - 11.0	12.8	36.7	10.2	21	16.5	566	3750@65	-	BW
37X13.50R20 127Q	110133334	E	NA	80.9	11	8.5 - 11.0	13.9	36.6	11.1	21	16.5	567	3860@65	-	BW
LT275/55R20 120/117Q	110133352	E	NA	57.5	8.5	7.5 - 9.5	10.9	32.2	9.1	19	14.7	646	3085@80	2835@80	BW
LT275/60R20 123/120Q	110133372	E	NA	56.4	8	8.0 - 9.5	10.8	33.3	9.1	19	15.2	623	3415@80	3085@80	BW
LT275/65R20 126/123 Q	110133335	E	NA	64.8	8	7.5 - 9.5	11	34.3	9	19	15.6	605	3750@80	3415@80	BW
LT285/60R20 125/122Q	110133371	E	NA	60.7	8.5	8.5 - 10.0	11.4	33.7	9.4	19	15.4	616	3640@80	3305@80	BW
LT285/65R20 127/124Q	110133375	E	NA	61.6	8.5	8.5 - 10.0	11.6	34.7	9.4	19	15.7	598	3860@80	3525@80	BW
LT295/55R20 123/120Q	110133344	E	NA	63.9	9.5	8.0 - 10.0	12	33	9.9	20	15.1	629	3415@80	3085@80	BW
LT295/60R20 126/123 Q	110133336	E	NA	66.8	8.5	8.0 - 10.0	11.7	34.1	9.6	20	15.5	609	3750@80	3415@80	BW
LT295/65R20 129/126Q	110133364	E	NA	69.2	8.5	8.5 - 10.5	11.6	35.3	9.6	20	16	589	4080@80	3750@80	BW
LT305/55R20 121/118 Q	110133333	E	NA	65	9.5	8.5 - 11.0	12.4	33.4	10	20	15.2	622	3195@65	2910@65	BW
LT305/55R20 125/122Q	110133358	F	NA	64.9	9.5	9.0 - 11.0	12.4	33.5	10	20	15.3	620	3640@80	3305@80	BW
LT315/60R20 125/122Q	110133350	D	NA	71.9	9.5	8.5 - 11.0	12.8	35	10.4	20	15.9	593	3640@65	3305@65	BW
LT325/60R20 126/123Q	110133376	E	NA	74.7	9.5	9.5 - 11.5	13	35.6	10.6	20	16.1	584	3750@65	3415@65	BW
33X12.50R22 109Q	110133354	E	NA	65.4	10	8.5 - 11.0	12.2	32.8	10.4	21	15.2	634	2270@65	-	BW
35X12.50R22 121Q	110133363	F	NA	71.3	10	8.5 - 11.0	12.7	34.8	10.2	21	16	598	3195@80	-	BW
35X12.50R22 117Q	110133348	E	NA	70.1	10	8.5 - 11.0	12.8	34.7	10.2	21	16	598	2835@65	-	BW
37X12.50R22 123Q	110133341	E	NA	76.9	10	9.0 - 11.5	12.1	36.9	10.2	21	16.8	564	3415@65	-	BW
37X13.50R22 123Q	110133340	E	NA	80.7	11	8.5 - 11.0	13.1	36.8	11.1	21	16.8	564	3415@65	-	BW
LT285/55R22 124/121Q	110133347	E	NA	63.9	9	8.0 - 10.0	11.6	34.8	9.5	19	16	598	3525@80	3195@80	BW
LT325/50R22 122Q	110133351	E	NA	75.8	10	9.5 - 11.5	13.1	35.1	10.8	20	16.1	592	3305@65	-	BW
37X13.50R24 120Q	110133345	E	NA	77.8	11	8.5 - 11.0	13.2	36.9	11.1	21	17	564	3085@65	-	BW

GEOLANDAR M/T® G003 SxS

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON | OFF-ROAD **Side-by-Sides/UTVs**

Built specifically for side-by-sides with a cut and chip-resistant compound, offering durability and tenacious traction.



FEATURES AND BENEFITS

OFF-ROAD DURABILITY
Rock-solid GEO-SHIELD® construction is engineered to withstand punishment from even the most brutal trail.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
32X9.50R15 101Q	110133377	B		43.9	7.5	6.0 - 8.0	9.6	31.7	7.4	18	14	655	1820@35	-	BW
33X9.50R15 104Q	110133378	B		47.1	7.5	6.0 - 8.0	9.8	32.6	7.4	18	14.4	636	1985@35	-	BW
35X9.50R15	110133380	B		52.7	7.5	6.0 - 8.0	10.2	34.6	7.7	18	15.2	599	2205@35	-	BW
37X11.50R17 121Q	110133379	C		70.5	9	7.5 - 10.0	11.9	36.7	9.1	21	16.2	566	3195@50	-	BW

GEOLANDAR A/T XD

ALL-SEASON | OFF-ROAD | COMMERCIAL GRADE **Trucks | Work Vans**

A commercial grade all-terrain tire engineered to provide outstanding on- and off-road durability for full size pickup trucks and commercial vans all year round.



FEATURES AND BENEFITS

ON/OFF ROAD DURABILITY
GEO-SHIELD® technology and sidewall armor provide dependable protection against impacts and punctures for ultimate peace of mind while on the job site.

OUTSTANDING ALL-WEATHER PERFORMANCE
Engineered to tackle the most extreme winter conditions as the temperatures drop while maintaining all-season performance.

LONG TREAD LIFE
Built to provide long tread life without compromising all-weather performance.

ENHANCED CUT & CHIP RESISTANCE
Advanced compound provides long wear in harsh conditions.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
LT215/85R16 115/112Q	110117101	E	NA	42.3	6	5.5 - 7.0	8.5	30.6	6.5	18	13.7	680	2680@80	2470@80	BW
LT225/75R16 115/112Q	110117102	E	NA	42.4	6	6.0 - 7.5	8.7	29.4	7	18	13.2	707	2680@80	2470@80	BW
LT235/85R16 120/116Q	110117103	E	NA	49.2	6.5	6.0 - 7.5	9.3	31.8	7.4	18	14.2	654	3042@80	2778@80	BW
LT245/75R16 120/116Q	110117104	E	NA	48.1	7	6.5 - 8.0	9.7	30.5	7.8	18	13.6	682	3042@80	2778@80	BW
LT265/75R16 123/120Q	110117105	E	NA	54.2	7.5	7.0 - 9.0	10.6	31.7	8.4	19	14.1	656	3415@80	3085@80	BW
35X12.50R17 121Q	110117106	E	NA	71.7	10	8.0 - 10.5	12.8	34.5	10.2	22	15.3	602	3195@65	-	BW
37X12.50R17 128Q	110117132	F	NA	76.5	10	8.0 - 10.5	13.1	36.5	10.2	22	16.1	569	3970@80	-	BW
LT235/80R17 120/117Q	110117107	E	NA	49	6.5	6.0 - 8.0	9.4	31.8	7.4	18	14.3	653	3085@80	2835@80	BW
LT245/70R17 119/116Q	110117108	E	NA	48.4	7	6.5 - 8.0	9.8	30.7	7.8	18	13.8	677	3000@80	2755@80	BW
LT245/75R17 121/118Q	110117109	E	NA	50.4	7	6.5 - 8.0	9.8	31.5	7.8	18	14.2	659	3195@80	2910@80	BW
LT265/70R17 121/118Q	110117110	E	NA	55.2	8	7.0 - 9.0	11	31.7	8.7	19	14.2	656	3195@80	2910@80	BW
LT285/70R17 121/118Q	110117111	E	NA	61.1	8.5	7.5 - 9.5	11.7	32.8	9.4	19	14.7	633	3195@80	2910@80	BW
LT315/70R17 128/125Q	110117134	F	NA	70.5	9.5	8.0 - 10.5	12.8	34.4	10.1	20	15.3	603	3970@80	3640@80	BW
35X12.50R18 123Q	110117112	E	NA	70.9	10	8.5 - 11.0	12.5	34.5	10.2	22	15.4	602	3415@65	-	BW
37X12.50R18 128Q	110117133	F	NA	76.9	10	8.0 - 10.5	12.8	36.5	10.2	22	16.2	569	3970@80	-	BW
LT265/65R18 122/119Q	110117113	E	NA	54.7	8	8.0 - 9.5	10.8	31.6	8.7	19	14.3	657	3305@80	3000@80	BW
LT265/70R18 124/121Q	110117114	E	NA	56	8	7.0 - 9.0	10.8	32.6	8.7	19	14.7	636	3525@80	3195@80	BW
LT275/65R18 123/120Q	110117115	E	NA	56.8	8	8.0 - 9.5	11.1	32	9	19	14.5	648	3415@80	3085@80	BW
LT275/70R18 125/122Q	110117116	E	NA	59.3	8	7.0 - 9.0	11	33.2	9	19	14.9	625	3640@80	3305@80	BW
LT285/65R18 125/122Q	110117117	E	NA	60.2	8.5	8.5 - 10.0	11.7	32.5	9.4	19	14.7	639	3640@80	3305@80	BW
LT285/75R18 129/126Q	110117118	E	NA	65.4	8	7.5 - 9.5	11.4	34.8	9	19	15.6	597	4080@80	3750@80	BW
LT295/70R18 129/126Q	110117119	E	NA	67.2	8.5	7.5 - 10.0	11.9	34.3	9.6	20	15.3	606	4080@80	3750@80	BW
LT305/70R18 128/125Q	110117135	F	NA	70.5	9	8.0 - 10.0	12.3	34.8	10	20	15.6	596	3970@80	3640@80	BW
33X12.50R20 114Q	110117120	E	NA	66.7	10	8.5 - 11.0	12.6	32.5	10.2	22	14.9	639	2600@65	-	BW
35X12.50R20 121Q	110117121	E	NA	70.7	10	8.5 - 11.0	12.4	34.5	10.2	22	15.7	602	3195@65	-	BW
37X12.50R20 128Q	110117131	F	NA	77.6	10	8.5 - 11.0	12.6	36.5	10.2	22	16.4	569	3970@80	-	BW
LT265/60R20 121/118Q	110117122	E	NA	56.9	8	8.0 - 9.5	10.8	32.6	9	19	14.9	637	3195@80	2910@80	BW
LT275/55R20 120/117Q	110117123	E	NA	56.5	8.5	8.0 - 9.5	11.3	31.9	9.1	19	14.6	652	3085@80	2835@80	BW
LT275/60R20 123/120Q	110117124	E	NA	59.5	8	8.0 - 9.5	11.1	33.1	9.1	19	15.1	627	3415@80	3085@80	BW
LT275/65R20 126/123Q	110117125	E	NA	62.1	8	8.0 - 9.5	11.1	34.1	9	19	15.5	609	3750@80	3415@80	BW
LT285/60R20 125/122Q	110117126	E	NA	62	8.5	8.5 - 10.0	11.6	33.5	9.4	19	15.3	620	3640@80	3305@80	BW
LT285/65R20 127/124Q	110117130	E	NA	63.5	8.5	8.5 - 10.0	11.7	34.6	9.4	19	15.7	600	3860@80	3525@80	BW
LT295/60R20 126/123Q	110117136	E	NA	64.6	8.5	8.5 - 10.5	11.8	33.9	9.6	20	15.4	612	3750@80	3415@80	BW
LT295/65R20 129/126Q	110117127	E	NA	68.1	8.5	8.5 - 10.5	12	35.1	9.6	20	15.9	592	4080@80	3750@80	BW
LT305/55R20 121/118Q	110117128	E	NA	65.8	9.5	9.0 - 11.0	12.6	33.1	10	20	15.1	627	3195@65	2910@65	BW

GEOLANDAR X-AT®

ALL-SEASON | OFF-ROAD **Crossovers/SUVs | Trucks**

Extreme versatility takes you from peak to pavement and back with absolute authority.



FEATURES AND BENEFITS

OFF-ROAD DURABILITY
Protects against impacts and punctures for ultimate peace of mind.

LONG TREAD LIFE
Optimized contact area and unique compound provide flatter footprint and longer tread life.

QUIET RIDE
Distinctive tread grooves dramatically reduce pattern and road noise for a smooth, quiet ride in the segment.

OFF-ROAD TRACTION
Specially-engineered tread pattern provides strength and grip no matter how rugged the road.

50,000-Mile Limited Treadwear Warranty (Euro-Metric Sizes)

45,000-Mile Limited Treadwear Warranty (LT-Metric Sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
31X10.50R15 109Q	110116001	C	NA	46.3	8.5	7.0 - 9.0	10.6	30.7	8.4	17	13.6	676	2270@50	-	BW
245/75R16 111T	110116078	SL	500/A/B	38.3	7	6.5 - 8.0	9.8	30.5	7.5	14	13.6	682	2403@51	-	BW
265/70R16 116T	110116079	XL	500/A/B	40.5	8	7.0 - 9.0	10.8	30.6	8.1	14	13.7	678	2756@50	-	BW
LT235/70R16 104/101Q	110116037	C	NA	40.3	7	6.0 - 8.0	9.4	29.2	7.5	16	13.2	711	1985@50	1820@50	BW
LT235/85R16 120/116Q	110116052	E	NA	50.1	6.5	6.0 - 7.5	9.4	31.9	7.3	16	14.2	651	3042@80	2778@80	BW
LT245/70R16 118/115Q	110116053	E	NA	48.2	7	6.5 - 8.0	9.9	29.8	7.9	16	13.4	697	2910@80	2680@80	BW
LT265/70R16 121/118Q	110116054	E	NA	52.3	8	7.0 - 9.0	10.9	30.8	8.6	17	13.8	674	3195@80	2910@80	BW
LT265/75R16 123/120Q	110116002	E	NA	54.5	7.5	7.0 - 8.0	10.4	32	8.3	17	14.2	650	3415@80	3085@80	BW
LT275/70R16 119/116Q	110116055	D	NA	57.1	8	7.0 - 9.0	11.1	31.4	8.8	18	14	662	3000@65	2755@65	BW
LT285/75R16 126/123Q	110116056	E	NA	58.2	8	7.5 - 9.5	11.4	33.1	8.9	18	14.7	628	3750@80	3415@80	BW
LT315/75R16 127/124Q	110116057	E	NA	69.4	8.5	8.0 - 10.5	12.4	34.8	9.8	19	15.3	598	3860@65	3525@65	BW
235/75R17 109T	110116080	SL	500/A/B	38.8	6.5	6.0 - 8.0	9.3	30.8	7.2	14	13.9	674	2271@51	-	BW
245/70R17 110T	110116081	SL	500/A/B	38.2	7	6.5 - 8.0	9.8	30.5	7.5	14	13.8	681	2337@51	-	BW
255/65R17 114T	110116082	XL	500/A/B	38.2	7.5	7.0 - 9.0	10.2	30	7.8	14	13.6	692	2601@50	-	BW
255/70R17 112T	110116083	SL	500/A/B	40.8	7.5	6.5 - 8.5	10.2	31.1	7.8	14	14	669	2469@51	-	BW
265/65R17 116T	110116084	XL	500/A/B	39.7	8	7.5 - 9.5	10.7	30.6	8.2	14	13.8	680	2756@50	-	BW
265/70R17 115T	110116085	SL	500/A/B	42.5	8	7.0 - 9.0	10.7	31.7	8.1	14	14.2	655	2679@51	-	BW
33X12.50R17 121Q	110116067	F	NA	64.8	10	8.5 - 11.0	12.6	32.8	10	19	14.6	634	3195@80	-	BW
35X11.50R17 128Q	110116099	E		65.3	9	7.5 - 10.0	11.8	34.7	9.1	18	15.4	599	3970@80	-	BW
35X12.50R17 121Q	110116003	E	NA	70.3	10	8.0 - 10.5	12.8	34.8	10	19	15.4	597	3195@65	-	BW
37X12.50R17 124Q	110116004	D	NA	76.9	10	8.5 - 11.0	13.1	36.8	10	19	16.2	565	3525@50	-	BW
37X13.50R17 121Q	110116005	E	NA	80.2	11	8.5 - 11.0	14.1	36.8	10.9	19	16.2	565	3195@65	-	BW
LT235/80R17 120/117Q	110116039	E	NA	50.9	6.5	6.0 - 8.0	9.3	32.2	7.3	16	14.4	646	3085@80	2835@80	BW
LT245/70R17 119/116S	110116058	E	NA	50.4	7	6.5 - 8.0	9.9	30.8	7.8	15	13.9	674	3000@80	2755@80	BW
LT245/75R17 121/118Q	110116038	E	NA	50.9	7	6.5 - 8.0	9.6	31.8	7.7	16	14.3	653	3195@80	2910@80	BW
LT255/80R17 121/118Q	110116068	E	NA	53.2	7	6.5 - 8.5	10.1	33.3	7.7	16	14.8	624	3195@80	2910@80	BW
LT265/65R17 120/117Q	110116028	E	NA	53.1	8	8.0 - 9.5	10.9	30.7	8.6	17	13.8	676	3085@80	2835@80	BW
LT265/70R17 121/118Q	110116006	E	NA	55.8	8	7.0 - 8.5	10.8	32	8.6	17	14.3	650	3195@80	2910@80	BW
LT265/70R17 112/109T	110116059	C	NA	48.7	8	7.0 - 9.0	10.9	31.9	8.6	16	14.3	652	2470@50	2270@50	BW
LT275/70R17 114/110R	110116061	C	NA	55.2	8	7.0 - 9.0	11	32.4	8.8	17	14.5	642	2600@50	2335@50	BW
LT285/70R17 121/118S	110116063	D	NA	57.2	8.5	7.5 - 9.5	11.7	33	9.1	17	14.7	630	3195@65	2910@65	BW
LT285/70R17 121/118Q	110116007	E	NA	61.1	8.5	7.5 - 9.5	11.7	33	9.1	18	14.7	630	3195@80	2910@80	BW
LT285/75R17 121/118Q	110116064	E	NA	63.7	8	7.5 - 9.5	11.5	34	8.9	18	15.1	611	3195@80	2910@80	BW
LT295/70R17 121/118Q	110116008	E	NA	64.8	8.5	7.5 - 10.0	11.8	33.5	9.4	18	15	619	3195@80	2910@80	BW
LT305/70R17 121/118Q	110116069	E	NA	65	9	8.0 - 10.0	12.4	34	9.8	18	15.1	611	3195@65	2910@65	BW
LT315/70R17 113/110S	110116070	C	NA	61.1	9.5	8.0 - 10.5	12.7	34.6	10	17	15.4	601	2535@35	2335@35	BW
245/75R18 112T	110116086	SL	500/A/B	42	7	6.5 - 8.0	9.7	32.5	7.5	14	14.7	639	2469@51	-	BW
255/70R18 116T	110116087	XL	500/A/B	42.4	7.5	6.5 - 8.5	10.3	32	7.8	14	14.5	648	2756@50	-	BW

GEOLANDAR X-AT®

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
265/60R18 114T	110116088	XL	500/A/B	39.9	8	7.5 - 9.5	10.7	30.5	8.3	14	13.9	682	2601@50	-	BW
265/65R18 114T	110116089	SL	500/A/B	42	8	7.5 - 9.5	10.7	31.5	8.2	14	14.3	659	2601@51	-	BW
265/70R18 116T	110116110	SL	500/A/B	44.4	8	7.0 - 9.0	10.6	32.6	8.1	14	14.7	637	2756@51	-	BW
275/65R18 116T	110116090	XL	500/A/B	44.2	8	7.5 - 9.5	11	32.1	8.3	14	14.5	647	2756@50	-	BW
285/65R18 116T	110116091	SL	500/A/B	46.8	8.5	8.0 - 10.0	11.6	32.6	8.8	14	14.7	637	2756@51	-	BW
33X12.50R18 122Q	110116034	F	NA	64.1	10	8.5 - 11.0	12.6	32.7	10	19	14.7	636	3305@80	-	BW
33X12.50R18 118Q	110116009	E	NA	64.2	10	8.5 - 11.0	12.6	32.7	10	19	14.7	635	2910@65	-	BW
35X12.50R18 128Q	110116010	F	NA	72.8	10	8.5 - 11.0	12.5	34.7	10	19	15.5	598	3970@80	-	BW
37X12.50R18 128Q	110116071	E	NA	75.4	10	8.0 - 10.5	12.8	36.8	10	19	16.3	564	3970@65	-	BW
37X13.50R18 128Q	110116011	E	NA	80.2	11	8.5 - 11.0	13.8	36.7	10.9	19	16.3	566	3970@65	-	BW
LT255/60R18 117/114Q	110116065	E	NA	51.8	7.5	7.5 - 9.0	10.4	30.4	8.3	16	13.8	683	2835@80	2600@80	BW
LT265/60R18 119/116Q	110116048	E	NA	53.5	8	8.0 - 9.5	10.6	30.7	8.7	17	14	676	3000@80	2755@80	BW
LT265/65R18 122/119Q	110116040	E	NA	57	8	8.0 - 9.5	10.9	31.7	8.6	17	14.4	655	3305@80	3000@80	BW
LT265/70R18 124/121Q	110116042	E	NA	59.6	8	7.0 - 9.0	11	32.9	8.6	17	14.8	632	3525@80	3195@80	BW
LT275/65R18 123/120Q	110116041	E	NA	60.1	8	8.0 - 9.5	11.1	32.3	8.8	18	14.6	643	3415@80	3085@80	BW
LT275/70R18 125/122Q	110116012	E	NA	62.4	8	7.0 - 9.0	11	33.5	8.8	18	15	620	3640@80	3305@80	BW
LT285/60R18 122/119Q	110116029	E	NA	60.5	8.5	8.5 - 10.0	11.6	31.6	9.4	18	14.3	657	3305@80	3000@80	BW
LT285/65R18 125/122Q	110116013	E	NA	62.4	8.5	8.5 - 10.0	11.6	32.8	9.1	18	14.8	633	3640@80	3305@80	BW
LT285/70R18 127/124Q	110116072	E	NA	62.9	8.5	7.5 - 9.5	11.6	33.6	9.4	18	15.1	618	3860@80	3525@80	BW
LT285/75R18 129/126Q	110116014	E	NA	66.1	8	7.5 - 9.5	11.5	35.1	8.9	18	15.7	592	4080@80	3750@80	BW
LT295/70R18 129/126Q	110116015	E	NA	67.7	8.5	7.5 - 10.0	11.9	34.6	9.4	18	15.5	600	4080@80	3750@80	BW
LT305/65R18 124/121Q	110116073	E	NA	65.2	9	9.0 - 11.0	12.1	34	9.8	18	15.2	611	3525@65	3195@65	BW
LT305/70R18 126/123Q	110116016	E	NA	69.9	9	8.5 - 10.0	12.4	35	9.8	18	15.6	593	3750@65	3415@65	BW
LT325/65R18 127/124Q	110116030	E	NA	73.9	9.5	9.0 - 12.0	13.1	34.8	10.5	19	15.5	598	3860@65	3525@65	BW
265/60R20 112H	110116092	SL	500/B/B	43.9	8	7.5 - 9.5	10.7	32.4	8.3	14	14.9	640	2469@51	-	BW
275/55R20 117T	110116093	XL	500/B/B	44.8	8.5	7.5 - 9.5	11.3	31.8	8.9	14	14.6	653	2833@50	-	BW
275/60R20 116T	110116094	XL	500/B/B	45.3	8	7.5 - 9.5	11.2	33	8.5	14	15.1	630	2756@50	-	BW
275/65R20 116T	110116103		500/B/B	48.5	8	7.5 - 9.5	11.1	34.1	8.3	14	15.5	609	2756@51	-	BW
285/55R20 116T	110116104	XL	500/B/B	47	9	8.0 - 10.0	11.7	32.3	9.4	14	14.8	643	2756@50	-	BW
295/55R20 116T	110116105		500/B/B	48.1	9.5	8.0 - 10.5	12.2	32.7	9.8	14	15	635	2756@51	-	BW
305/50R20 120S	110116106	XL	500/B/B	47.2	9.5	8.5 - 11.0	12.3	32	10.4	14	14.7	648	3086@50	-	BW
305/55R20 116S	110116107	SL	500/B/B	50.3	9.5	8.5 - 11.0	12.3	33.1	10	14	15.1	627	2756@51	-	BW
33X11.50R20 118Q	110116100	E		59.9	9	8.0 - 10.5	11.4	32.8	9.1	18	15	634	2910@80	-	BW
33X12.50R20 119Q	110116035	F	NA	65.6	10	8.5 - 11.0	12.7	32.7	10	19	14.9	636	3000@80	-	BW
33X12.50R20 114Q	110116017	E	NA	65.7	10	8.5 - 11.0	12.6	32.6	10	19	14.9	636	2600@65	-	BW
35X11.50R20 124Q	110116074	E	NA	64.7	9	8.0 - 10.5	11.9	34.6	9.4	18	15.7	600	3525@80	-	BW
35X12.50R20 125Q	110116036	F	NA	71.2	10	8.5 - 11.0	12.6	34.7	10	19	15.7	599	3640@80	-	BW
35X12.50R20 121Q	110116018	E	NA	71.2	10	8.5 - 11.0	12.6	34.7	10	19	15.7	598	3195@65	-	BW
35X13.50R20 121Q	110116019	E	NA	74.7	11	9.5 - 12.0	13.5	34.7	10.9	19	15.7	598	3195@65	-	BW
37X11.50R20 128Q	110116101	E		69.7	9	7.5 - 10.0	11.6	36.9	9.1	18	16.6	564	3970@80	-	BW
37X12.50R20 126Q	110116020	E	NA	76.9	10	8.5 - 11.0	12.9	36.7	10	19	16.5	566	3750@65	-	BW
37X13.50R20 127Q	110116021	E	NA	80.7	11	8.5 - 11.0	13.7	36.8	10.9	19	16.5	565	3860@65	-	BW
38X13.50R20 128Q	110116097	E		82.1	11	9.5 - 12.0	13.8	37.8	10.9	19	16.9	550	3970@65	-	BW
LT265/60R20 121/118Q	110116043	E	NA	58	8	8.0 - 9.5	10.7	32.8	8.7	17	15	634	3195@80	2910@80	BW
LT275/55R20 120/117Q	110116044	E	NA	57.1	8.5	8.0 - 9.5	11.2	32.3	8.8	18	14.8	643	3085@80	2835@80	BW
LT275/65R20 126/123Q	110116022	E	NA	64.2	8	7.5 - 9.5	11.3	34.3	8.8	18	15.6	605	3750@80	3415@80	BW
LT285/55R20 122/119Q	110116032	E	NA	61.6	9	8.5 - 10.0	11.8	32.5	9.6	18	14.9	639	3305@80	3000@80	BW
LT285/60R20 125/122Q	110116033	E	NA	63.4	8.5	8.5 - 10.0	11.5	33.7	9.4	18	15.3	617	3640@80	3305@80	BW
LT285/65R20 127/124Q	110116066	E	NA	62.7	8.5	8.5 - 10.0	11.8	34.8	9.1	18	15.8	598	3860@80	3525@80	BW
LT295/55R20 123/120Q	110116075	E	NA	61.5	9.5	8.5 - 10.5	12.3	33	9.8	18	15.1	630	3415@80	3085@80	BW
LT295/60R20 126/123Q	110116046	E	NA	64.6	8.5	8.5 - 10.5	11.8	34.1	9.6	18	15.5	609	3750@80	3415@80	BW
LT295/65R20 129/126Q	110116023	E	NA	69.7	8.5	8.0 - 10.0	12	35.3	9.4	18	16	588	4080@80	3750@80	BW
LT305/55R20 121/118Q	110116024	E	NA	65.7	9.5	8.5 - 11.0	12.4	33.4	9.9	18	15.2	622	3195@65	2910@65	BW
LT315/60R20 125/122Q	110116096	E	NA	69.9	9.5	9.5 - 11.0	12.6	34.8	10.4	19	15.8	597	3640@65	3305@65	BW
LT325/60R20 126/123Q	110116031	E	NA	76.2	9.5	9.5 - 11.5	13.4	35.5	10.6	19	16	585	3750@65	3415@65	BW
275/50R22 115T	110116108	XL	500/B/B	47.2	8.5	7.5 - 9.5	11.3	32.9	9.4	14	15.2	632	2679@50	-	BW
305/45R22 118S	110116109	XL	500/B/B	46.3	10	9.5 - 11.5	11.9	32.7	10.4	14	15.2	636	2910@50	-	BW
33X12.50R22 114Q	110116047	F	NA	66.3	10	9.0 - 11.0	12.3	32.8	10.2	19	15.2	633	2600@80	-	BW
35X12.50R22 121Q	110116025	F	NA	71.9	10	8.5 - 11.0	12.6	34.7	10	19	16	598	3195@80	-	BW
37X12.50R22 127Q	110116026	F	NA	76.7	10	9.0 - 11.5	12.6	36.9	10	19	16.8	563	3860@80	-	BW
37X13.50R22 123Q	110116027	E	NA	81.1	11	8.5 - 11.0	13.5	36.8	10.9	19	16.8	564	3415@65	-	BW
LT285/50R22 121/118Q	110116102	E	NA	60.5	9	8.5 - 10.0	11.6	33.6	9.5	18	15.5	619	3195@80	2910@80	BW
LT285/55R22 124/121Q	110116095	E	NA	64.2	9	8.5 - 10.0	11.7	34.6	9.5	18	15.9	600	3525@80	3195@80	BW
LT295/55R22 125/122Q	110116098	E	NA	64.4	9.5	8.5 - 10.5	12.3	35.1	9.8	18	16.1	592	3640@80	3305@80	BW
37X13.50R24 124Q	110116076	F		76.4	11	9.5 - 12.0	13.4	36.9	10.9	19	17	563	3525@80	-	BW
LT315/50R24 127/124Q	110116077	F	NA	73	10	9.5 - 11.0	12.7	36.8	10	19	17	564	3860@80	3525@80	BW

GEOLANDAR A/T4

ALL-SEASON | OFF-ROAD **Crossovers/SUVs | Trucks**

An all-terrain tire with real off-road durability.



FEATURES AND BENEFITS

OUTSTANDING OFF-ROAD DURABILITY
Sturdy construction provides reliable off-road resilience and performance.

OPTIMIZED ON/OFF-ROAD TRACTION
Engineered for dynamic off-road traction and outstanding on-road performance.

RELIABLE ALL-WEATHER PERFORMANCE
Advanced tread pattern and compound provide excellent year-round performance in dry, wet, and snow-covered road conditions.

ON-ROAD COMFORT
Optimized construction and tread pattern provide on-road comfort and longer tread wear.

65,000-Mile Limited Treadwear Warranty (Euro-Metric Sizes)

55,000-Mile Limited Treadwear Warranty (LT-Metric Sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/70R15 96H	110101873	SL	660/A/B	23.5	6	5.0 - 7.0	8.2	26.3	6.2	13	11.9	790	1565@51	-	BW
215/70R15 98H	110101874	SL	660/A/B	25.1	6.5	5.5 - 7.0	8.7	26.9	6.5	13	12.1	772	1653@51	-	OWL
225/70R15 100T	110101875	SL	660/A/B	27.1	6.5	6.0 - 7.5	8.9	27.4	6.6	13	12.4	757	1764@51	-	OWL
235/70R15 103T	110101876	SL	660/A/B	29.3	7	6.0 - 8.0	9.4	28	7	14	12.6	742	1929@51	-	OWL
235/75R15 109T	110101877	XL	660/A/B	31.5	6.5	6.0 - 8.0	9.3	28.9	6.9	13	12.9	720	2271@50	-	OWL
265/70R15 112H	110101878	SL	660/A/B	36.4	8	7.0 - 9.0	10.6	29.7	8	14	13.2	700	2469@51	-	BW
30X9.50R15 104S	110101801	C		36.4	7.5	6.0 - 8.0	9.5	29.6	7.1	17	13.2	701	1985@50	-	OWL
31X10.50R15 109S	110101802	C	NA	42.3	8.5	7.0 - 9.0	10.6	30.7	8	18	13.6	676	2270@50	-	OWL
32X11.50R15 113S	110101803	C		48.7	9	7.5 - 10.0	11.6	31.7	8.6	18	14	655	2535@50	-	OWL
33X10.50R15 114S	110101804	C		45.3	8.5	7.0 - 9.0	11	32.6	8	18	14.4	636	2600@50	-	OWL
33X12.50R15 108S	110101805	C	NA	51.2	10	8.0 - 10.5	12.6	32.7	9.4	18	14.4	636	2205@35	-	OWL
LT215/75R15 106/103S	110101806	D	NA	30.9	6	5.5 - 7.0	8.5	28	6.4	16	12.6	743	2095@65	1930@65	BW
LT235/75R15 110/107S	110101807	D	NA	37.4	6.5	6.0 - 8.0	9.3	29.1	6.9	17	13	715	2335@65	-	OWL
205/70R16 97H	110101879	SL	660/A/B	25.3	6	5.0 - 7.0	8.3	27.3	6.2	13	12.4	760	1609@51	-	BW
215/60R16 95H	110101880	SL	660/A/B	25.7	6.5	6.0 - 7.5	8.8	26.1	6.9	13	12	795	1521@51	-	BW
215/65R16 98H	110101881	SL	660/A/B	26	6.5	6.0 - 7.5	8.7	27.1	6.5	13	12.3	767	1653@51	-	BW
215/70R16 100H	110101882	SL	660/A/B	26.6	6.5	5.5 - 7.0	8.8	27.8	6.5	13	12.6	746	1764@51	-	BW
225/70R16 103H	110101883	SL	660/A/B	30	6.5	6.0 - 7.5	9	28.4	6.6	13	12.8	731	1929@51	-	BW
235/60R16 100H	110101884	SL	660/A/B	27.7	7	6.5 - 8.5	9.4	27.2	7.2	13	12.4	765	1764@51	-	BW
235/70R16 106T	110101885	SL	660/A/B	30.7	7	6.0 - 8.0	9.6	29	7	13	13.1	717	2094@51	-	OWL
245/70R16 111H	110101886	XL	660/A/B	32.9	7	6.5 - 8.0	9.8	29.5	7.2	13	13.3	704	2403@50	-	OWL
245/75R16 111T	110101887	SL	660/A/B	34.7	7	6.5 - 8.0	9.7	30.5	7.2	13	13.6	682	2403@51	-	OWL
255/65R16 109H	110101888	SL	660/A/B	31.7	7.5	7.0 - 9.0	10.4	29.1	7.7	13	13.1	714	2271@51	-	BW
255/70R16 111H	110101889	SL	660/A/B	34.4	7.5	6.5 - 8.5	10.2	30	7.6	13	13.5	692	2403@51	-	OWL
265/70R16 112T	110101890	SL	660/A/B	37.3	8	7.0 - 9.0	10.7	30.6	8	14	13.7	680	2469@51	-	OWL
265/75R16 116T	110101891	SL	660/A/B	38.6	7.5	7.0 - 9.0	10.7	31.7	7.9	14	14.1	655	2756@51	-	OWL
275/70R16 114H	110101892	SL	660/A/B	38.7	8	7.0 - 9.0	11.1	31.1	8.2	14	13.9	669	2601@51	-	BW
LT215/85R16 115/112R	110101808	E	NA	36.2	6	5.5 - 7.0	8.6	30.6	6.4	16	13.7	679	2680@80	2470@80	BW
LT225/75R16 115/112S	110101809	E	NA	37.5	6	6.0 - 7.5	8.7	29.5	6.6	16	13.3	704	2680@80	2470@80	BW
LT235/85R16 120/116S	110101810	E	NA	46.3	6.5	6.0 - 7.5	9.4	32	7	17	14.2	650	3042@80	2778@80	BW
LT245/70R16 118/115R	110101811	E	NA	42	7	6.5 - 8.0	9.7	29.8	7.3	17	13.4	698	2910@80	2680@80	BW
LT245/75R16 120/116S	110101812	E	NA	44.4	7	6.5 - 8.0	9.8	30.7	7.3	17	13.7	677	3042@80	2778@80	OWL
LT265/70R16 121/118S	110101813	E	NA	46.9	8	7.0 - 9.0	10.8	30.8	8	18	13.8	675	3195@80	2910@80	OWL
LT265/75R16 123/120S	110101814	E	NA	49.7	7.5	7.0 - 9.0	10.7	31.8	8	18	14.2	653	3415@80	3085@80	OWL
LT285/75R16 126/123S	110101815	E	NA	54.6	8	7.5 - 9.5	11.5	32.9	8.6	18	14.6	632	3750@80	3415@80	OWL
LT295/75R16 128/125R	110101816	E	NA	59.7	8	7.5 - 10.0	11.7	33.6	8.8	18	14.9	618	3970@80	3640@80	BW
LT305/70R16 124/121S	110101817	E	NA	57.1	9	8.0 - 10.0	12.1	33.1	9.2	18	14.7	628	3525@65	3195@65	BW
LT315/75R16 127/124R	110101818	E	NA	62.8	8.5	8.0 - 10.5	12.2	34.5	9.3	18	15.2	602	3860@65	3525@65	OWL

GEOLANDAR A/T4

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/60R17 96H	110101893	SL	660/A/B	27	6.5	6.0 - 7.5	8.7	27.2	6.9	13	12.5	765	1565@51	-	BW
215/65R17 103H	110101894	XL	660/A/B	27.3	6.5	6.0 - 7.5	8.7	28	6.5	13	12.8	741	1929@50	-	BW
225/55R17 101H	110101895	XL	660/A/B	28.1	7	6.0 - 8.0	9.1	26.9	7.3	13	12.4	773	1819@50	-	BW
225/60R17 99H	110101896	SL	660/A/B	28.4	6.5	6.0 - 8.0	9.1	27.6	7	13	12.6	752	1709@51	-	BW
225/65R17 102H	110101897	SL	660/A/B	28.7	6.5	6.0 - 8.0	9	28.5	6.8	13	13	730	1874@51	-	BW
235/65R17 108H	110101898	XL	660/A/B	30.5	7	6.5 - 8.5	9.4	29.1	7.1	13	13.2	713	2205@50	-	BW
235/70R17 109H	110101899	XL	660/A/B	31.8	7	6.0 - 8.0	9.5	30	7	13	13.6	692	2271@50	-	BW
235/75R17 109T	110101900	SL	660/A/B	34.3	6.5	6.0 - 8.0	9.3	30.9	6.9	13	13.9	673	2271@51	-	OWL
245/65R17 111H	110101901	XL	660/A/B	31.8	7	7.0 - 8.5	9.8	29.6	7.4	13	13.4	703	2403@50	-	OWL
245/70R17 110T	110101902	SL	660/A/B	33.4	7	6.5 - 8.0	9.8	30.5	7.2	13	13.8	681	2337@51	-	BW
245/75R17 112T	110101903	SL	660/A/B	36.2	7	6.5 - 8.0	9.7	31.6	7.2	13	14.2	658	2469@51	-	BW
255/65R17 114H	110101904	XL	660/A/B	34.8	7.5	7.0 - 9.0	10.3	30.1	7.7	13	13.6	690	2601@50	-	BW
255/70R17 112T	110101905	SL	660/A/B	36.6	7.5	6.5 - 8.5	10.2	31.1	7.6	13	14	667	2469@51	-	OWL
255/75R17 115T	110101906	SL	660/A/B	39	7	6.5 - 8.5	10.2	32	7.6	13	14.4	648	2679@51	-	OWL
265/65R17 112T	110101907	SL	660/A/B	36.6	8	7.5 - 9.5	10.6	30.6	8	14	13.8	680	2469@51	-	BW
265/70R17 115T	110101908	SL	660/A/B	39.1	8	7.0 - 9.0	10.7	31.7	8	14	14.2	656	2679@51	-	OWL
275/65R17 115H	110101909	SL	660/A/B	39.2	8	7.5 - 9.5	11	31.1	8.3	13	14	667	2679@51	-	BW
285/65R17 116H	110101910	SL	660/A/B	39.4	8.5	8.0 - 10.0	11.4	31.7	8.6	13	14.2	655	2756@51	-	BW
35X12.50R17 125R	110101863	E		65.9	10	8.0 - 10.5	12.6	34.7	9.8	18	15.4	599	3640@65	-	BW
LT225/65R17 107/103S	110101819	D	NA	37.7	6.5	6.5 - 8.0	8.9	28.7	6.9	16	13.1	723	2150@65	1930@65	BW
LT235/80R17 120/117S	110101820	E	NA	45.1	6.5	6.0 - 8.0	9.3	32.1	6.9	17	14.4	647	3085@80	2835@80	BW
LT245/65R17 111/108S	110101821	D	NA	40.3	7	7.0 - 8.5	9.6	29.8	7.6	17	13.5	697	2405@65	2205@65	BW
LT245/70R17 119/116S	110101822	E	NA	44.4	7	6.5 - 8.0	9.8	30.8	7.3	17	13.9	675	3000@80	-	OWL
LT245/75R17 121/118S	110101823	E	NA	47	7	6.5 - 8.0	9.7	31.7	7.3	17	14.2	655	3195@80	2910@80	OWL
LT255/65R17 119/116S	110101824	E	NA	43.7	7.5	7.5 - 9.0	10.1	30.3	7.9	18	13.7	686	3000@80	2755@80	BW
LT255/70R17 121/118S	110101870	E	NA	47.9	7.5	6.5 - 8.5	10.1	31.4	7.8	18	14.1	662	3195@80	2910@80	OWL
LT255/80R17 121/118R	110101825	E	NA	52.2	7	6.5 - 8.5	10.1	33.2	7.6	18	14.8	625	3195@80	2910@80	BW
LT265/65R17 120/117S	110101826	E	NA	47.5	8	8.0 - 9.5	10.7	30.8	8.3	18	13.9	675	3085@80	2835@80	OWL
LT265/70R17 121/118S	110101827	E	NA	50.9	8	7.0 - 9.0	10.7	31.9	8	18	14.3	652	3195@80	2910@80	OWL
LT275/70R17 124/121S	110101828	E	NA	52.8	8	7.0 - 9.0	11.1	32.4	8.3	18	14.5	640	3525@80	3195@80	OWL
LT285/70R17 121/118S	110101829	E	NA	55	8.5	7.5 - 9.5	11.5	33	8.6	18	14.7	630	3195@80	2910@80	OWL
LT285/75R17 121/118S	110101830	E	NA	59.4	8	7.5 - 9.5	11.3	34.1	8.6	18	15.2	610	3195@80	2910@80	BW
LT295/70R17 121/118S	110101831	E	NA	59.8	8.5	7.5 - 10.0	11.7	33.4	8.8	18	14.9	622	3195@80	2910@80	BW
LT305/70R17 121/118R	110101832	E	NA	60.2	9	8.0 - 10.0	12.1	34	9.2	18	15.1	611	3195@65	-	BW
LT315/70R17 121/118S	110101833	E	NA	60.9	9.5	8.0 - 10.5	12.6	34.4	9.5	18	15.3	604	3195@65	2910@65	BW
P285/70R17 117T	110101911	SL	660/A/B	44.1	8.5	7.5 - 9.5	11.6	33	8.5	14	14.7	630	2833@51	-	BW
225/55R18 98H	110101912	SL	660/A/B	27.9	7	6.0 - 8.0	9.2	27.8	7.3	13	12.8	747	1653@51	-	BW
225/60R18 104H	110101913	XL	660/A/B	29.1	6.5	6.0 - 8.0	9	28.7	7	13	13.2	724	1984@50	-	BW
235/55R18 104H	110101914	XL	660/A/B	30.4	7.5	6.5 - 8.5	9.6	28.1	7.6	13	12.9	739	1984@50	-	BW
235/60R18 107H	110101915	XL	660/A/B	31.1	7	6.5 - 8.5	9.5	29.1	7.2	13	13.3	714	2149@50	-	BW
235/65R18 110H	110101916	XL	660/A/B	32	7	6.5 - 8.5	9.4	30.1	7.1	13	13.7	691	2337@50	-	BW
245/60R18 109H	110101917	XL	660/A/B	32.8	7	7.0 - 8.5	9.8	29.6	7.6	13	13.5	703	2271@50	-	BW
255/55R18 109H	110101918	XL	660/A/B	33.7	8	7.0 - 9.0	10.5	29	8.3	13	13.3	716	2271@50	-	BW
255/60R18 112H	110101919	XL	660/A/B	34.4	7.5	7.0 - 9.0	10.2	30	8	13	13.7	692	2469@50	-	BW
255/65R18 115H	110101920	XL	660/A/B	37.3	7.5	7.0 - 9.0	10.3	31.1	7.7	13	14.1	669	2679@50	-	BW
255/70R18 116H	110101921	XL	660/A/B	37.5	7.5	6.5 - 8.5	10.3	32.1	7.6	13	14.5	647	2756@50	-	BW
265/60R18 110H	110101922	SL	660/A/B	36.6	8	7.5 - 9.5	10.9	30.5	8.3	14	13.9	681	2337@51	-	BW
265/65R18 114H	110101923	SL	660/A/B	38.6	8	7.5 - 9.5	10.8	31.6	8	14	14.3	657	2601@51	-	BW
265/70R18 116H	110101924	SL	660/A/B	40.5	8	7.0 - 9.0	10.8	32.5	8	14	14.7	639	2756@51	-	BW
275/60R18 113H	110101925	SL	660/A/B	36.9	8	7.5 - 9.5	10.9	31	8.5	14	14.1	670	2535@51	-	BW
275/65R18 116H	110101926	SL	660/A/B	40.9	8	7.5 - 9.5	11.1	32.1	8.3	14	14.5	647	2756@51	-	BW
275/70R18 116T	110101927	SL	660/A/B	43	8	7.0 - 9.0	11	33.5	8.2	14	15	620	2756@51	-	OWL
285/60R18 116H	110101928	SL	660/A/B	40.6	8.5	8.0 - 10.0	11.5	31.5	8.8	13	14.3	659	2756@51	-	BW
33X12.50R18 118S	110101834	E	NA	54.2	10	8.5 - 11.0	12.4	32.7	9.8	18	14.7	636	2910@65	-	BW
35X12.50R18 123S	110101835	E	NA	62.1	10	8.5 - 11.0	12.3	34.6	9.5	18	15.5	600	3415@65	-	BW
LT245/75R18 121/118S	110101836	E	NA	48.7	7	6.5 - 8.0	9.9	32.7	7.3	17	14.7	636	3195@80	2910@80	OWL
LT255/70R18 117/114S	110101837	D	NA	48.1	7.5	6.5 - 8.5	10.3	32.3	7.8	18	14.6	643	2835@65	2600@65	BW
LT265/60R18 119/116S	110101838	E	NA	46.6	8	8.0 - 9.5	10.7	30.8	8.3	18	14	675	3000@80	2755@80	BW
LT265/65R18 122/119S	110101839	E	NA	50.6	8	8.0 - 9.5	10.7	31.8	8.3	18	14.4	653	3305@80	3000@80	OWL
LT265/70R18 124/121S	110101840	E	NA	51.6	8	7.0 - 9.0	10.7	32.8	8.1	18	14.8	633	3525@80	3195@80	BW
LT275/65R18 123/120S	110101841	E	NA	52	8	8.0 - 9.5	10.9	32.4	8.5	18	14.6	642	3415@80	3085@80	OWL
LT275/70R18 125/122S	110101842	E	NA	55.4	8	7.0 - 9.0	11	33.4	8.3	18	15	622	3640@80	3305@80	OWL
LT285/65R18 125/122S	110101843	E	NA	54.4	8.5	8.5 - 10.0	11.5	32.8	8.8	18	14.8	634	3640@80	3305@80	BW
LT285/75R18 129/126S	110101844	E	NA	60.9	8	7.5 - 9.5	11.1	34.8	8.4	18	15.6	596	4080@80	3750@80	BW
LT295/70R18 129/126S	110101845	E	NA	62.7	8.5	7.5 - 10.0	11.8	34.3	8.8	18	15.4	605	4080@80	3750@80	BW
LT305/65R18 124/121S	110101846	E	NA	63	9	9.0 - 11.0	12	33.8	9.3	18	15.2	615	3525@65	3195@65	BW
LT305/70R18 126/123R	110101864	E	NA	67.8	9	8.0 - 10.0	12.4	35	9.7	18	15.6	594	3750@65	3415@65	BW
LT325/60R18 124/121S	110101847	E	NA	66.9	9.5	9.5 - 11.5	13.1	33.5	10.2	18	15.1	619	3525@65	3195@65	BW
LT325/65R18 127/124S	110101848	E	NA	70.7	9.5	9.5 - 11.5	13.1	34.7	10	18	15.5	598	3860@65	3525@65	BW
235/55R19 105H	110101929	XL	660/A/B	31.7	7.5	6.5 - 8.5	9.6	29.2	7.6	13	13.5	711	2039@50	-	BW
255/55R19 111H	110101930	XL	660/A/B	35.6	8	7.0 - 9.0	10.4	30	8.3	13	13.8	690	2403@50	-	BW
265/55R19 109H	110101931	SL	660/A/B	37.7	8.5	7.5 - 9.5	10.9	30.6	8.7	14	14	680	2271@51	-	BW
235/55R20 105H	110101932	XL	660/A/B	33.3	7.5	6.5 - 8.5	9.5	30.2	7.6	13	14	687	2039@50	-	BW
245/50R20 105H	110101933	XL	660/A/B	33.1	7.5	7.0 - 8.5	9.9	29.8	8.6	13	13.8	698	2039@50	-	BW
245/60R20 111H	110101934	XL	660/A/B	36.2	7	7.0 - 8.5	9.7	31.7	7.6	13	14.6	655	2403@50	-	BW

GEOLANDAR A/T4

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
255/50R20 109H	110101935	XL	660/A/B	35.7	8	7.0 - 9.0	10.2	30.2	8.9	13	14	687	2271@50	-	BW
255/55R20 110H	110101936	XL	660/A/B	38.1	8	7.0 - 9.0	10.2	31.1	8.3	13	14.3	669	2337@50	-	BW
265/50R20 111H	110101937	XL	660/A/B	36.9	8.5	7.5 - 9.5	10.7	30.6	9.3	14	14.1	679	2403@50	-	BW
265/55R20 113H	110101938	XL	660/A/B	39.9	8.5	7.5 - 9.5	10.9	31.6	8.7	14	14.5	657	2535@50	-	BW
275/55R20 117H	110101939	XL	660/A/B	41.5	8.5	7.5 - 9.5	11.2	31.9	8.9	14	14.6	652	2833@50	-	BW
275/60R20 115H	110101940	SL	660/A/B	41.9	8	7.5 - 9.5	10.9	33.1	8.5	14	15.1	627	2679@51	-	BW
275/65R20 116H	110101941	SL	660/A/B	44.3	8	7.5 - 9.5	11	34.1	8.3	14	15.5	609	2756@51	-	BW
285/50R20 112H	110101942	SL	660/A/B	41.7	9	8.0 - 10.0	11.6	31.3	9.8	13	14.4	663	2469@51	-	BW
305/55R20 116T	110101943	SL	660/A/B	48.9	9.5	8.5 - 11.0	12.6	33.1	10	14	15.1	628	2756@51	-	BW
33X12.50R20 114S	110101849	E		61.1	10	8.5 - 11.0	12.5	32.9	10	18	15	632	2600@65	-	BW
35X12.50R20 121R	110101850	E	NA	61.4	10	8.5 - 11.0	12.4	34.7	9.8	18	15.7	598	3195@65	-	BW
LT265/60R20 121/118S	110101851	E	NA	51.7	8	8.0 - 9.5	10.6	32.7	8.3	18	14.9	636	3195@80	2910@80	BW
LT275/55R20 120/117S	110101852	E	NA	52.3	8.5	8.0 - 9.5	11.1	32.1	9	18	14.7	647	3085@80	2835@80	BW
LT275/60R20 123/120S	110101853	E	NA	54.2	8	8.0 - 9.5	11	33.1	8.6	18	15.1	627	3415@80	3085@80	BW
LT275/65R20 126/123S	110101854	E	NA	53.4	8	8.0 - 9.5	11	34.3	8.5	18	15.6	606	3750@80	3415@80	BW
LT285/55R20 122/119S	110101855	E	NA	54.5	9	8.5 - 10.0	11.6	32.6	9.4	18	14.9	638	3305@80	3000@80	BW
LT285/60R20 125/122S	110101856	E	NA	57.5	8.5	8.5 - 10.0	11.6	33.6	9.2	18	15.3	619	3640@80	3305@80	BW
LT285/65R20 127/124S	110101857	E	NA	58.8	8.5	8.5 - 10.0	11.6	34.6	8.9	18	15.7	600	3860@80	3525@80	BW
LT295/55R20 123/120S	110101858	E	NA	56	9.5	8.5 - 10.5	12.2	33	9.6	18	15.1	630	3415@80	3085@80	BW
LT295/60R20 126/123S	110101859	E	NA	58.5	8.5	8.5 - 10.5	11.7	34	9.3	18	15.5	611	3750@80	3415@80	BW
LT295/65R20 129/126S	110101860	E	NA	67	8.5	8.5 - 10.5	11.8	35.4	9.1	18	16	588	4080@80	3750@80	BW
LT305/55R20 121/118S	110101861	E	NA	58.2	9.5	9.0 - 11.0	12.2	33.4	9.8	18	15.2	622	3195@65	2910@65	BW
LT325/60R20 126/123S	110101862	E	NA	71.8	9.5	9.5 - 11.5	13	35.5	10.2	18	16	586	3750@65	3415@65	BW
275/55R21 116H	110101944	XL	660/A/B	44.1	8.5	7.5 - 9.5	11.3	32.8	8.9	14	15.1	633	2756@50	-	BW
275/50R22 115H	110101945	XL	660/A/B	44.3	8.5	7.5 - 9.5	11.1	33	9.6	14	15.3	630	2679@50	-	BW
285/45R22 114H	110101946	XL	660/A/B	42.3	9.5	9.0 - 10.5	11	32.1	9.8	14	14.9	647	2601@50	-	BW
305/45R22 118T	110101947	XL	660/A/B	45.8	10	9.5 - 11.5	11.9	32.8	10.9	14	15.2	633	2910@50	-	BW
LT285/50R22 121/118S	110101867	E	NA	62.2	9	8.5 - 10.0	11.5	33.6	9.4	18	15.5	619	3195@80	-	BW
LT285/55R22 124/121S	110101866	E	NA	64.2	9	8.5 - 10.0	11.7	34.6	9.4	18	15.9	600	3525@80	-	BW
LT305/55R22 122/119S	110101865	E	NA	69.9	9.5	9.0 - 11.0	12.4	35.5	9.9	18	16.3	586	3305@65	-	BW
LT325/50R22 127Q	110101868	F	NA	73.8	10	9.5 - 11.5	13.2	35.2	10.7	18	16.1	591	3860@80	-	BW
LT275/50R24 121/118S	110101869	E	NA	61.5	8.5	8.0 - 9.5	10.9	35.3	9.1	18	16.4	589	3195@80	2910@80	BW

GEOLANDAR A/T G015

ALL-SEASON | OFF-ROAD **Crossovers/SUVs | Trucks**

An all-weather, all-terrain tire that capably carries both on- and off-road duties.



FEATURES AND BENEFITS

COMPETITIVE ALL-WEATHER TRACTION
Severe snow service-rated (3PMSF) for confident wet and winter traction.

LONG TREAD LIFE
A flatter profile and Enduro compound designed to deliver longer treadwear and increased tread life.

OFF-ROAD DURABILITY
Dependable off-road performance from a sturdy, Endurocore construction.

ON/OFF-ROAD TRACTION
Advanced tread design provides capable off-road traction while staying quiet on the highway.

60,000-Mile Limited Treadwear Warranty (P-Metric Sizes)

50,000-Mile Limited Treadwear Warranty (LT-Metric Sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/70R15 98H	110101581	SL	600/A/B	26.7	6.5	5.5 - 7.0	8.7	26.9	6.5	12	12.1	773	1653@51	-	OWL
LT255/70R16 115/112S	110101681	D	NA	44.3	7.5	6.5 - 8.5	10.4	30.2	8	17	13.5	688	2680@65	2470@65	BW
P235/70R16 104T	110101511	SL	600/A/B	32.4	7	6.0 - 8.0	9.3	29	7	13	13.1	716	1984@51	-	OWL
LT245/70R17 119/116R	110101638	E	NA	45.4	7	6.5 - 8.0	9.7	30.6	7.6	17	13.8	678	3000@80	2755@80	OWL
LT255/65R17 119/116S	110101682	E		45.5	7.5	7.5 - 9.0	10.2	30.3	8	17	13.7	686	3000@80	2755@80	BW
LT265/70R17 121/118S	110101640	E	NA	51	8	7.0 - 8.5	10.7	31.9	8.3	18	14.3	651	3195@80	2910@80	OWL
P245/65R17 105T	110101521	SL	600/A/B	35.1	7	7.0 - 8.5	9.6	29.6	7.2	12	13.4	702	2039@51	-	OWL
235/55R18 104H	110101675	XL	600/A/B	30.2	7.5	6.5 - 8.5	9.6	28.2	7.5	11	13	737	1984@50	-	BW
255/55R18 109H	110101618	XL	600/A/B	34.4	8	7.0 - 9.0	10.4	29.1	8.1	12	13.3	715	2271@50	-	BW
265/60R18 110H	110101530	SL	600/A/B	38	8	7.5 - 9.5	10.8	30.5	8	12	13.9	681	2337@51	-	BW
235/55R19 105H	110101621	XL	600/A/B	32	7.5	6.5 - 8.5	9.6	29.1	7.5	11	13.5	713	2039@50	-	BW
255/55R19 111H	110101619	XL	600/A/B	36.2	8	7.0 - 9.0	10.4	30	8.1	12	13.8	692	2403@50	-	BW
265/50R20 107H	110101620	SL	600/A/B	38.8	8.5	7.5 - 9.5	10.9	30.4	8.9	12	14	684	2149@51	-	BW
LT325/50R22 122R	110101667	E	NA	68.5	10	9.5 - 11.5	13.1	35.1	10.5	16	16.1	592	3305@65	-	BW

GEOLANDAR H/T4™

ALL-SEASON **Crossovers/SUVs | Trucks | Work Vans**

Rugged reliability meets the open road.



FEATURES AND BENEFITS

OPTIMIZED ALL-SEASON PERFORMANCE
Comprehensive ability to deliver reliable handling, traction, and safety across a wide range of weather conditions.

SMOOTH, QUIET RIDE
Harmonious balance of materials, construction, and design all working together to provide a comfortable driving experience.

ON-ROAD DURABILITY
Endures the everyday stresses of city and highway roads while maintaining all-season performance and safety.

LONG TREAD LIFE
Designed to extend the lifespan of the tire while having an excellent balance between performance and cost efficiency.

70,000-Mile Limited Treadwear Warranty (P-metric sizes)

55,000-Mile Limited Warranty (LT-metric sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
185/60R15C 94/92T	110106266	C		21.4	5.5	5.5 - 6.0	7.4	23.8	6.2	13	10.9	874	1475@54	1390@54	BW
215/70R15 103H	110106201	XL	800/A/A	25.9	6.5	5.5 - 7.0	8.6	26.9	6.3	12	12.2	771	1929@50	-	BW
235/75R15 109T	110106250	XL	800/A/B	29.8	6.5	6.0 - 8.0	9.2	28.9	6.9	12	12.9	719	2271@50	-	BW
255/70R15 112S	110106202	XL	800/A/B	33.1	7.5	6.5 - 8.5	10.2	29.1	7.4	12	13	713	2469@50	-	BW
265/70R15 112H	110106251	SL	800/A/B	33.3	8	7.0 - 9.0	10.7	29.6	7.7	12	13.2	701	2469@51	-	BW
195/75R16C 107/105R	110106252	D		30.6	5.5	5.0 - 6.0	7.7	27.6	6.2	13	12.5	754	2150@69	2040@69	BW
225/75R16 108T	110106203	XL	800/A/B	30.6	6	6.0 - 7.5	8.6	29.4	6.6	12	13.2	706	2205@50	-	BW
235/65R16C 121/119R	110106253	E		38.6	7	6.5 - 7.5	9.5	28.1	7.9	14	12.7	739	3195@83	3000@83	BW
235/70R16 109T	110106205	XL	800/A/B	31.1	7	6.0 - 8.0	9.5	29	6.9	12	13.1	716	2271@50	-	BW
235/75R16 112T	110106206	XL	800/A/B	32.6	6.5	6.0 - 8.0	9.3	29.9	6.9	12	13.4	695	2469@50	-	BW
245/70R16 111T	110106207	XL	800/A/B	32.4	7	6.5 - 8.0	9.6	29.6	7.1	12	13.3	702	2403@50	-	BW
245/75R16 115T	110106208	XL	800/A/B	34.8	7	6.5 - 8.0	9.9	30.5	7.3	12	13.6	682	2679@50	-	BW
255/65R16 113T	110106209	XL	800/A/B	32.6	7.5	7.0 - 9.0	10.2	29.2	7.6	12	13.1	712	2535@50	-	BW
255/70R16 115T	110106210	XL	800/A/B	34.6	7.5	6.5 - 8.5	10.2	30.1	7.4	12	13.5	691	2679@50	-	BW
265/70R16 116T	110106211	XL	800/A/B	37	8	7.0 - 9.0	10.8	30.7	7.7	13	13.7	677	2756@50	-	BW
265/75R16 116T	110106212	XL	800/A/B	38.8	7.5	7.0 - 9.0	10.6	31.7	7.9	12	14.1	655	2756@50	-	BW
275/70R16 116H	110106213	XL	800/A/B	38.8	8	7.0 - 9.0	11	31.2	8	12	13.9	665	2756@50	-	BW
LT215/85R16 115/112R	110106254	E	NA	37.7	6	5.5 - 7.0	8.4	30.5	6.4	14	13.7	681	2680@80	2470@80	BW
LT225/75R16 115/112S	110106255	E	NA	37	6	6.0 - 7.5	8.7	29.4	6.8	14	13.2	707	2680@80	2470@80	BW
LT245/75R16 120/116S	110106257	E	NA	42.5	7	6.5 - 8.0	9.7	30.6	7.6	14	13.7	679	3042@80	2778@80	BW
235/70R17 109T	110106214	XL	800/A/B	31.7	7	6.0 - 8.0	9.4	30	6.9	12	13.6	692	2271@50	-	BW
235/75R17 113T	110106215	XL	800/A/B	33.7	6.5	6.0 - 8.0	9.3	30.9	6.9	12	13.9	672	2535@50	-	BW
245/65R17 111T	110106216	XL	800/A/B	33.1	7	7.0 - 8.5	9.7	29.6	7.2	11	13.4	702	2403@50	-	BW
245/70R17 114T	110106217	XL	800/A/B	30	7	6.5 - 8.0	9.8	30.6	7.1	12	13.8	678	2601@50	-	BW
245/75R17 112T	110106218	SL	800/A/B	36.8	7	6.5 - 8.0	9.8	31.6	7.3	12	14.2	658	2469@51	-	BW
255/65R17 114T	110106219	XL	800/A/B	35.3	7.5	7.0 - 9.0	10.2	30.1	7.6	12	13.6	690	2601@50	-	BW
255/70R17 116T	110106220	XL	800/A/B	36.2	7.5	6.5 - 8.5	10.3	31.1	7.4	12	14	669	2756@50	-	BW
265/65R17 116T	110106221	XL	800/A/B	35.9	8	7.5 - 9.5	10.8	30.6	7.9	12	13.8	678	2756@50	-	BW
265/70R17 116H	110106222	XL	800/A/B	39.2	8	7.0 - 9.0	10.8	31.6	7.7	13	14.2	657	2756@50	-	BW
LT245/75R17 121/118S	110106260	E	NA	43.9	7	6.5 - 8.0	9.7	31.7	7.6	14	14.2	656	3195@80	2910@80	BW
245/60R18 109V	110106225	XL	800/A/A	32.4	7	7.0 - 8.5	9.8	29.6	7.2	11	13.5	701	2271@50	-	BW
255/60R18 112V	110106226	XL	800/A/A	33.7	7.5	7.0 - 9.0	10.1	30.1	7.6	11	13.7	690	2469@50	-	BW
255/65R18 115H	110106227	XL	800/A/B	36.6	7.5	7.0 - 9.0	10.3	31.1	7.6	12	14.1	668	2679@50	-	BW
255/70R18 116H	110106228	XL	800/A/B	38.1	7.5	6.5 - 8.5	10.3	32	7.4	12	14.5	648	2756@50	-	BW
265/60R18 114H	110106229	XL	800/A/A	35.7	8	7.5 - 9.5	10.7	30.6	7.9	12	13.9	680	2601@50	-	BW
265/65R18 116T	110106230	XL	800/A/A	38.6	8	7.5 - 9.5	10.7	31.6	7.9	12	14.3	658	2756@50	-	BW
265/70R18 116T	110106231	XL	800/A/B	40.3	8	7.0 - 9.0	10.6	32.8	7.7	13	14.8	634	2756@50	-	BW
275/60R18 117H	110106232	XL	800/A/A	39	8	7.5 - 9.5	11	30.9	8.1	12	14.1	671	2833@50	-	BW

GEOLANDAR H/T4™

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
275/65R18 116H	110106233	XL	800/A/B	40.3	8	7.5 - 9.5	11.1	32	8.1	12	14.5	648	2756@50	-	BW
285/60R18 120V	110106234	XL	800/A/B	40.3	8.5	8.0 - 10.0	11.5	31.4	8.5	12	14.2	661	3086@50	-	BW
285/65R18 116H	110106235	SL	800/A/B	41.9	8.5	8.0 - 10.0	11.5	32.6	8.5	12	14.7	636	2756@51	-	BW
LT275/70R18 125/122S	110106263	E	NA	50.9	8	7.0 - 9.0	11.1	33.3	8.4	16	15	624	3640@80	3305@80	BW
255/60R19 113H	110106236	XL	800/A/B	36	7.5	7.0 - 9.0	10.2	31.1	7.6	11	14.2	668	2535@50	-	BW
265/55R19 113V	110106237	XL	800/A/A	36.8	8.5	7.5 - 9.5	10.8	30.6	8.3	11	14	680	2535@50	-	BW
245/60R20 107H	110106238	SL	800/A/A	34.8	7	7.0 - 8.5	9.6	31.9	7.2	11	14.6	652	2149@51	-	BW
255/60R20 113V	110106239	XL	800/A/A	37.9	7.5	7.0 - 9.0	10.2	32.1	7.6	11	14.7	647	2535@50	-	BW
265/55R20 113V	110106240	XL	800/A/A	39	8.5	7.5 - 9.5	10.7	31.6	8.3	11	14.5	657	2535@50	-	BW
275/55R20 117H	110106241	XL	800/A/A	39.4	8.5	7.5 - 9.5	11.1	32	8.6	11	14.7	650	2833@50	-	BW
275/60R20 116H	110106242	XL	800/A/A	41.4	8	7.5 - 9.5	11	33	8.1	12	15.1	629	2756@50	-	BW
275/65R20 116V	110106243	SL	800/A/B	42.8	8	7.5 - 9.5	11	34.2	8.1	11	15.5	608	2756@51	-	BW
285/50R20 116V	110106244	XL	800/A/A	40.3	9	8.0 - 10.0	11.7	31.3	9.4	12	14.4	664	2756@50	-	BW
LT265/60R20 121/118S	110106264	E	NA	50	8	8.0 - 9.5	10.7	32.7	8.4	15	14.9	636	3195@80	2910@80	BW
LT275/65R20 126/123S	110106265	E	NA	54	8	8.0 - 9.5	11	34.3	8.4	16	15.6	606	3750@80	3415@80	BW
275/50R21 113V	110106245	XL	800/A/A	39.5	8.5	7.5 - 9.5	11.1	31.9	9.1	11	14.8	650	2535@50	-	BW
275/55R21 116H	110106246	XL	800/A/A	40.3	8.5	7.5 - 9.5	11.1	33	8.6	11	15.2	630	2756@50	-	BW
275/50R22 115H	110106247	XL	800/A/A	40.8	8.5	7.5 - 9.5	11.1	33	9.1	11	15.3	629	2679@50	-	BW
285/45R22 114H	110106248	XL	800/A/A	39.5	9.5	9.0 - 10.5	11.3	32.1	9.4	12	15	646	2601@50	-	BW

GEOLANDAR® H/T G056

ALL-SEASON **Crossovers/SUVs | Trucks**

All-season performance for highway confidence in all conditions.



FEATURES AND BENEFITS

QUIET RIDE
Unique symmetric tread pattern minimizes road noise for a quiet ride.

COMPETITIVE ALL-SEASON TRACTION
Advanced compound and symmetric tread pattern combine to offer superior wet and winter grip.

LONG TREAD LIFE
A flat profile, 3D siping and an advanced silica compound provide long-lasting, even wear.

ON-ROAD DURABILITY
Sturdy construction provides the strength to stand up to everyday demands.

70,000-Mile Limited Treadwear Warranty (P-metric sizes)

50,000-Mile Limited Warranty (LT-metric sizes)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
265/70R15 112H	110105639	SL	720/A/A	36.1	8	7.0 - 9.0	10.8	29.5	8.1	13	13.2	704	2469@51	-	BW
30X9.50R15 104S	110105640	C	NA	35	7.5	6.5 - 8.5	9.5	29.4	7	13	13.1	706	1985@50	-	OWL
31X10.50R15 109S	110105641	C	NA	39.7	8.5	7.0 - 9.0	10.7	30.4	7.9	13	13.5	683	2270@50	-	OWL
P235/75R15 108T	110105604	XL	720/A/B	31.4	6.5	6.0 - 8.0	9.1	29	7.2	12	13	717	2183@50	-	OWL
275/70R16 114H	110105642	SL	720/A/A	40.8	8	7.0 - 9.0	11	31.1	8.3	12	13.9	668	2601@51	-	BW
LT225/75R16 115/112S	110105659	E	NA	36.6	6	6.0 - 7.0	8.7	29.3	6.8	14	13.2	708	2680@80	2470@80	BW
LT235/85R16 120/116R	110105660	E	NA	43.5	6.5	6.0 - 7.5	9.4	31.9	7	14	14.2	651	3042@80	2778@80	BW
LT245/75R16 120/116S	110105661	E	NA	42.1	7	6.5 - 8.0	9.9	30.6	7.6	14	13.7	679	3042@80	2778@80	OWL
LT265/75R16 123/120R	110105662	E	NA	46.5	7.5	7.0 - 8.0	10.6	31.7	8.1	15	14.1	655	3415@80	3085@80	OWL
LT285/75R16 126/123S	110105675	E	NA	54	8	7.5 - 9.0	11.7	32.8	8.7	16	14.6	633	3750@80	3415@80	OWL
P235/70R16 104T	110105602	SL	720/A/B	30.4	7	6.0 - 8.0	9.4	28.9	7.2	12	13	718	1984@51	-	OWL
P235/75R16 109T	110105605	XL	720/A/B	33.2	6.5	6.0 - 8.0	9.2	29.9	7.2	12	13.4	694	2271@50	-	OWL
P245/70R16 106H	110105608	SL	720/A/A	38.1	7	6.5 - 8.0	9.8	29.5	7.5	12	13.3	704	2094@51	-	OWL
P255/65R16 106T	110105612	SL	720/A/B	33.3	7.5	7.0 - 9.0	10.2	29	7.8	12	13.1	716	2094@51	-	OWL
P255/70R16 109T	110105615	SL	720/A/B	36	7.5	6.5 - 8.5	10.2	30.1	7.8	12	13.5	690	2271@51	-	OWL
P265/70R16 111T	110105621	SL	720/A/B	38	8	7.0 - 9.0	10.7	30.6	8.1	13	13.7	680	2403@51	-	OWL
265/70R17 115H	110105682	SL	720/A/A	39.4	8	7.0 - 9.0	10.8	31.8	8.1	13	14.3	654	2679@51	-	OWL
LT225/75R17 116/113S	110105679	E	NA	39	6	6.0 - 7.5	8.7	30.7	6.9	14	13.8	677	2755@80	2535@80	BW
LT235/80R17 120/117R	110105663	E	NA	42.8	6.5	6.0 - 7.5	9.2	31.9	7	14	14.3	651	3085@80	2835@80	OWL
LT245/70R17 119/116R	110105664	E	NA	41.8	7	6.5 - 8.0	9.6	30.7	7.6	14	13.8	677	3000@80	2755@80	OWL
LT265/70R17 121/118S	110105666	E	NA	47.3	8	7.0 - 8.5	10.7	31.8	8.2	15	14.3	653	3195@80	2910@80	OWL
LT285/70R17 121/118S	110105676	E	NA	54.2	8.5	7.5 - 9.0	11.7	32.8	8.7	16	14.6	634	3195@80	2910@80	OWL
P235/70R17 108T	110105603	XL	720/A/B	32.9	7	6.0 - 8.0	9.4	30	7.2	12	13.6	693	2205@50	-	OWL
P235/75R17 108S	110105677	SL	720/A/B	35.1	6.5	6.0 - 8.0	9.3	31.1	7.3	12	14	667	2205@51	-	OWL
P245/65R17 105T	110105607	SL	720/A/B	33.9	7	7.0 - 8.5	9.7	29.6	7.5	12	13.4	703	2039@51	-	BW
P245/70R17 108H	110105609	SL	720/A/A	35.7	7	6.5 - 8.0	9.8	30.6	7.5	12	13.8	680	2205@51	-	OWL
P255/65R17 108T	110105613	SL	720/A/B	35.7	7.5	7.0 - 9.0	10.2	30.1	7.8	12	13.6	690	2205@51	-	OWL
P255/70R17 110T	110105616	SL	720/A/B	37.5	7.5	6.5 - 8.5	10.2	31	7.8	12	14	670	2337@51	-	OWL
P265/65R17 110T	110105619	SL	720/A/B	38.6	8	7.5 - 9.5	10.6	30.6	8.1	12	13.8	678	2337@51	-	OWL
255/60R18 112V	110105670	XL	720/A/A	35.7	7.5	7.0 - 9.0	10.2	30	8	11	13.7	692	2469@50	-	BW
275/60R18 113H	110105672	SL	720/A/A	39	8	7.5 - 9.5	10.9	31	8.3	12	14.1	670	2535@51	-	BW
LT275/65R18 123/120S	110105667	E	NA	50.3	8	7.5 - 9.0	11.1	32.2	8.4	16	14.5	645	3415@80	3085@80	OWL
LT275/70R18 125/122R	110105668	E	NA	52.6	8	7.0 - 8.5	11.1	33.3	8.4	16	15	623	3640@80	3305@80	OWL
P245/60R18 104H	110105606	SL	720/A/A	32.6	7	7.0 - 8.5	9.6	29.6	7.3	11	13.5	703	1984@51	-	BW
P255/65R18 109T	110105614	SL	720/A/B	38.5	7.5	7.0 - 9.0	10.3	31.1	7.8	12	14.1	668	2271@51	-	BW
P255/70R18 112H	110105617	SL	720/A/A	38.7	7.5	6.5 - 8.5	10.2	32	7.8	12	14.5	648	2469@51	-	BW
P265/65R18 112T	110105620	SL	720/A/B	38.2	8	7.5 - 9.5	10.5	31.5	8.1	12	14.3	660	2469@51	-	BW
P265/70R18 114S	110105623	SL	720/A/B	40.9	8	7.0 - 9.0	10.7	32.6	8.1	13	14.7	637	2601@51	-	OWL

GEOLANDAR® H/T G056

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
P255/60R19 108H	110105611	SL	720/A/A	36.2	7.5	7.0 - 9.0	10.2	31.1	8	11	14.2	669	2205@51	-	BW
LT265/60R20 121/118R	110105674	E	NA	51.8	8	7.5 - 9.5	10.7	32.8	8.4	15	15	633	3195@80	2910@80	BW
LT275/65R20 126/123S	110105673	E	NA	56	8	7.5 - 9.5	11	34.3	8.4	16	15.6	606	3750@80	3415@80	BW
285/45R22 114H	110105669	XL	720/A/A	39.2	9.5	9.0 - 10.5	10.9	32	9.8	12	14.9	648	2601@50	-	BW
P275/50R22 111H	110105678	SL	720/A/A	41.2	8.5	7.5 - 9.5	11.1	32.8	9.2	12	15.2	633	2403@51	-	BW

GEOLANDAR CV4S

ALL-SEASON **Crossovers/SUVs | Minivans**

Long-lasting, all-weather performance with a severe snow service rating.



FEATURES AND BENEFITS

SUPREME WINTER TRACTION
Engineered to tackle the most extreme winter conditions as the temperatures drop while maintaining all-season performance.

EXCELLENT WET PERFORMANCE
Designed for reliable wet performance and resistance to hydroplaning.

LONG TREAD LIFE
Built to provide long tread life without compromising all-weather performance.

QUIET, COMFORTABLE RIDE
Advanced construction and pattern provides on-road comfort in dry, wet, and snow conditions year-round.

60,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

30,000-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/65R16 98H	110156137	SL	660/A/A	23.6	6.5	6.0 - 7.5	8.8	27	6.4	11	12.3	769	1653@51	-	BW
215/70R16 100H	110156138	SL	660/A/A	25.4	6.5	5.5 - 7.0	8.7	27.8	6.4	12	12.6	746	1764@51	-	BW
235/70R16 106H	110156139	SL	660/A/A	29	7	6.0 - 8.0	9.4	29	7	12	13.1	716	2094@51	-	BW
265/70R16 112T	110156140	SL	660/A/A	34.8	8	7.0 - 9.0	10.7	30.6	7.9	13	13.7	680	2469@51	-	BW
215/55R17 98V	110156141	XL	660/A/A	25.5	7	6.0 - 7.5	8.8	26.3	6.9	11	12.1	789	1653@50	-	BW
215/60R17 100V	110156148	XL	660/A/A	25.4	6.5	6.0 - 7.5	8.6	27.2	6.5	11	12.5	762	1764@50	-	BW
215/65R17 99H	110156142	SL	660/A/A	25.2	6.5	6.0 - 7.5	8.7	28	6.4	11	12.8	742	1709@51	-	BW
225/55R17 101V	110156101	XL	660/A/A	26.6	7	6.0 - 8.0	9.1	26.9	7.2	11	12.3	774	1819@50	-	BW
225/60R17 99V	110156102	SL	660/A/A	25.7	6.5	6.0 - 8.0	8.8	27.6	6.8	11	12.6	753	1709@51	-	BW
225/65R17 102H	110156103	SL	660/A/A	27.1	6.5	6.0 - 8.0	9.1	28.4	6.8	11	12.9	732	1874@51	-	BW
235/55R17 103V	110156104	XL	660/A/A	27.9	7.5	6.5 - 8.5	9.6	27.1	7.6	11	12.4	766	1929@50	-	BW
235/60R17 102H	110156105	SL	660/A/A	27.2	7	6.5 - 8.5	9.3	28.2	7	11	12.9	736	1874@51	-	BW
235/65R17 108V	110156106	XL	660/A/A	30.1	7	6.5 - 8.5	9.6	29.1	7	11	13.2	714	2205@50	-	BW
245/65R17 111H	110156143	XL	660/A/A	31.1	7	7.0 - 8.5	9.8	29.6	7.2	12	13.4	701	2403@50	-	BW
245/70R17 110T	110156155	SL	660/A/A	33.5	7	6.5 - 8.0	10	30.5	7.2	12	13.8	681	2337@51	-	BW
265/70R17 115T	110156107	SL	660/A/A	36.8	8	7.0 - 9.0	10.6	31.7	7.9	13	14.2	656	2679@51	-	BW
215/55R18 99V	110156108	XL	660/A/A	26.7	7	6.0 - 7.5	8.8	27.4	6.9	11	12.7	759	1709@50	-	BW
225/55R18 98V	110156109	SL	660/A/A	27.8	7	6.0 - 8.0	9	27.8	7.2	11	12.8	747	1653@51	-	BW
225/60R18 104V	110156110	XL	660/A/A	27.9	6.5	6.0 - 8.0	8.8	28.8	6.8	11	13.2	722	1984@50	-	BW
235/55R18 100V	110156111	SL	660/A/A	27.9	7.5	6.5 - 8.5	9.5	28	7.4	11	12.9	741	1764@51	-	BW
235/60R18 107V	110156112	XL	660/A/A	29.7	7	6.5 - 8.5	9.4	29	7	11	13.3	717	2149@50	-	BW
235/65R18 110V	110156113	XL	660/A/A	31.1	7	6.5 - 8.5	9.5	30.1	7	11	13.7	691	2337@50	-	BW
245/60R18 105V	110156114	SL	660/A/A	30.4	7	7.0 - 8.5	9.7	29.5	7.2	12	13.5	704	2039@51	-	BW
255/55R18 109V	110156154	XL	660/A/A	32.4	8	7.0 - 9.0	10.4	29.1	8.1	12	13.3	715	2271@50	-	BW
255/60R18 112V	110156156	XL	660/A/A	33.5	7.5	7.0 - 9.0	10.2	29.9	7.6	12	13.7	694	2469@50	-	BW
255/65R18 111H	110156115	SL	660/A/A	35.9	7.5	7.0 - 9.0	10.4	31	7.6	12	14.1	670	2403@51	-	BW
265/60R18 110V	110156116	SL	660/A/A	34.6	8	7.5 - 9.5	10.7	30.6	8	12	13.9	680	2337@51	-	BW
265/65R18 114T	110156144	SL	660/A/A	36.4	8	7.5 - 9.5	10.7	31.5	8	13	14.3	659	2601@51	-	BW
275/65R18 116H	110156117	SL	660/A/A	39.6	8	7.5 - 9.5	11.1	32.1	8.1	13	14.5	647	2756@51	-	BW
225/55R19 99V	110156118	SL	660/A/A	28.2	7	6.0 - 8.0	9.1	28.8	7	11	13.3	722	1709@51	-	BW
235/45R19 99V	110156119	XL	660/A/A	27.2	8	7.5 - 9.0	9.3	27.2	7.8	12	12.7	763	1709@50	-	BW
235/50R19 103V	110156120	XL	660/A/A	29.7	7.5	6.5 - 8.5	9.5	28.4	7.8	11	13.2	731	1929@50	-	BW
235/55R19 105V	110156121	XL	660/A/A	30.4	7.5	6.5 - 8.5	9.5	29.3	7.4	11	13.5	710	2039@50	-	BW
245/45R19 102V	110156145	XL	660/A/A	27.9	8	7.5 - 9.0	9.5	27.8	8	12	12.9	746	1874@50	-	BW
245/55R19 103V	110156122	SL	660/A/A	31.5	7.5	7.0 - 8.5	10	29.7	7.7	12	13.7	699	1929@51	-	BW
255/50R19 107V	110156123	XL	660/A/A	33.6	8	7.0 - 9.0	10.2	29.1	8.5	12	13.5	713	2149@50	-	BW
255/55R19 111V	110156150	XL	660/A/A	33.5	8	7.0 - 9.0	10.3	30.2	8.1	12	13.9	688	2403@50	-	BW
255/60R19 109H	110156124	SL	660/A/A	35.1	7.5	7.0 - 9.0	10.1	31.2	7.6	12	14.3	666	2271@51	-	BW

GEOLANDAR CV4S

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
265/50R19 110V	110156125	XL	660/A/A	34.6	8.5	7.5 - 9.5	10.6	29.5	8.8	12	13.6	704	2337@50	-	BW
275/55R19 111V	110156126	SL	660/A/A	37.8	8.5	7.5 - 9.5	11.1	30.9	8.7	12	14.1	672	2403@51	-	BW
235/45R20 100V	110156151	XL	660/A/A	28	8	7.5 - 9.0	9.4	28.3	7.8	12	13.3	733	1764@50	-	BW
235/50R20 104V	110156157	XL	660/A/A	30.6	7.5	6.5 - 8.5	9.4	29.4	7.8	11	13.7	705	1984@50	-	BW
235/55R20 102V	110156127	SL	660/A/A	31.2	7.5	6.5 - 8.5	9.5	30.2	7.4	11	14	689	1874@51	-	BW
245/45R20 103V	110156128	XL	660/A/A	29.2	8	7.5 - 9.0	9.4	28.9	8	12	13.5	719	1929@50	-	BW
245/50R20 105V	110156129	XL	660/A/A	33.1	7.5	7.0 - 8.5	9.7	29.8	8	12	13.8	698	2039@50	-	BW
255/40R20 101V	110156152	XL	660/A/A	29.5	9	8.5 - 10.0	10.1	28	8.5	12	13.1	742	1819@50	-	BW
255/45R20 105V	110156130	XL	660/A/A	32.7	8.5	8.0 - 9.5	10	29	8.4	12	13.5	717	2039@50	-	BW
255/50R20 109V	110156131	XL	660/A/A	34.5	8	7.0 - 9.0	10.3	30.2	8.5	12	14	689	2271@50	-	BW
255/55R20 110V	110156132	XL	660/A/A	35.7	8	7.0 - 9.0	10.4	31	8.1	12	14.3	670	2337@50	-	BW
265/45R20 108V	110156133	XL	660/A/A	34.1	9	8.5 - 10.0	10.5	29.4	8.8	12	13.7	707	2205@50	-	BW
265/50R20 111V	110156134	XL	660/A/A	36.2	8.5	7.5 - 9.5	10.7	30.5	8.8	12	14.1	681	2403@50	-	BW
275/45R20 110V	110156147	XL	660/A/A	34.4	9	8.5 - 10.5	10.7	29.8	9.1	13	13.8	698	2337@50	-	BW
275/50R20 113V	110156149	XL	660/A/A	37.5	8.5	7.5 - 9.5	11	30.8	8.9	13	14.2	674	2535@50	-	BW
275/55R20 117V	110156135	XL	660/A/A	39.5	8.5	7.5 - 9.5	11.2	31.9	8.7	13	14.6	652	2833@50	-	BW
275/60R20 116H	110156136	XL	660/A/A	41.4	8	7.5 - 9.5	10.8	33	8.1	13	15.1	629	2756@50	-	BW
285/45R22 114H	110156146	XL	660/A/A	39.2	9.5	9.0 - 10.5	11.1	32.2	9.4	13	15	646	2601@50	-	BW

GEOLANDAR CV G058

ALL-SEASON **Crossovers/SUVs | Minivans**

An all-season tire that delivers complete confidence to drivers of crossovers and midsize SUVs.



FEATURES AND BENEFITS

COMPETITIVE WET TRACTION
Proprietary tread compound and design for optimal wet grip and confident braking.

SUPERIOR WINTER TRACTION
Engineered with features to stay flexible as temperatures drop.

LONG TREAD LIFE
Optimized contact patch and proprietary tread compound for long-lasting wear.

QUIET RIDE
A distinctive, multi-pitch tread pattern helps reduce road noise.

65,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments & Front Position Tires Used in Staggered Fitments)

32,500-Mile Limited Treadwear Warranty (Rear Position Tires Used in Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/65R16 98H	110105804	SL	740/A/A	22.8	6.5	6.0 - 7.5	8.7	27	6.4	11	12.3	770	1653@51	-	BW
215/70R16 100H	110105805	SL	740/A/A	25.8	6.5	5.5 - 7.0	8.5	27.9	6.4	11	12.6	745	1764@51	-	BW
225/70R16 103H	110105807	SL	740/A/A	27.5	6.5	6.0 - 7.5	8.9	28.4	6.8	12	12.8	732	1929@51	-	BW
235/70R16 106H	110105809	SL	740/A/A	29.7	7	6.0 - 8.0	9.4	29	7	11	13.1	716	2094@51	-	BW
215/60R17 96H	110105811	SL	740/A/A	24.4	6.5	6.0 - 7.5	8.5	27.2	6.4	11	12.5	763	1565@51	-	BW
215/65R17 99H	110105812	SL	740/A/A	24.1	6.5	6.0 - 7.5	8.8	28	6.4	11	12.8	742	1709@51	-	BW
215/70R17 101H	110105813	SL	740/A/A	26.7	6.5	5.5 - 7.0	8.5	28.9	6.4	11	13.2	718	1819@51	-	BW
225/55R17 97V	110105814	SL	740/A/A	25	7	6.0 - 8.0	9.1	26.8	7.2	11	12.3	775	1609@51	-	BW
225/60R17 99H	110105815	SL	740/A/A	25.7	6.5	6.0 - 8.0	8.9	27.6	6.8	11	12.6	753	1709@51	-	BW
225/65R17 102H	110105816	SL	740/A/A	26.6	6.5	6.0 - 8.0	9	28.5	6.8	11	13	730	1874@51	-	BW
235/55R17 99H	110105817	SL	740/A/A	26.1	7.5	6.5 - 8.5	9.5	27.2	7.6	11	12.5	764	1709@51	-	BW
235/60R17 102V	110105818	SL	740/A/A	26.8	7	6.5 - 8.5	9.4	28.1	7	11	12.8	740	1874@51	-	BW
235/65R17 108V	110105819	XL	740/A/A	30.2	7	6.5 - 8.5	9.5	29.1	7	11	13.2	714	2205@50	-	BW
245/65R17 107H	110105820	SL	740/A/A	31	7	7.0 - 8.5	9.8	29.5	7.3	11	13.4	704	2149@51	-	BW
255/60R17 106H	110105821	SL	740/A/A	30	7.5	7.0 - 9.0	10.2	29	7.6	11	13.2	716	2094@51	-	BW
215/55R18 99V	110105823	XL	740/A/A	26.1	7	6.0 - 7.5	8.8	27.3	6.9	11	12.6	760	1709@50	-	BW
225/55R18 98V	110105825	SL	740/A/A	27.2	7	6.0 - 8.0	9	27.8	7.2	11	12.8	748	1653@51	-	BW
225/60R18 100H	110105826	SL	740/A/A	27.6	6.5	6.0 - 8.0	8.9	28.5	6.8	11	13.1	728	1764@51	-	BW
235/50R18 97V	110105828	SL	740/A/A	28.7	7.5	6.5 - 8.5	9.6	27.2	8	11	12.6	763	1609@51	-	BW
235/55R18 100V	110105829	SL	740/A/A	28	7.5	6.5 - 8.5	9.4	28	7.6	11	12.9	741	1764@51	-	BW
235/60R18 107V	110105830	XL	740/A/A	30.4	7	6.5 - 8.5	9.4	29.1	7	11	13.3	715	2149@50	-	BW
235/65R18 106V	110105831	SL	740/A/A	30.5	7	6.5 - 8.5	9.4	30	7	11	13.7	692	2094@51	-	BW
245/60R18 105V	110105847	SL	740/A/A	30	7	7.0 - 8.5	9.6	29.6	7.3	11	13.5	703	2039@51	-	BW
255/55R18 109V	110105833	XL	740/A/A	32.2	8	7.0 - 9.0	10.3	28.9	8.2	11	13.3	718	2271@50	-	BW
255/65R18 111H	110105846	SL	740/A/A	35.5	7.5	7.0 - 9.0	10.3	31	7.7	11	14.1	670	2403@51	-	BW
265/60R18 110V	110105844	SL	740/A/A	34.1	8	7.5 - 9.5	10.7	30.6	8	11	13.9	680	2337@51	-	BW
225/55R19 99V	110105834	SL	740/A/A	28.2	7	6.0 - 8.0	9.1	28.7	7.2	11	13.3	723	1709@51	-	BW
235/50R19 103V	110105835	XL	740/A/A	30.1	7.5	6.5 - 8.5	9.4	28.4	8	11	13.2	732	1929@50	-	BW
235/55R19 105V	110105836	XL	740/A/A	30.3	7.5	6.5 - 8.5	9.5	29.2	7.6	11	13.5	711	2039@50	-	BW
245/55R19 103V	110105848	SL	740/A/A	31.3	7.5	7.0 - 8.5	10	29.7	8	11	13.7	700	1929@51	-	BW
255/50R19 107V	110105838	XL	740/A/A	32.8	8	7.0 - 9.0	10.4	29.1	8.6	11	13.4	714	2149@50	-	BW
255/60R19 113V	110105845	XL	740/A/A	34.2	7.5	7.0 - 9.0	10	31.1	7.7	11	14.2	667	2535@50	-	BW
235/55R20 102V	110105839	SL	740/A/A	30.6	7.5	6.5 - 8.5	9.5	30.1	7.6	11	13.9	691	1874@51	-	BW
245/50R20 102V	110105840	SL	740/A/A	31.7	7.5	7.0 - 8.5	9.9	29.6	8	11	13.8	701	1874@51	-	BW
255/50R20 109V	110105841	XL	740/A/A	34.2	8	7.0 - 9.0	10.2	30.1	8.6	11	13.9	690	2271@50	-	BW
255/55R20 110V	110105842	XL	740/A/A	35.2	8	7.0 - 9.0	10.3	31.2	8.2	11	14.4	666	2337@50	-	BW
265/50R20 107V	110105843	SL	740/A/A	35.7	8.5	7.5 - 9.5	10.7	30.4	9	11	14.1	683	2149@51	-	BW

GEOLANDAR X-CV

ALL-SEASON **Crossovers/SUVs**

The GEOLANDAR X-CV is engineered to perform on today's luxury sport crossovers and SUVs.



FEATURES AND BENEFITS

SUPERIOR HANDLING
Innovative tread pattern with reinforced shoulder provides sharp, sure handling and stability.

ALL-SEASON GRIP
Specially designed tread pattern for confident traction on wet and wintry roads.

QUIET RIDE
A staggered five-pitch block variation reduces noise.

LONG TREAD LIFE
A wider flat contact patch and new advanced silica compound promotes long-lasting, even wear.

50,000-Mile Limited Treadwear Warranty (Non-Staggered Fitments and Front Position Staggered Fitments)

25,000-Mile Limited Treadwear Warranty (Rear Position Staggered Fitments)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
235/60R18 107W	110157027	XL	520/A/A	31.8	7	6.5 - 8.5	9.6	29.1	7.3	11	13.3	714	2149@50	-	BW
255/55R18 109W	110157001	XL	520/A/A	32.6	8	7.0 - 9.0	10.5	28.9	8	11	13.2	720	2271@50	-	BW
225/45R19 96W	110157045	XL	520/A/A	26.7	7.5	7.0 - 8.5	8.8	27	7.4	11	12.6	770	1565@50	-	BW
235/45R19 99W	110157002	XL	520/A/A	25.8	8	7.5 - 9.0	9.3	27.3	7.6	11	12.7	760	1709@50	-	BW
235/55R19 105W	110157003	XL	520/A/A	30	7.5	6.5 - 8.5	9.5	29.1	7.3	11	13.5	713	2039@50	-	BW
235/60R19 103W	110157038	SL	520/A/A	31.4	7	6.5 - 8.5	9.6	30.1	7.3	11	13.8	691	1929@51	-	BW
245/50R19 105W	110157046	XL	520/A/A	31.5	7.5	7.0 - 8.5	10	28.7	7.8	11	13.3	724	2039@50	-	BW
255/45R19 104W	110157047	XL	520/A/A	31.3	8.5	8.0 - 9.5	10.1	28	8.3	11	13	742	1984@50	-	BW
255/50R19 107W	110157004	XL	520/A/A	32.4	8	7.0 - 9.0	10.4	28.9	8	11	13.4	718	2149@50	-	BW
255/55R19 111W	110157005	XL	520/A/A	35.1	8	7.0 - 9.0	10.5	29.9	8	11	13.8	694	2403@50	-	BW
265/50R19 110W	110157006	XL	520/A/A	34.8	8.5	7.5 - 9.5	10.7	29.3	8.3	11	13.5	708	2337@50	-	BW
265/55R19 109W	110157048	SL	520/A/A	36.1	8.5	7.5 - 9.5	10.9	30.4	8.4	11	14	683	2271@51	-	BW
275/50R19 112W	110157029	XL	520/A/A	37.1	8.5	7.5 - 9.5	11.1	29.8	8.7	11	13.7	696	2469@50	-	BW
275/55R19 111W	110157007	SL	520/A/A	39.5	8.5	7.5 - 9.5	11.3	30.7	8.6	11	14.1	676	2403@51	-	BW
235/45R20 100W	110157008	XL	520/A/A	27.6	8	7.5 - 9.0	9.2	28.3	7.6	11	13.3	733	1764@50	-	BW
235/50R20 104W	110157028	XL	520/A/A	29.6	7.5	6.5 - 8.5	9.5	29.3	7.4	11	13.6	709	1984@50	-	BW
245/45R20 103W	110157024	XL	520/A/A	28.9	8	7.5 - 9.0	9.6	28.7	8	11	13.4	725	1929@50	-	BW
255/40R20 101W	110157050	XL	520/A/A	30.5	9	8.5 - 10.0	10.1	28.1	8.5	11	13.2	738	1819@50	-	BW
255/45R20 105W	110157009	XL	520/A/A	31.1	8.5	8.0 - 9.5	10.2	28.9	8.3	11	13.5	719	2039@50	-	BW
255/50R20 109W	110157010	XL	520/A/A	34.8	8	7.0 - 9.0	10.5	29.9	8	11	13.9	694	2271@50	-	BW
255/55R20 110W	110157011	XL	520/A/A	35.1	8	7.0 - 9.0	10.4	30.8	8	11	14.2	674	2337@50	-	BW
265/45R20 108W	110157012	XL	520/A/A	32.8	9	8.5 - 10.0	10.6	29.2	8.6	11	13.6	711	2205@50	-	BW
265/50R20 111W	110157013	XL	520/A/A	35.1	8.5	7.5 - 9.5	10.8	30.3	8.3	11	14	685	2403@50	-	BW
275/40R20 106W	110157014	XL	520/A/A	33.1	9.5	9.0 - 11.0	11	28.6	9.1	11	13.3	727	2094@50	-	BW
275/45R20 110W	110157015	XL	520/A/A	35.3	9	8.5 - 10.5	11	29.6	8.9	11	13.7	702	2337@50	-	BW
275/50R20 113W	110157016	XL	520/A/A	39.2	8.5	7.5 - 9.5	11.2	30.7	8.7	11	14.2	677	2535@50	-	BW
285/45R20 112W	110157025	XL	520/A/A	39.5	9.5	9.0 - 10.5	11.3	30	9.3	12	13.9	693	2469@50	-	BW
295/40R20 110W	110157026	XL	520/A/A	39.3	10.5	10.0 - 11.5	11.9	29.1	9.8	12	13.5	714	2337@50	-	BW
235/45R21 101W	110157051	XL	520/A/A	29.5	8	7.5 - 9.0	9.4	29.3	7.6	11	13.7	708	1819@50	-	BW
235/50R21 101W	110157040	SL	520/A/A	31.5	7.5	6.5 - 8.5	9.5	30.4	7.4	11	14.2	683	1819@51	-	BW
245/45R21 104W	110157030	XL	520/A/A	29.8	8	7.5 - 9.0	9.6	29.7	8	11	13.9	700	1984@50	-	BW
255/40R21 102W	110157052	XL	520/A/A	31.4	9	8.5 - 10.0	10.1	29.2	8.5	11	13.7	712	1874@50	-	BW
265/40R21 105W	110157031	XL	520/A/A	32.2	9.5	9.0 - 10.5	10.6	29.4	8.7	11	13.8	705	2039@50	-	BW
265/45R21 104W	110157017	SL	520/A/A	32.2	9	8.5 - 10.0	10.7	30.2	8.6	11	14.1	688	1984@51	-	BW
275/40R21 107W	110157018	XL	520/A/A	33.5	9.5	9.0 - 11.0	11	29.6	9.1	11	13.9	702	2149@50	-	BW
275/45R21 110W	110157019	XL	520/A/A	35.9	9	8.5 - 10.5	10.9	30.6	8.9	11	14.3	678	2337@50	-	BW
285/40R21 109W	110157032	XL	520/A/A	36.1	10	9.5 - 11.0	11.3	30	9.4	12	14	692	2271@50	-	BW
285/45R21 113W	110157033	XL	520/A/A	38.7	9.5	9.0 - 10.5	11.3	31	9.3	12	14.4	670	2535@50	-	BW

GEOLANDAR X-CV

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
295/35R21 107W	110157020	XL	520/A/A	34.2	10.5	10.0 - 11.5	11.6	29.1	9.8	12	13.6	715	2149@50	-	BW
295/40R21 111W	110157021	XL	520/A/A	37.3	10.5	10.0 - 11.5	11.9	30.2	9.8	12	14.1	688	2403@50	-	BW
315/35R21 111W	110157034	XL	520/A/A	39.2	11	10.5 - 12.5	12.6	29.6	10.4	12	13.9	701	2403@50	-	BW
315/40R21 115W	110157035	XL	520/A/A	41.9	11	10.5 - 12.5	12.6	30.8	10.4	12	14.3	674	2679@50	-	BW
255/45R22 107W	110157042	XL	520/A/A	33.8	8.5	8.0 - 9.5	10	31.1	8.3	11	14.6	667	2149@50	-	BW
265/35R22 102W	110157036	XL	520/A/A	30.6	9.5	9.0 - 10.5	10.6	29.4	8.8	11	13.9	707	1874@50	-	BW
265/40R22 106W	110157022	XL	520/A/A	34.6	9.5	9.0 - 10.5	10.6	30.3	8.7	11	14.2	685	2094@50	-	BW
275/40R22 108W	110157023	XL	520/A/A	35.7	9.5	9.0 - 11.0	10.9	30.6	9.1	11	14.4	679	2205@50	-	BW
HL275/45R22 115W	110157053	XL	520/A/A	37.8	9	8.5 - 10.5	10.8	31.7	8.9	11	14.8	655	2679@50	-	BW
285/35R22 106W	110157037	XL	520/A/A	34.5	10	9.5 - 11.0	11.3	30	9.4	11	14.1	693	2094@50	-	BW

PARADA Spec-X®

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON **Crossovers/SUVs**

A respected tire for those who respect good looks with performance to match.



FEATURES AND BENEFITS

SUPERIOR HANDLING
Sporty tread design and wide profile gives you confident handling on the street.

COMPETITIVE WET TRACTION
Provides tremendous water evacuation for outstanding traction in wet weather.

LONG TREAD LIFE
Special construction and dimpled design help achieve long even wear.

QUIET RIDE
A multi-pitched tread pattern reduces pattern and road noise for a quieter ride.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
225/60R18 100H	110100248	SL	420/A/A	28.6	6.5	6.0 - 8.0	8.9	28.5	6.9	11	13.1	730	1764@51	-	BW
255/40R20 101V	110100224	XL	420/A/A	31.1	9	8.5 - 10.0	10.1	28.1	8.9	11	13.2	739	1819@50	-	BW
255/45R20 105V	110100225	XL	420/A/A	32.2	8.5	8.0 - 9.5	9.9	29.1	8.8	11	13.5	713	2039@50	-	BW
275/40R20 106V	110100236	XL	420/A/A	33.9	9.5	9.0 - 11.0	10.8	28.6	9.6	11	13.3	726	2094@50	-	BW
275/45R20 110V	110100226	XL	420/A/A	34.8	9	8.5 - 10.5	10.6	29.9	9.4	11	13.9	695	2337@50	-	BW
275/55R20 117V	110100231	XL	420/A/A	39.9	8.5	7.5 - 9.5	10.9	31.9	9	11	14.7	650	2833@50	-	BW
285/50R20 112V	110100229	SL	420/A/A	40.4	9	8.0 - 10.0	11.5	31.3	9.5	11	14.4	664	2469@51	-	BW
295/45R20 114V	110100227	XL	420/A/A	40.8	10	9.5 - 11.0	11.6	30.6	10.2	11	14.1	679	2601@50	-	BW
255/35R22 99V	110100238	XL	420/A/A	30.5	9	8.5 - 10.0	10.2	29.1	8.9	11	13.8	713	1709@50	-	BW
265/30R22 97V	110100217	XL	420/A/A	31.4	9.5	9.0 - 10.0	10.2	28.6	9.6	11	13.6	727	1609@50	-	BW
265/35R22 102V	110100218	XL	420/A/A	32.4	9.5	9.0 - 10.5	10.4	29.5	9.3	11	13.9	704	1874@50	-	BW
265/40R22 106V	110100220	XL	420/A/A	35.9	10	9.0 - 10.5	10.6	30.5	9.3	11	14.3	681	2094@50	-	BW
285/30R22 101V	110100239	XL	420/A/A	33.1	10	9.5 - 10.5	11.1	28.9	10.3	11	13.7	720	1819@50	-	BW
285/35R22 106V	110100219	XL	420/A/A	36.6	10	9.5 - 11.0	11	30.1	10	11	14.2	690	2094@50	-	BW
285/40R22 110V	110100240	XL	420/A/A	37.6	10	9.5 - 11.0	11.2	31.1	10	12	14.6	668	2337@50	-	BW
285/45R22 114V	110100222	XL	420/A/A	39.7	9.5	9.0 - 10.5	10.9	32.2	9.8	11	15	645	2601@50	-	BW
305/40R22 114V	110100221	XL	420/A/A	41.7	11	10.0 - 12.0	12.2	31.7	10.7	11	14.8	655	2601@50	-	BW
305/45R22 118V	110100223	XL	420/A/A	44.1	10	9.5 - 11.5	11.5	32.9	10.5	11	15.2	632	2910@50	-	BW
285/40R24 112V	110100242	XL	420/A/A	40.4	10	9.5 - 11.0	11.7	33	10	12	15.5	630	2469@50	-	BW
295/35R24 110V	110100210	XL	420/A/A	43.2	11	10.0 - 11.5	11.9	32.3	10.3	11	15.2	643	2337@50	-	BW
305/35R24 112V	110100211	XL	420/A/A	43.9	11	10.0 - 12.0	12.1	32.7	10.7	11	15.4	636	2469@50	-	BW
315/35R24 114V	110100212	XL	420/A/A	45.6	11	10.5 - 12.5	12.4	32.9	11	11	15.5	632	2601@50	-	BW
325/45R24 116V	110100243	XL	420/A/A	51.4	11	10.0 - 12.0	12.8	35.4	11.2	12	16.5	587	2756@50	-	BW

BluEarth-Van All Season® RY61

SATISFACTION 30 DAY TRIAL GUARANTEED

ALL-SEASON | COMMERCIAL GRADE **Work Vans**

The BluEarth-Van All Season RY61 delivers an optimum balance of long tread wear, excellent durability, and reliable performance.



FEATURES AND BENEFITS

CONFIDENT ALL-SEASON TRACTION
Large center tread blocks for improved road contact and 3D snow sipes for reliable grip in snow and ice.

LONG TREAD LIFE
Optimized tread pattern forms a stable footprint to prevent irregular wear.

DURABLE CONSTRUCTION
Bead protector prevents bead and casing wear while the anti-crack serration defends against sidewall cracking.

FUEL-EFFICIENT TECHNOLOGY
Triple polymer compound formulated for lowered rolling resistance.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
195/70R15C 104/102T	110106102	D	NA	28.2	6	5.0 - 6.0	7.9	25.9	6.4	12	11.8	802	1985@65	1875@65	BW
205/65R15C 102/100T	110106103	C	NA	28.5	6	5.5 - 6.5	8.1	25.5	6.7	12	11.6	816	1875@54	1765@54	BW
195/75R16C 107/105R	110106104	D	NA	30.1	5.5	5.0 - 6.0	7.7	27.5	6.2	13	12.5	755	2150@69	2040@69	BW
205/75R16C 113/111R	110106115	E	NA	31.7	5.5	5.5 - 6.5	8.1	28.1	6.4	13	12.7	738	2535@76	2405@76	BW
215/55R16 97H	110106108	XL	500/A/A	23.1	7	6.0 - 7.5	9	25.4	7.5	11	11.7	818	1609@50	-	BW
225/75R16C 121/120R	110106105	E	NA	37.2	6	6.0 - 7.0	8.9	29.3	7	13	13.2	708	3195@83	3085@83	BW
235/65R16C 121/119R	110106106	E	NA	36.7	7	6.5 - 7.5	9.5	27.9	7.7	13	12.6	744	3195@83	3000@83	BW
LT215/85R16 115/112Q	110106109	E	NA	39	6	5.5 - 7.0	8.7	30.5	6.9	13	13.6	682	2680@80	2470@80	BW
LT225/75R16 115/112R	110106110	E	NA	37.1	6	6.0 - 7.5	8.7	29.3	7.2	13	13.2	708	2680@80	2470@80	BW
LT245/75R16 120/116Q	110106111	E	NA	41	7	6.5 - 8.0	9.8	30.5	7.9	13	13.6	682	3042@80	2778@80	BW
225/55R17C 109/107H	110106107	D	NA	34	7	6.5 - 7.5	9.1	26.8	7.9	11	12.3	776	2270@69	2150@69	BW
LT245/70R17 119/116R	110106114	E	NA	41.5	7	6.5 - 8.0	9.6	30.5	7.9	13	13.8	681	3000@80	2755@80	BW
LT245/75R17 121/118R	110106113	E	NA	44.2	7	6.5 - 8.0	9.8	31.5	7.9	13	14.2	659	3195@80	2910@80	BW

BluEarth WINTER V906

SATISFACTION 30 DAY TRIAL GUARANTEED



WINTER **Performance Cars | Crossovers/SUVs**

The V- & W-speed rated winter performance tire for sedans, CUVs and smaller SUVs.

FEATURES AND BENEFITS

OUTSTANDING SNOW TRACTION
Special new compound and strategically placed 3D sipes enhance snow and ice traction.

EXCELLENT WET PERFORMANCE
Directional tread design with smooth angled grooves channels water away to prevent hydroplaning.

SUPERIOR HANDLING
Optimized tread profile increases road contact for improved handling.

RELIABLE TREAD LIFE
Robust construction and improved road contact area promotes even tread wear.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/50R17 93V	110109617	XL		21.1	6.5	5.5 - 7.5	8.3	25.2	6.7	11	11.7	826	1433@50	-	BW
205/55R17 95V	110109603	XL		22.8	6.5	5.5 - 7.5	8.4	26.2	6.6	11	12.1	793	1521@50	-	BW
215/50R17 95V	110109608	XL		22.9	7	6.0 - 7.5	8.8	25.6	7	10	11.9	812	1521@50	-	BW
215/55R17 98V	110109604	XL		24.9	7	6.0 - 7.5	8.9	26.6	6.9	10	12.2	781	1653@50	-	BW
215/65R17 99V	110109602	SL		24	6.5	6.0 - 7.5	8.6	28.4	6.2	11	12.9	732	1709@51	-	BW
225/45R17 94V	110109607	XL		23.3	7.5	7.0 - 8.5	9	25.2	7.2	10	11.7	824	1477@50	-	BW
225/50R17 98V	110109606	XL		25.3	7	6.0 - 8.0	9.1	26.1	7.3	10	12	796	1653@50	-	BW
225/55R17 101V	110109605	XL		25.7	7	6.0 - 8.0	9.3	27.1	7.3	10	12.4	767	1819@50	-	BW
225/40R18 92W	110109612	XL		22.5	8	7.5 - 9.0	9.1	25.1	7.2	10	11.8	827	1389@50	-	BW
225/45R18 95V	110109616	XL		24.5	7.5	7.0 - 8.5	8.8	26.1	7.3	10	12.1	797	1521@50	-	BW
235/45R18 98V	110109615	XL		25.2	8	7.5 - 9.0	9.3	26.6	7.6	10	12.3	782	1653@50	-	BW
245/40R18 97W	110109614	XL		25	8.5	8.0 - 9.5	9.7	25.9	8	10	12.1	801	1609@50	-	BW
245/45R18 100V	110109613	XL		26.9	8	7.5 - 9.0	9.6	26.9	8	10	12.5	773	1764@50	-	BW
235/40R19 96V	110109636	XL		25.3	8.5	8.0 - 9.5	9.5	26.5	7.6	10	12.4	783	1565@50	-	BW
275/35R19 100V	110109637	XL		28.4	9.5	9.0 - 11.0	10.8	26.8	8.9	10	12.5	775	1764@50	-	BW

BluEarth *WINTER V906 SUV

SATISFACTION 30 DAY TRIAL GUARANTEED

WINTER **Crossovers/SUVs**

The V- & W-speed rated winter performance tire for CUVs and smaller SUVs.



FEATURES AND BENEFITS

OUTSTANDING SNOW TRACTION
Special new compound and strategically placed 3D sipes enhance snow and ice traction.

EXCELLENT WET PERFORMANCE
Directional tread design with smooth angled grooves channels water away to prevent hydroplaning.

SUPERIOR HANDLING
Optimized tread profile increases road contact for improved handling.

RELIABLE TREAD LIFE
Robust construction and improved road contact area promotes even tread wear.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
235/55R17 103V	110109623	XL		26.4	7.5	6.5 - 8.5	9.5	27.4	7.6	10	12.6	757	1929@50	-	BW
225/55R18 102V	110109622	XL		27.1	7	6.0 - 8.0	9.1	28	7.3	10	12.9	743	1874@50	-	BW
235/60R19 103V	110109624	SL		30.6	7	6.5 - 8.5	9.4	30.4	7.2	10	13.9	683	1929@51	-	BW
245/50R19 105V	110109625	XL		31.3	7.5	7.0 - 8.5	9.9	28.9	8.1	10	13.4	718	2039@50	-	BW
235/50R20 104V	110109626	XL		30.6	7.5	6.5 - 8.5	9.6	29.7	7.8	10	13.8	700	1984@50	-	BW
235/55R20 102V	110109620	SL		30.6	7.5	6.5 - 8.5	9.6	30.3	7.6	10	14	685	1874@51	-	BW
265/45R20 108V	110109627	XL		33.3	9	8.5 - 10.0	10.7	29.6	8.9	10	13.8	701	2205@50	-	BW
275/45R20 110V	110109618	XL		34.9	9	8.5 - 10.5	10.9	30	8.9	10	13.9	692	2337@50	-	BW
275/50R20 113V	110109628	XL		37.9	8.5	7.5 - 9.5	11.3	31.2	9.1	10	14.4	665	2535@50	-	BW
305/40R20 112V	110109619	XL		37.5	11	10.0 - 12.0	12.6	30	10.3	10	13.9	693	2469@50	-	BW
285/40R21 109W	110109629	XL		35.6	10	9.5 - 11.0	11.5	30.1	9.8	10	14.1	690	2271@50	-	BW
295/40R21 111V	110109621	XL		37	10.5	10.0 - 11.5	12	30.6	10.1	10	14.2	679	2403@50	-	BW
285/35R22 106W	110109630	XL		35.3	10	9.5 - 11.0	11.3	30.2	9.8	10	14.2	687	2094@50	-	BW
285/40R22 110W	110109631	XL		37.6	10	9.5 - 11.0	11.4	31.3	9.7	10	14.6	663	2337@50	-	BW
315/30R22 107W	110109632	XL		36.7	11	10.5 - 11.5	12.4	29.8	10.8	10	14.1	696	2149@50	-	BW
325/35R22 114W	110109633	XL		40.7	11.5	11.0 - 13.0	13	31.3	11.2	10	14.6	664	2601@50	-	BW

BluEarth *WINTER® V905

WINTER **Performance Cars | Crossovers/SUVs**

A high-traction winter tire that performs best when conditions are at their worst.



FEATURES AND BENEFITS

COMPETITIVE WET TRACTION
Directional tread design quickly channels water away for wet grip and resistance to hydroplaning.

EXCELLENT WINTER TRACTION
Hundreds of adaptive sipes and a flexible tread compound enhance grip in all winter driving conditions.

FUEL EFFICIENT
Special tread compound and construction combine to provide low rolling resistance.

LEADING HANDLING
Designed for responsive handling throughout winter's worst weather.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/40R17 87V	110190690	XL		21.7	7.5	7.0 - 8.5	8.6	24	7.4	10	11.2	865	1201@50	-	BW
215/45R17 91V	110190606	XL	NA	22.3	7	7.0 - 8.0	8.5	24.9	7	11	11.6	835	1356@50	-	BW
235/45R17 97V	110190612	XL	NA	24.7	8	7.5 - 9.0	9.4	25.5	7.6	10	11.8	814	1609@50	-	BW
215/40R18 89V	110190617	XL		22.3	7.5	7.0 - 8.5	8.5	25	7.4	10	11.7	831	1279@50	-	BW
215/50R18 92V	110190688	SL		25.2	7	6.0 - 7.5	8.9	26.8	7	11	12.4	776	1389@51	-	BW
215/55R18	110190676	XL		27.7	7	6.0 - 7.5	8.9	27.6	7	11	12.8	752	1709@50	-	BW
235/40R18 95W	110190624	XL	NA	25.4	8.5	8.0 - 9.5	9.6	25.6	7.6	10	11.9	813	1521@50	-	BW
235/50R18 101V	110190626	XL	NA	27.3	7.5	6.5 - 8.5	9.4	27.5	7.6	10	12.7	756	1819@50	-	BW
245/50R18 104V	110190630	XL	NA	28.2	7.5	7.0 - 8.5	9.8	27.9	8	10	12.9	744	1984@50	-	BW
255/40R18 99V	110190632	XL	NA	30	9	8.5 - 10.0	10.2	26.4	8.7	10	12.3	787	1709@50	-	BW
265/35R18 97V	110190635	XL		27.3	9.5	9.0 - 10.5	10.6	25.5	9.2	10	11.9	814	1609@50	-	BW
225/40R19 93W	110190678	XL		24.6	8	7.5 - 9.0	9	26.3	7.7	10	12.4	789	1433@50	-	BW
225/45R19 96V	110190637	XL	NA	24.7	7.5	7.0 - 8.5	8.7	27.2	7.3	11	12.7	763	1565@50	-	BW
225/55R19 99V	110190638	SL	NA	28.9	7	6.0 - 8.0	9.2	29	7.3	11	13.4	716	1709@51	-	BW
235/35R19 91W	110190679	XL		24.7	8.5	8.0 - 9.5	9.5	25.5	8.1	10	12	814	1356@50	-	BW
235/45R19 99V	110190639	XL	NA	27.3	8	7.5 - 9.0	9.3	27.7	7.6	10	12.9	751	1709@50	-	BW
235/55R19 101V	110190640	SL	NA	30	7.5	6.2 - 8.5	9.6	29.5	7.6	10	13.6	704	1819@51	-	BW
245/40R19 98V	110190641	XL	NA	30	8.5	8.0 - 9.5	9.7	27	8.3	10	12.6	768	1653@50	-	BW
245/45R19 102W	110190642	XL	NA	28.2	8	7.5 - 9.0	9.6	28	8	10	13	741	1874@50	-	BW
245/50R19 105V	110190670	XL		37.1	7.5	7.0 - 8.5	9.7	28.9	8.2	10	13.4	718	2039@50	-	BW
255/40R19 100V	110190643	XL	NA	27.3	9	8.5 - 10.0	10.1	27.4	8.4	10	12.8	757	1764@50	-	BW
255/45R19 104V	110190644	XL	NA	30	8.5	8.0 - 9.5	10	28.3	8.6	10	13.1	733	1984@50	-	BW
255/50R19 107V	110190645	XL	NA	30	8	7.0 - 9.0	10.5	29.2	8.5	10	13.5	711	2149@50	-	BW
265/50R19 110V	110190647	XL		30	8.5	7.5 - 9.5	10.8	29.8	8.8	10	13.7	697	2337@50	-	BW
275/45R19 108V	110190649	XL		30	9	8.5 - 10.5	10.8	29.1	9.3	10	13.4	715	2205@50	-	BW
245/40R20 99V	110190652	XL		29.1	8.5	8.0 - 9.5	9.7	28	8.3	10	13.1	742	1709@50	-	BW
255/50R20 109V	110190654	XL	NA	30	8	7.0 - 9.0	10.4	30.3	8.4	10	14	685	2271@50	-	BW
265/35R20 99V	110190655	XL	NA	29.8	9.5	9.0 - 10.5	10.6	27.6	8.9	10	12.9	754	1709@50	-	BW
265/50R20 111V	110190684	XL		35.4	8.5	7.5 - 9.5	10.8	30.7	8.8	10	14.2	676	2403@50	-	BW
275/40R20 106V	110190657	XL	NA	32.2	9.5	9.0 - 11.0	11	28.9	9.1	10	13.5	718	2094@50	-	BW
315/35R20 110V	110190660	XL	NA	35.5	11	10.5 - 12.5	12.5	29	10.6	10	13.5	716	2337@50	-	BW
245/40R21 100V	110190661	XL	NA	30	8.5	8.0 - 9.5	9.7	29	8.3	10	13.6	716	1764@50	-	BW
265/40R21 105V	110190662	XL	NA	30.6	9.5	9.0 - 10.5	10.6	29.7	9.1	10	13.9	699	2039@50	-	BW
285/35R21 105V	110190663	XL	NA	32.6	10	9.5 - 11.0	11.3	29.2	9.5	10	13.7	712	2039@50	-	BW
295/35R21 107V	110190664	XL	NA	33.7	10.5	10.0 - 11.5	11.5	29.3	9.8	10	13.7	710	2149@50	-	BW

iceGUARD iG53

WINTER **Passenger Cars**

An advanced studless winter tire for confident traction on ice and snow when you need it most.



FEATURES AND BENEFITS

EXCELLENT SNOW TRACTION
Advanced tread design provides hundreds of biting edges for confident snow traction.

COMPETITIVE ICE TRACTION
Absorptive compound improves grip in icy conditions and provides greater resistance to wear.

FUEL EFFICIENT
Unique construction and compound combine create a fuel efficient design.

PREDICTABLE HANDLING
Distinctive uni-directional tread design enhances road contact for better handling in all conditions.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
175/70R14 84T	110115320	SL	NA	16	5	4.5 - 6.0	7	23.9	5.8	11	10.9	868	1102@51	-	BW
195/65R15 91T	110115325	SL	NA	19	6	5.5 - 7.0	8	25.2	6.5	11	11.5	823	1356@51	-	BW
185/55R16 83H	110115353	SL		17.4	6	5.0 - 6.5	7.6	24.2	6.5	11	11.2	858	1074@51	-	BW
195/50R16 84H	110115326	SL	NA	18.1	6	5.5 - 7.0	7.8	23.7	6.7	11	11	877	1102@51	-	BW
205/65R16 95T	110115329	SL	NA	22.6	6	5.5 - 7.5	8.3	26.6	6.8	11	12.1	782	1521@50	-	BW
225/60R16 98T	110115332	SL	NA	24.5	6.5	6.0 - 8.0	8.9	26.9	7.5	12	12.2	774	1653@51	-	BW
205/50R17 93H	110115333	XL	NA	23.1	6.5	5.5 - 7.5	8.3	25.2	7.2	11	11.7	826	1433@50	-	BW
215/65R17 99T	110115336	SL	NA	25.6	6.5	6.0 - 7.5	8.7	28	7.2	11	12.8	741	1709@51	-	BW
225/45R17 91H	110115337	SL	NA	23.1	7.5	7.0 - 8.5	8.8	25.1	7.8	11	11.7	828	1356@51	-	BW
235/45R17 97H	110115340	XL	NA	25.8	8	7.5 - 9.0	9.3	25.6	8.2	12	11.8	813	1609@50	-	BW
245/45R17 99H	110115342	XL	NA	26.9	8	7.5 - 9.0	9.5	25.9	8.7	12	12	803	1709@50	-	BW
215/55R18 95H	110115343	SL	NA	25.8	7	6.0 - 7.5	8.9	27.5	7.5	11	12.7	756	1521@51	-	BW
225/40R18 92H	110115344	XL	NA	22.7	8	7.5 - 9.0	9.1	25.1	7.8	11	11.8	827	1389@50	-	BW
225/45R18 95H	110115345	XL	NA	25.1	7.5	7.0 - 8.5	8.9	25.9	7.8	11	12.1	802	1521@51	-	BW
225/50R18 95H	110115346	SL	NA	26	7	6.0 - 8.0	9.1	27	7.8	11	12.5	769	1521@51	-	BW
235/45R18 94H	110115347	SL	NA	24.9	8	7.5 - 9.0	9.3	26.5	8.2	12	12.3	785	1477@51	-	BW
245/40R18 97H	110115349	XL	NA	26.7	8.5	8.0 - 9.5	9.6	25.9	8.7	12	12.1	802	1609@50	-	BW
235/50R20 104T	110115354	XL		31.4	7.5	6.5 - 8.5	9.7	29.2	8.2	12	13.6	712	1984@50	-	BW
235/50R21 101T	110115355			30	7.5	6.5 - 8.5	9.6	30.3	8.2	12	14.1	686	1819@51	-	BW

iceGUARD® G075

WINTER **Crossovers/SUVs | Trucks | Minivans**

The ultimate snowshoes for maximum winter grip in your SUV, crossover or light truck.



FEATURES AND BENEFITS

EXCELLENT WINTER TRACTION
Three-dimensional sipes and micro-edges provide biting edges that grip the snow.

ON-ROAD DURABILITY
Durable tread compound resists wear and provides more stability for CUVs and SUVs.

FUEL EFFICIENT
Special construction and compound create a fuel-efficient design.

PRECISE HANDLING
Distinctive uni-directional tread design enhances road contact for better handling in all conditions.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
205/70R16 97T	110175139	SL	NA	26.1	6	5.0 - 7.0	8.2	27.2	6.7	13	12.4	764	1609@51	-	BW
215/65R16 98T	110175137	SL	NA	23.8	6.5	6.0 - 7.5	8.7	26.9	7	13	12.2	774	1653@51	-	BW
225/70R16 103T	110175101	SL	NA	28.9	6.5	6.0 - 7.5	8.8	28.4	7.4	13	12.8	732	1929@51	-	BW
235/70R16 106T	110175102	SL	NA	32.4	7	6.0 - 8.0	9.3	28.9	7.7	13	13	718	2094@51	-	BW
265/70R16 112S	110175103	SL	NA	35.7	8	7.0 - 9.0	10.6	30.4	8.7	14	13.6	683	2469@51	-	BW
215/60R17 96T	110175138	SL	NA	26.3	6.5	6.0 - 7.5	8.7	27.1	7	13	12.4	766	1565@51	-	BW
225/60R17 99T	110175104	SL	NA	26.7	6.5	6.0 - 8.0	8.8	27.7	7.3	13	12.7	750	1709@51	-	BW
225/65R17 102T	110175105	SL	NA	29.3	6.5	6.0 - 8.0	8.9	28.5	7.3	13	13	730	1874@51	-	BW
235/60R17 102T	110175106	SL	NA	28.7	7	6.5 - 8.5	9.4	28	7.7	13	12.8	742	1874@51	-	BW
235/65R17 108T	110175107	XL	NA	32.2	7	6.5 - 8.5	9.5	29	7.7	13	13.2	717	2205@50	-	BW
245/65R17 107T	110175108	SL	NA	33.3	7	7.0 - 8.5	9.8	29.4	8	13	13.3	707	2149@51	-	BW
245/70R17 110T	110175109	SL	NA	34.8	7	6.5 - 8.0	9.6	30.5	8	13	13.8	681	2337@51	-	BW
255/70R17 112S	110175143	SL	NA	36.8	7.5	6.5 - 8.5	10.3	31.1	8.3	13	14	669	2469@51	-	BW
265/65R17 112S	110175110	SL	NA	37.5	8	7.5 - 9.5	10.7	30.4	8.7	13	13.7	683	2469@51	-	BW
265/70R17 115S	110175111	SL	NA	38.8	8	7.0 - 9.0	10.6	31.6	8.7	14	14.2	658	2679@51	-	BW
LT315/70R17 121/118S	110175147	E	NA	61.8	9.5	8.0 - 10.5	12.8	34.5	10.3	18	15.3	602	3195@65	2910@65	BW
225/60R18 100T	110175113	SL	NA	28.9	6.5	6.0 - 8.0	8.9	28.5	7.3	13	13.1	729	1764@51	-	BW
235/60R18 107T	110175115	XL	NA	31.7	7	6.5 - 8.5	9.3	29	7.7	13	13.3	716	2149@50	-	BW
235/65R18 106T	110175116	SL	NA	32.8	7	6.5 - 8.5	9.3	29.9	7.7	13	13.6	694	2094@51	-	BW
245/60R18 105T	110175117	SL	NA	34	7	7.0 - 8.5	9.7	29.4	8	13	13.4	706	2039@51	-	BW
255/55R18 109T	110175118	XL	NA	35.5	8	7.0 - 9.0	10.4	29.1	8.9	13	13.3	714	2271@50	-	BW
255/60R18 112T	110175119	XL	NA	35.1	7.5	7.0 - 9.0	10.2	30	8.3	13	13.7	692	2469@50	-	BW
255/70R18 113T	110175141	SL		39.1	7.5	6.5 - 8.5	10.1	32.1	8.3	13	14.5	647	2535@51	-	BW
265/60R18 110S	110175120	SL	NA	37.5	8	7.5 - 9.5	10.6	30.4	8.7	13	13.8	683	2337@51	-	BW
265/70R18 116T	110175155	SL		41.2	8	7.0 - 9.0	10.6	32.4	8.7	14	14.6	640	2756@51	-	BW
285/60R18 116T	110175121	SL	NA	42.1	8.5	8.0 - 10.0	11.4	31.4	9.3	13	14.2	661	2756@51	-	BW
225/55R19 99T	110175122	SL	NA	30	7	6.0 - 8.0	9.1	28.8	7.9	13	13.3	721	1709@51	-	BW
235/50R19 99T	110175145	SL		30.4	7.5	6.5 - 8.5	9.7	28.2	8.3	13	13.1	736	1709@51	-	BW
235/55R19 101T	110175123	SL	NA	30.6	7.5	6.5 - 8.5	9.6	29.1	8.3	13	13.4	714	1819@51	-	BW
245/55R19 103T	110175124	SL	NA	33.1	7.5	7.0 - 8.5	9.9	29.6	8.6	14	13.6	703	1929@51	-	BW
265/50R19 110T	110175127	XL	NA	35.5	8.5	7.5 - 9.5	10.9	29.3	9.3	14	13.5	708	2337@50	-	BW
245/50R20 102T	110175129	SL	NA	33.1	7.5	7.0 - 8.5	9.8	29.6	8.6	14	13.8	701	1874@51	-	BW
255/45R20 105T	110175156	XL		34.2	8.5	8.0 - 9.5	10.1	28.9	8.9	14	13.5	719	2039@50	-	BW
255/50R20 109T	110175130	XL	NA	35.3	8	7.0 - 9.0	10.2	30	9	14	13.9	692	2271@50	-	BW
255/55R20 110T	110175157	XL		38.8	8	7.0 - 9.0	10.3	30.9	9	14	14.3	672	2337@50	-	BW
265/50R20 111T	110175131	XL	NA	37.9	8.5	7.5 - 9.5	10.9	30.3	9.3	14	14	685	2403@50	-	BW
265/60R20 112T	110175158			41.1	8	7.5 - 9.5	10.7	32.3	8.7	14	14.8	643	2469@51	-	BW
275/60R20 116S	110175140	XL		42.9	8	7.5 - 9.5	11	32.8	9.6	14	15	633	2756@50	-	BW

iceGUARD® G075

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
285/50R20 112T	110175135	SL	NA	41.4	9	8.0 - 10.0	11.6	31.1	10	14	14.3	669	2469@51	-	BW
255/40R21 102T	110175159	XL		32.5	9	8.5 - 10.0	10.2	29.1	8.9	14	13.7	713	1874@50	-	BW
275/50R22 115T	110175160	XL		42.9	8.5	7.5 - 9.5	11.2	32.9	9.6	14	15.2	632	2679@50	-	BW

iceGUARD® iG51v

WINTER **Crossovers/SUVs | Trucks**

Long-lasting durability and confidence-inspired handling for crossovers, SUVs and trucks.



FEATURES AND BENEFITS

COMPETITIVE WET TRACTION
Advanced shoulder and circumferential grooves work hard to expel snow and evacuate water.

SUPERIOR WINTER TRACTION
Engineered with grooves and sipes that work in tandem to expel snow and improve traction.

CAPABLE HANDLING
A variable angle center rib increases block rigidity for better handling in all conditions.

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (IN)	TREAD DEPTH (32/IN)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDE WALL TYPE
					MEASURED (IN)	APPROVED (IN)	OVERALL WIDTH (IN)	OVERALL DIAMETER (IN)			STATIC RADIUS (IN)	REV PER MILE	SINGLE	DUAL	
215/70R15 98T	110151101	SL	NA	24.1	6.5	5.5 - 7.0	8.7	26.9	7	13	12.1	774	1653@51	-	BW



Yokohama Tire Corporation | 800.423.4544 | yokohamatire.com
Commercial Customer Service: 800.423.4544, ext. 2, opt. 2 | Credit Department: ext. 3977
Consumer Affairs: 800.722.9888 | Commercial Customer Service Dealer Order Fax: 800.455.9656

CMS-0875-1122
© 2022 Yokohama Tire Corporation